

TMSGProperty component

[Properties](#) [Methods](#)

Unit

[smmsg](#)

Description

TMSGProperty represents a property/attribute in a [message](#).

AsString property

Applies to

[TMSGProperty](#) component

Declaration

```
property AsString: WideString;
```

Description

Returns the text value of the property/attribute.

Category property

Applies to

[TMSGProperty](#) component

Declaration

property Category: [TMSGPropertyCategory](#);

Description

Returns the category for property/attribute.

SubProperties property

Applies to

[TMSGProperty](#) component

Declaration

```
property SubProperties: TMSGProperties;
```

Description

Some properties/attributes (for example, file attachments, forwarded messages etc) can have the list of sub-properties.

This collection of sub-properties stored in `SubProperties`

TagID property

Applies to

[TMSGProperty](#) component

Declaration

```
property TagID: Integer;
```

Description

Every property/attribute have the TagID which depends from property/attribute [type](#) and functional part.

The list of tags and their functional description you may find at

<http://www.mapi33.adexsolutions.com/docs/MAPI33.Tags.html>

The short list of supported tags:

Member Name Description

PR_1_LINKED_MESSAGE_ENTRYID 0x780E0102

PR_2_LINKED_MESSAGE_ENTRYID 0x78100102

PR_7BIT_DISPLAY_NAME Contains a 7-bit ASCII version of a messaging user's name.

PR_AB_DEFAULT_DIR Contains the entry identifier of the address book container that is to be shown to the user first.

PR_AB_DEFAULT_PAB Contains the entry identifier of the address book container that is to be used as the personal address book.

PR_AB_PROVIDER_ID Contains an address book provider's Guid structure.

PR_AB_PROVIDERS Contains a list of identifiers for address book providers in the current profile.

PR_AB_SEARCH_PATH Contains a list of entry identifiers for address book containers that are to be searched to resolve names.

PR_AB_SEARCH_PATH_UPDATE Contains a list of entry identifiers for address book containers explicitly configured by the user.

PR_ABSTRACT 0x3FDA001E

PR_ABSTRACT_A 0x3FDA001E
PR_ABSTRACT_W 0x3FDA001F
PR_ACCEPT_MALFORMED_821_ADRS 0x01F00003
PR_ACCESS Contains a bitmask of flags indicating the operations a client application can perform on the open object.
PR_ACCESS_LEVEL Contains a bitmask of flags indicating the level at which a client application can access the open object.
PR_ACCOUNT Contains the recipient's account name.
PR_ACCOUNT_A Contains the recipient's account name.
PR_ACCOUNT_W Contains the recipient's account name.
PR_ACKNOWLEDGEMENT_MODE Contains the identifier of the mode for message acknowledgment.
PR_ACL_DATA Contains the binary form of the PR_ACL_TABLE object, which is the access control list (ACL) table for a folder.
PR_ACL_TABLE Contains a table consisting of all the access control lists (ACLs) applied to a folder.
PR_ACTION 0x10800003
PR_ACTION_DATE 0x10820040
PR_ACTION_FLAG 0x10810003
PR_ACTIVE_USER_ENTRYID 0x66520102
PR_ADATP3_DEFAULT 0x3DE6000B
PR_ADDITIONAL_REN_ENTRYIDS 0x36D81102
PR_ADDR_CC 0x0E98001F
PR_ADDR_CC_A 0x0E98001E
PR_ADDR_CC_W 0x0E98001F
PR_ADDR_TO 0x0E97001F
PR_ADDR_TO_A 0x0E97001E
PR_ADDR_TO_W 0x0E97001F
PR_ADDRBOOK_FOR_LOCAL_SITE_ENTRYID 0x66260102
PR_ADDRBOOK_MID 0x674F0014
PR_ADDRESS_BOOK_DISPLAY_NAME 0x3FE8001E
PR_ADDRESS_BOOK_ENTRYID Contains the name-service entry identifier of a directory object referring to a public folder.
PR_ADDRESS_REWRITE 0x01EC0003
PR_ADDRESSING_NEVER_FAILS 0x01A50003
PR_ADDRTYPE Contains the messaging user's e-mail address type, such as Simple Mail Transfer Protocol (SMTP).

PR_ADDRTYPE_A Contains the messaging user's e-mail address type, such as Simple Mail Transfer Protocol (SMTP).

PR_ADDRTYPE_W Contains the messaging user's e-mail address type, such as Simple Mail Transfer Protocol (SMTP).

PR_ADMID 0x670C001E

PR_ADMIN_DISPLAY_NAME Contains the display name shown by admin.

PR_ADMIN_DISPLAY_NAME_A Contains the display name shown by admin.

PR_ADMIN_DISPLAY_NAME_W Contains the display name shown by admin.

PR_ADMIN_MDB_GUID 0x66FF0102

PR_ADMIN_NOTIFICATION 0x01020003

PR_ADMIN_SECURITY_DESCRIPTOR Contains the Administrator permissions on a folder. By default, they are not set on individual folders, but are inherited from the root folder. However, if you set specific Administrator permissions on a folder, this property is added and replicated with that folder.

PR_ADMIN_SECURITY_DESCRIPTOR_AS_XML 0x0E6B001E

PR_ADMIN_SECURITY_DESCRIPTOR_AS_XML_A 0x0E6B001E

PR_ADMIN_SECURITY_DESCRIPTOR_AS_XML_W 0x0E6B001F

PR_ADMINISTRATOR_EMAIL 0x0100101E

PR_ADVERTISE_SMTP_EXTENSIONS 0x01EB0003

PR_AGE_LIMIT 0x0E670102

PR_AGENT_FOLDER_ENTRYID 0x78310102

PR_AGENT_OWNER 0x780A0102

PR_AGENT_STORE_ENTRYID 0x780F0102

PR_AGING_GRANULARITY 0x36EE0003

PR_AGING_PERIOD 0x36EC0003

PR_ALTERNATE_RECIPIENT Contains a list of entry identifiers for alternate recipients designated by the originally intended recipient.

PR_ALTERNATE_RECIPIENT_ALLOWED Contains true if the sender permits autoforwarding of this message.

PR_ALWAYS_USE_ETRN 0x01EF0003

PR_ALWAYS_USE_TURN 0x01FC0003

PR_ANR Contains a string value for use in a property restriction on an address book container contents table.

PR_ANR_A Contains a string value for use in a property restriction on an address book container contents table.

PR_ANR_W Contains a string value for use in a property restriction on an address book container contents table.

PR_ANTIVIRUS_SCAN_INFO 0x0E88001E

PR_ANTIVIRUS_SCAN_STATUS 0x0E870003

PR_ANTIVIRUS_VENDOR 0x0E85001E

PR_ANTIVIRUS_VERSION 0x0E860003

PR_APPEND_DEFAULT_DOMAIN 0x01E90003

PR_ARCHIVE_LEVEL 0x01B30003

PR_ARRIVAL_TIME Contains the date and time a specific message arrived at a gateway.

PR_ARTICLE_NUM_NEXT 0x67510003

PR_ASSERT_STATE 0x01960003

PR_ASSIGNED_ACCESS 0x66FF0003

PR_ASSISTANT Contains the name of the recipient's administrative assistant.

PR_ASSISTANT_A Contains the name of the recipient's administrative assistant.

PR_ASSISTANT_TELEPHONE_NUMBER Contains the telephone number of the recipient's administrative assistant.

PR_ASSISTANT_TELEPHONE_NUMBER_A Contains the telephone number of the recipient's administrative assistant.

PR_ASSISTANT_TELEPHONE_NUMBER_W Contains the telephone number of the recipient's administrative assistant.

PR_ASSISTANT_W Contains the name of the recipient's administrative assistant.

PR_ASSOC_CONTENT_COUNT Contains the total number of associated messages in the folder.

PR_ASSOC_MESSAGE_SIZE Contains the total size of all associated messages in a folder.

PR_ASSOC_MESSAGE_SIZE_EXTENDED Contains the total size of all associated messages in a folder.

PR_ASSOC_MSG_W_ATTACH_COUNT Contains the total number of associated messages with attachment.

PR_ASSOCIATED 0x67AA000B

PR_ATTACH_ADDITIONAL_INFO Provides file type information for a

non-Windows attachment.

PR_ATTACH_CONTENT_BASE Contains the content base header of a MIME message attachment.

PR_ATTACH_CONTENT_BASE_A Contains the content base header of a MIME message attachment.

PR_ATTACH_CONTENT_BASE_W Contains the content base header of a MIME message attachment.

PR_ATTACH_CONTENT_DISPOSITION 0x3716001F

PR_ATTACH_CONTENT_ID Contains the content identification header of a MIME message attachment.

PR_ATTACH_CONTENT_ID_A Contains the content identification header of a MIME message attachment.

PR_ATTACH_CONTENT_ID_W Contains the content identification header of a MIME message attachment.

PR_ATTACH_CONTENT_LOCATION Contains the content location header of a MIME message attachment.

PR_ATTACH_CONTENT_LOCATION_A Contains the content location header of a MIME message attachment.

PR_ATTACH_CONTENT_LOCATION_W Contains the content location header of a MIME message attachment.

PR_ATTACH_DATA_BIN Contains binary attachment data typically accessed through the COM IStream interface.

PR_ATTACH_DATA_OBJ Contains an attachment object typically accessed through the OLE IStorage interface.

PR_ATTACH_DISPOSITION 0x3716001E

PR_ATTACH_DISPOSITION_A 0x3716001E

PR_ATTACH_DISPOSITION_W 0x3716001F

PR_ATTACH_ENCODING Contains an ASN.1 object identifier specifying the encoding for an attachment.

PR_ATTACH_EXTENSION Contains a filename extension that indicates the document type of an attachment.

PR_ATTACH_EXTENSION_A Contains a filename extension that indicates the document type of an attachment.

PR_ATTACH_EXTENSION_W Contains a filename extension that indicates the document type of an attachment.

PR_ATTACH_FILENAME Contains an attachment's base filename and extension, excluding path.

PR_ATTACH_FILENAME_A Contains an attachment's base filename and extension, excluding path.

PR_ATTACH_FILENAME_W Contains an attachment's base filename and extension, excluding path.

PR_ATTACH_FLAGS Contains a bitmask of flags for an attachment.

PR_ATTACH_ID 0x3F880014

PR_ATTACH_LONG_FILENAME Contains an attachment's long filename and extension, excluding path.

PR_ATTACH_LONG_FILENAME_A Contains an attachment's long filename and extension, excluding path.

PR_ATTACH_LONG_FILENAME_W Contains an attachment's long filename and extension, excluding path.

PR_ATTACH_LONG_PATHNAME Contains an attachment's fully qualified long path and filename.

PR_ATTACH_LONG_PATHNAME_A Contains an attachment's fully qualified long path and filename.

PR_ATTACH_LONG_PATHNAME_W Contains an attachment's fully qualified long path and filename.

PR_ATTACH_METHOD Contains a MAPI-defined constant representing the way the contents of an attachment can be accessed.

PR_ATTACH_MIME_SEQUENCE Contains the MIME sequence number of a MIME message attachment.

PR_ATTACH_MIME_TAG Contains formatting information about a Multipurpose Internet Mail Extensions (MIME) attachment.

PR_ATTACH_MIME_TAG_A Contains formatting information about a Multipurpose Internet Mail Extensions (MIME) attachment.

PR_ATTACH_MIME_TAG_W Contains formatting information about a Multipurpose Internet Mail Extensions (MIME) attachment.

PR_ATTACH_NETSCAPE_MAC_INFO 0x37150102

PR_ATTACH_NUM Contains a number that uniquely identifies the attachment within its parent message.

PR_ATTACH_ON_ASSOC_MSG_COUNT Contains the total number of attachments on associated messages.

PR_ATTACH_ON_NORMAL_MSG_COUNT Contains the total number of attachments on normal messages.

PR_ATTACH_PATHNAME Contains an attachment's fully qualified path and filename.

PR_ATTACH_PATHNAME_A Contains an attachment's fully qualified path and filename.

PR_ATTACH_PATHNAME_W Contains an attachment's fully qualified path and filename.

PR_ATTACH_RENDERING Contains a Microsoft Windows metafile with rendering information for an attachment.

PR_ATTACH_SIZE Contains the sum, in bytes, of the sizes of all properties on an attachment.

PR_ATTACH_TAG Contains an ASN.1 object identifier specifying the application that supplied an attachment.

PR_ATTACH_TRANSPORT_NAME Contains the name of an attachment file modified so that it can be correlated with TNEF messages.

PR_ATTACH_TRANSPORT_NAME_A Contains the name of an attachment file modified so that it can be correlated with TNEF messages.

PR_ATTACH_TRANSPORT_NAME_W Contains the name of an attachment file modified so that it can be correlated with TNEF messages.

PR_ATTACH_VIRUS_SCAN_INFO 0x0E960102

PR_ATTACH_X400_XP 0x7CDB000B

PR_ATTACHMENT_CONTACTPHOTO 0x7FFF000B

PR_ATTACHMENT_FLAGS 0x7FFD0003

PR_ATTACHMENT_HIDDEN 0x7FFE000B

PR_ATTACHMENT_LINKID 0x7FFA0003

PR_ATTACHMENT_X400_PARAMETERS Was originally meant to contain an ASN.1 object identifier specifying how the attachment should be handled during transmission.

PR_ATTR_HIDDEN 0x10F4000B

PR_ATTR_READONLY 0x10F6000B

PR_ATTR_SYSTEM 0x10F5000B

PR_AUTHORIZING_USERS Contains a list of entry identifiers for users who have authorized the sending of a message.

PR_AUTO_ADD_NEW_SUBS 0x65E5000B

PR_AUTO_FORWARD_COMMENT Contains a comment added by the autoforwarding agent.

PR_AUTO_FORWARD_COMMENT_A Contains a comment added by the autoforwarding agent.

PR_AUTO_FORWARD_COMMENT_W Contains a comment added by the autoforwarding agent.

PR_AUTO_FORWARDED Contains true if an automatic agent has forwarded a message.

PR_AUTO_RESET 0x670C1048

PR_AUTO_RESPONSE_SUPPRESS 0x3FDF0003

PR_AVERAGE_TRANSMISSION_TIME Contains the average transmission time (in seconds) for this server.

PR_BACKFILL_ENTRY_COUNT Contains the number of backfill entries for this public folder.

PR_BACKFILL_FLAGS 0x66EA0003

PR_BACKFILL_ID Contains 22 byte (16-byte GUID + 6-byte Globcnt) Backfill identification number. Several entries may have the same ID which means they were sent in one request to the same server.

PR_BACKFILL_RANKING Contains a ranking (start with 1) that helps us to choose which server to issue a backfill request against. If two servers both have a change we need, we will pick the server with the smaller backfill priority. If the property is not present the server is inactive.

PR_BACKFILL_TIMEOUT 0x66F00040

PR_BEEPER_TELEPHONE_NUMBER Contains the recipient's pager telephone number.

PR_BEEPER_TELEPHONE_NUMBER_A Contains the recipient's pager telephone number.

PR_BEEPER_TELEPHONE_NUMBER_W Contains the recipient's pager telephone number.

PR_BEING_DELETED Is this Replica of this PF in the process of being deleted.

PR_BILATERAL_DEFAULT 0x3DEA000B

PR_BILATERAL_INFO 0x3FDC0102

PR_BIRTHDAY Contains the date of the recipient's birthday.

PR_BODY Contains the message text.

PR_BODY_A Contains the message text.

PR_BODY_CONTENT_ID 0x1015001E

PR_BODY_CONTENT_ID_A 0x1015001E

PR_BODY_CONTENT_ID_W 0x1015001F

PR_BODY_CONTENT_LOCATION 0x1014001E

PR_BODY_CONTENT_LOCATION_A 0x1014001E

PR_BODY_CONTENT_LOCATION_W 0x1014001F

PR_BODY_CRC Contains a circular redundancy check (CRC) value on the

message text.

PR_BODY_HTML Contains the Hypertext Markup Language (HTML) version of the message text.

PR_BODY_HTML_A Contains the Hypertext Markup Language (HTML) version of the message text.

PR_BODY_HTML_W Contains the Hypertext Markup Language (HTML) version of the message text.

PR_BODY_W Contains the message text.

PR_BUSINESS_ADDRESS_CITY Contains the name of the recipient's locality, such as the town or city.

PR_BUSINESS_ADDRESS_CITY_A Contains the name of the recipient's locality, such as the town or city.

PR_BUSINESS_ADDRESS_CITY_W Contains the name of the recipient's locality, such as the town or city.

PR_BUSINESS_ADDRESS_COUNTRY Contains the name of the recipient's country/region.

PR_BUSINESS_ADDRESS_COUNTRY_A Contains the name of the recipient's country/region.

PR_BUSINESS_ADDRESS_COUNTRY_W Contains the name of the recipient's country/region.

PR_BUSINESS_ADDRESS_POST_OFFICE_BOX Contains the number or identifier of the recipient's post office box.

PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_A Contains the number or identifier of the recipient's post office box.

PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_W Contains the number or identifier of the recipient's post office box.

PR_BUSINESS_ADDRESS_POSTAL_CODE Contains the postal code for the recipient's postal address.

PR_BUSINESS_ADDRESS_POSTAL_CODE_A Contains the postal code for the recipient's postal address.

PR_BUSINESS_ADDRESS_POSTAL_CODE_W Contains the postal code for the recipient's postal address.

PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE Contains the name of the recipient's state or province.

PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_A Contains the name of the recipient's state or province.

PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_W Contains the

name of the recipient's state or province.

PR_BUSINESS_ADDRESS_STREET Contains the recipient's street address.

PR_BUSINESS_ADDRESS_STREET_A Contains the recipient's street address.

PR_BUSINESS_ADDRESS_STREET_W Contains the recipient's street address.

PR_BUSINESS_FAX_NUMBER Contains the telephone number of the recipient's business fax machine.

PR_BUSINESS_FAX_NUMBER_A Contains the telephone number of the recipient's business fax machine.

PR_BUSINESS_FAX_NUMBER_W Contains the telephone number of the recipient's business fax machine.

PR_BUSINESS_HOME_PAGE Contains the web address (URL) of the recipient's business home page.

PR_BUSINESS_HOME_PAGE_A Contains the web address (URL) of the recipient's business home page.

PR_BUSINESS_HOME_PAGE_W Contains the web address (URL) of the recipient's business home page.

PR_BUSINESS_TELEPHONE_NUMBER Contains the primary telephone number of the recipient's place of business.

PR_BUSINESS_TELEPHONE_NUMBER_A Contains the primary telephone number of the recipient's place of business.

PR_BUSINESS_TELEPHONE_NUMBER_W Contains the primary telephone number of the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER Contains a secondary telephone number at the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER_A Contains a secondary telephone number at the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER_A_MV Contains a secondary telephone number at the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER_MV Contains a secondary telephone number at the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER_W Contains a secondary telephone number at the recipient's place of business.

PR_BUSINESS2_TELEPHONE_NUMBER_W_MV Contains a secondary telephone number at the recipient's place of business.

PR_CACHED_COLUMN_COUNT Contains the total number of cached columns on the folder.

PR_CAL_END_TIME 0x10C40040

PR_CAL_RECURRING_ID 0x10C50040

PR_CAL_REMINDER_NEXT_TIME 0x10CA0040

PR_CAL_START_TIME 0x10C30040

PR_CALLBACK_TELEPHONE_NUMBER Contains a telephone number that the message recipient can use to reach the sender.

PR_CALLBACK_TELEPHONE_NUMBER_A Contains a telephone number that the message recipient can use to reach the sender.

PR_CALLBACK_TELEPHONE_NUMBER_W Contains a telephone number that the message recipient can use to reach the sender.

PR_CAPABILITIES_TABLE Contains an embedded table object to provide a summary of the address book capabilities.

PR_CAR_TELEPHONE_NUMBER Contains the recipient's car telephone number.

PR_CAR_TELEPHONE_NUMBER_A Contains the recipient's car telephone number.

PR_CAR_TELEPHONE_NUMBER_W Contains the recipient's car telephone number.

PR_CATALOG 0x0E5B0102

PR_CATEG_COUNT Contains the total number of categorizations on the folder.

PR_CATEG_ID 0x674B0014

PR_CDO_EXPANSION_INDEX 0x10C70003

PR_CELLULAR_TELEPHONE_NUMBER Contains the recipient's mobile telephone number.

PR_CELLULAR_TELEPHONE_NUMBER_A Contains the recipient's mobile telephone number.

PR_CELLULAR_TELEPHONE_NUMBER_W Contains the recipient's mobile telephone number.

PR_CFG_CONN_TYPE 0x66030003

PR_CFG_ENABLE_DOWNLOAD 0x6621000B

PR_CFG_ENABLE_UPLOAD 0x6620000B

PR_CFG_GAL_ONLY 0x6625000B

PR_CFG_LAN_EXTERNAL_DELIVERY 0x6632000B

PR_CFG_LAN_HEADERS 0x6630000B

PR_CFG_LAN_LOCAL_AB 0x6631000B
PR_CFG_LOCAL_HEADER 0x6680000B
PR_CFG_MAILBOX 0x6601001E
PR_CFG_NETBIOS_NTIFY 0x6623000B
PR_CFG_PASSWORD 0x67F0001E
PR_CFG_RAS_CONFIRM 0x66470003
PR_CFG_RAS_EXTERNAL_DELIVERY 0x6639000B
PR_CFG_RAS_HEADERS 0x6640000B
PR_CFG_RAS_INIT_ON_START 0x6642000B
PR_CFG_RAS_LOCAL_AB 0x6641000B
PR_CFG_RAS_PROFILE 0x6646001E
PR_CFG_RAS_RETRYATTEMPTS 0x6648001E
PR_CFG_RAS_RETRYDELAY 0x6649001E
PR_CFG_RAS_TERM_ON_EXIT 0x6645000B
PR_CFG_RAS_TERM_ON_HDRS 0x6643000B
PR_CFG_RAS_TERM_ON_XFER 0x6644000B
PR_CFG_REMEMBER 0x6606000B
PR_CFG_SCHED_SESS_0 0x67000102
PR_CFG_SCHED_SESS_1 0x67010102
PR_CFG_SCHED_SESS_2 0x67020102
PR_CFG_SCHED_SESS_3 0x67030102
PR_CFG_SCHED_SESS_4 0x67040102
PR_CFG_SCHED_SESS_5 0x67050102
PR_CFG_SCHED_SESS_6 0x67060102
PR_CFG_SCHED_SESS_7 0x67070102
PR_CFG_SCHED_SESS_8 0x67080102
PR_CFG_SCHED_SESS_9 0x67090102
PR_CFG_SCHED_SESS_A 0x670A0102
PR_CFG_SCHED_SESS_B 0x670B0102
PR_CFG_SCHED_SESS_C 0x670C0102
PR_CFG_SCHED_SESS_D 0x670D0102
PR_CFG_SCHED_SESS_E 0x670E0102
PR_CFG_SCHED_SESS_F 0x670F0102
PR_CFG_SERVER_PATH 0x6600001E
PR_CFG_SESSION_LOG 0x6604000B
PR_CFG_SESSION_LOG_FILE 0x6605001E
PR_CFG_SPOOLER_POLL 0x6624001E

PR_CFG_UPLOADTO 0x66220003
PR_CHANGE_ADVISOR 0x6634000D
PR_CHANGE_KEY Contains a binary number that uniquely identifies the message or folder version.
PR_CHANGE_NOTIFICATION_GUID 0x66370048
PR_CHECK_IN_COMMENT 0x3F84001F
PR_CHECK_IN_TIME 0x3F830040
PR_CHILDRENS_NAMES Contains the names of the messaging user's children.
PR_CHILDRENS_NAMES_A Contains the names of the messaging user's children.
PR_CHILDRENS_NAMES_W Contains the names of the messaging user's children.
PR_CI_NOTIFICATION_ENABLED 0x0E5D000B
PR_CI_SEARCH_ENABLED 0x0E5C000B
PR_CLIENT_ACTIONS Contains the rule actions.
PR_CLIENT_ADAPTERSPEED 0x67280003
PR_CLIENT_IP 0x67240102
PR_CLIENT_IPMASK 0x67250102
PR_CLIENT_LATENCY 0x672C0003
PR_CLIENT_MACADDRESS 0x67260102
PR_CLIENT_MACHINENAME 0x6727001F
PR_CLIENT_MODE 0x67230003
PR_CLIENT_RPCATTEMPTED 0x67290003
PR_CLIENT_RPCERRORS 0x672B0102
PR_CLIENT_RPCSUCCEEDED 0x672A0003
PR_CLIENT_SUBMISSION 0x01F70003
PR_CLIENT_SUBMIT_TIME Contains the date and time the message sender submitted a message.
PR_CLIENT_VERSION 0x6704001E
PR_CLIENTS_USE_SMIME_SIG 0x01F40003
PR_CN_EXPORT 0x67590102
PR_CN_MAX Contains 22 byte (16-byte GUID + 6-byte Globcnt) maximum change number.
PR_CN_MIN Contains 22 byte (16-byte GUID + 6-byte Globcnt) minimum change number.
PR_CN_MV_EXPORT 0x675B1102

PR_CNSET Set of change numbers (ID Set) the server is reported to have for this folder.

PR_CNSET_FAI Set of FAI change numbers (ID Set) the server is reported to have for this folder.

PR_CODE_PAGE_ID 0x66C30003

PR_COLLECTOR The property is used with the MAPI OpenProperty function to retrieve either the IExchangeImportHierarchyChanges interface or the IExchangeImportContentsChanges interface.

PR_COMMENT Contains a comment about the purpose or content of an object.

PR_COMMENT_A Contains a comment about the purpose or content of an object.

PR_COMMENT_W Contains a comment about the purpose or content of an object.

PR_COMMON_NAME 0x017A001E

PR_COMMON_VIEWS_ENTRYID Contains the entry identifier of the predefined common view folder.

PR_COMPANY_MAIN_PHONE_NUMBER Contains the main telephone number of the messaging user's company.

PR_COMPANY_MAIN_PHONE_NUMBER_A Contains the main telephone number of the messaging user's company.

PR_COMPANY_MAIN_PHONE_NUMBER_W Contains the main telephone number of the messaging user's company.

PR_COMPANY_NAME Contains the recipient's company name.

PR_COMPANY_NAME_A Contains the recipient's company name.

PR_COMPANY_NAME_W Contains the recipient's company name.

PR_COMPUTER_NETWORK_NAME Contains the name of the recipient's computer network.

PR_COMPUTER_NETWORK_NAME_A Contains the name of the recipient's computer network.

PR_COMPUTER_NETWORK_NAME_W Contains the name of the recipient's computer network.

PR_CONFLICT_ENTRYID Contains the entry identifier of an original conflict message that contains conflicting versions of the message as attachments.

PR_CONFLICT_MSG_KEY 0x3FCA0102

PR_CONNECT_FLAGS Contains the type of connection.

PR_CONNECT_TIME Contains the time of connection.

PR_CONNECTION_MODULUS 0x67430003

PR_CONNECTION_RETRY_INTERVAL 0x01B0001E

PR_CONSOLE_STAT_FREQUENCY 0x01920003

PR_CONTACT_ADDRTYPES Contains the messaging user's e-mail address types, such as SMTP.

PR_CONTACT_ADDRTYPES_A Contains the messaging user's e-mail address types, such as SMTP.

PR_CONTACT_ADDRTYPES_W Contains the messaging user's e-mail address types, such as SMTP.

PR_CONTACT_COUNT Contains the number of contacts in a public folder.

PR_CONTACT_DEFAULT_ADDRESS_INDEX Contains the messaging user's default address index.

PR_CONTACT_EMAIL_ADDRESSES Contains the messaging user's e-mail address.

PR_CONTACT_EMAIL_ADDRESSES_A Contains the messaging user's e-mail address.

PR_CONTACT_EMAIL_ADDRESSES_W Contains the messaging user's e-mail address.

PR_CONTACT_ENTRYIDS Contains the entry identifier of the recipient.

PR_CONTACT_VERSION Contains the version of the recipient's contact information.

PR_CONTAINER_CLASS Was originally meant to contain a text string describing the type of a folder.

PR_CONTAINER_CLASS_A Was originally meant to contain a text string describing the type of a folder.

PR_CONTAINER_CLASS_W Was originally meant to contain a text string describing the type of a folder.

PR_CONTAINER_CONTENTS Contains an embedded contents table object that provides information about a container.

PR_CONTAINER_FLAGS Contains a bitmask of flags describing capabilities of an address book container.

PR_CONTAINER_HIERARCHY Contains an embedded hierarchy table object that provides information about the child containers.

PR_CONTAINER_MODIFY_VERSION Was originally meant to contain the current modification version for a folder.

PR_CONTENT_CONFIDENTIALITY_ALGORITHM_ID Contains an identifier for the algorithm used to confirm message content confidentiality.

PR_CONTENT_CORRELATOR Contains a value the message sender can use to match a report with the original message.

PR_CONTENT_COUNT Contains the total number of normal messages in the folder.

PR_CONTENT_FILTER_SCL 0x40760003

PR_CONTENT_IDENTIFIER Contains a key value that enables the message recipient to identify its content.

PR_CONTENT_IDENTIFIER_A Contains a key value that enables the message recipient to identify its content.

PR_CONTENT_IDENTIFIER_W Contains a key value that enables the message recipient to identify its content.

PR_CONTENT_INTEGRITY_CHECK Contains an ASN.1 content integrity check value that allows a message sender to help protect message content from disclosure to unauthorized recipients.

PR_CONTENT_LENGTH Contains a message length, in bytes, passed to a client application or service provider to determine if a message of that length can be delivered.

PR_CONTENT_RETURN_REQUESTED Contains true if a message should be returned with a nondelivery report.

PR_CONTENT_SEARCH_KEY Contains the entry identifier of the message inside the message transfer envelope (MTE).

PR_CONTENT_UNREAD Contains the number of unread messages in a folder, as computed by the message store.

PR_CONTENTS_SORT_ORDER Originally meant to contain a value specifying the sort order for the columns of a container.

PR_CONTENTS_SYNCHRONIZER The property is used with the MAPI OpenProperty function to retrieve the IExchangeExportChanges interface. This interface is for exporting only a folder's contents changes, not its hierarchy changes.

PR_CONTROL_FLAGS Contains a bitmask of flags governing the behavior of a control used in a dialog box built from a display table.

PR_CONTROL_ID Contains a unique identifier for a control used in a dialog box.

PR_CONTROL_STRUCTURE Contains a reference to a structure for a control used in a dialog box.

PR_CONTROL_TYPE Contains a value indicating a control type for a control used in a dialog box.

PR_CONV_PROHIBITED_DEFAULT 0x3DEF000B

PR_CONVERSATION_INDEX Contains a binary value that indicates the relative position of this message within a conversation thread.

PR_CONVERSATION_KEY The obsolete precursor of the PR_CONVERSATION_INDEX and PR_CONVERSATION_TOPIC properties.

PR_CONVERSATION_TOPIC Contains the topic of the first message in a conversation thread.

PR_CONVERSATION_TOPIC_A Contains the topic of the first message in a conversation thread.

PR_CONVERSATION_TOPIC_W Contains the topic of the first message in a conversation thread.

PR_CONVERSION_EITS Contains the encoded information types (EITs) that are applied to a message in transit to describe conversions.

PR_CONVERSION_INDICATION 0x7000000B

PR_CONVERSION_PROHIBITED Contains true if message conversions are prohibited by default for the associated messaging user.

PR_CONVERSION_STATE 0x67780003

PR_CONVERSION_WITH_LOSS_PROHIBITED Contains true if a message transfer agent (MTA) is prohibited from making message text conversions that lose information.

PR_CONVERTED_EITS Contains an identifier for the types of text in a message after conversion.

PR_CORRELATE Contains true if the sender of a message requests the correlation feature of the messaging system.

PR_CORRELATE_MTSID Contains the message transfer system (MTS) identifier used in correlating reports with sent messages.

PR_COUNTRY Contains the name of the recipient's country/region.

PR_COUNTRY_A Contains the name of the recipient's country/region.

PR_COUNTRY_W Contains the name of the recipient's country/region.

PR_CREATE_TEMPLATES Contains an embedded table object that contains dialog box template entry identifiers.

PR_CREATION_TIME Contains the creation date and time for an object (folder, message, etc).

PR_CREATION_VERSION Was originally meant to contain the message

store version current at the time a message was created.

PR_CREATOR_ENTRYID Contains the address book entry identifier of the user who created the message.

PR_CREATOR_FLAGS 0x40590003

PR_CREATOR_NAME Contains the display name of the user who created the message.

PR_CREATOR_SID 0x0E580102

PR_CREATOR_SID_AS_XML 0x0E6C001E

PR_CREATOR_SIMPLE_DISP_NAME 0x4038001F

PR_CREATOR_TOKEN 0x67830102

PR_CRUISE_CONTROL 0x01C80003

PR_CURRENT_VERSION Was originally meant to contain the current version of a message store.

PR_CUSTOMER_ID Contains the recipient's customer identification number.

PR_CUSTOMER_ID_A Contains the recipient's customer identification number.

PR_CUSTOMER_ID_W Contains the recipient's customer identification number.

PR_DAM_BACK_PATCHED 0x6647000B

PR_DAM_ORIG_MSG_SVREID 0x65C10102

PR_DAM_ORIGINAL_ENTRYID 0x66460102

PR_DAM_STORE_ENTRYID 0x65C00102

PR_DAP_SEARCH_ROOT 0x3DE5001E

PR_DATE_DISCOVERED_ABSENT_IN_DS 0x67080040

PR_DAV_SUBMIT_DATA 0x10C6001F

PR_DAV_TRANSFER_SECURITY_DESCRIPTOR 0x0E840102

PR_DC_FLAGS 0x7CD00003

PR_DC_MSP_CLEARANCE 0x3DE00003

PR_DC_SEC_BUTTONS 0x7CDA0040

PR_DDAT1 0x670E001E

PR_DDAT2 0x6710001E

PR_DDAT3 0x6712001E

PR_DDAT4 0x6714001E

PR_DDAV1 0x670F001E

PR_DDAV2 0x6711001E

PR_DDAV3 0x6713001E

PR_DDAV4 0x6715001E
PR_DEBUG 0x01040003
PR_DEBUG_BOX_STATE 0x01860003
PR_DECLINE_CONFLICTING_MEETING_REQUESTS 0x686F000B
PR_DECLINE_RECURRING_MEETING_REQUESTS 0x686E000B
PR_DEF_CREATE_DL Contains the template entry identifier for a default distribution list object.
PR_DEF_CREATE_MAILUSER Contains the template entry identifier for a default messaging user object.
PR_DEF_FORM_NAME 0x36E6001F
PR_DEF_MSG_CLASS 0x36E5001F
PR_DEFAULT_DOMAIN 0x01E8001E
PR_DEFAULT_PROFILE Contains true if a messaging user profile is the MAPI default profile.
PR_DEFAULT_ROUTING 0x0108001E
PR_DEFAULT_ROUTING_DIALUP 0x01090102
PR_DEFAULT_SECURITY 0x3DD30003
PR_DEFAULT_STORE Contains true if a message store is the default message store in the message store table.
PR_DEFAULT_VIEW_ENTRYID Contains the entry identifier of a folder's default view.
PR_DEFERRED_DELIVERY_DELTA 0x7CD20003
PR_DEFERRED_DELIVERY_TIME Contains the date and time at which a message sender wants a message delivered.
PR_DEFERRED_SEND_NUMBER Contains the units of time that the system waits before sending a message.
PR_DEFERRED_SEND_TIME Contains a future time at which a message is to be sent.
PR_DEFERRED_SEND_UNITS Contains the unit of time to be used with the PR_DEFERRED_SEND_NUMBER property to determine the PR_DEFERRED_SEND_TIME for a message that has been deferred.
PR_DELEGATED_BY_RULE 0x3FE3000B
PR_DELEGATES_DISPLAY_NAMES 0x6844101F
PR_DELEGATES_ENTRYIDS 0x68451102
PR_DELEGATES_SEE_PRIVATE 0x686B1003
PR_DELEGATION Contains the converted value of the attDelegate workgroup property.

PR_DELETE_AFTER_SUBMIT Contains true if a client application wants MAPI to delete the associated message after submission.

PR_DELETE_TIME 0x0E660040

PR_DELETED_ASSOC_MESSAGE_SIZE_EXTENDED 0x669D0014

PR_DELETED_ASSOC_MSG_COUNT 0x66430003

PR_DELETED_COUNT_TOTAL 0x670B0003

PR_DELETED_FOLDER_COUNT 0x66410003

PR_DELETED_MESSAGE_SIZE_EXTENDED 0x669B0014

PR_DELETED_MSG_COUNT 0x66400003

PR_DELETED_NORMAL_MESSAGE_SIZE_EXTENDED 0x669C0014

PR_DELETED_ON 0x668F0040

PR_DELETED_SUBFOLDER_CT 0x0E640003

PR_DELIVER_TIME Contains the date and time at which the original message was delivered.

PR_DELIVER_TO_DN 0x6744001F

PR_DELIVERY_POINT Contains a value that specifies the nature of the functional entity by means of which a message was or would have been delivered to the recipient.

PR_DELIVERY_ROUTING 0x0106101E

PR_DELIVERY_ROUTING_DIALUP 0x01070102

PR_DELTAX Contains the width of a dialog box control in standard Windows dialog units.

PR_DELTAY Contains the height of a dialog box control in standard Windows dialog units.

PR_DEPARTMENT_NAME Contains a name for the department in which the recipient works.

PR_DEPARTMENT_NAME_A Contains a name for the department in which the recipient works.

PR_DEPARTMENT_NAME_W Contains a name for the department in which the recipient works.

PR_DEPTH Represents the relative level of indentation, or depth, of an object in a hierarchy table.

PR_DEQUEUE_METHOD_DATA 0x01EE101E

PR_DESIGN_IN_PROGRESS Contains a flag that indicates a folder is being modified and can only be accessed by the owner.

PR_DETAILS_TABLE Contains an embedded display table object.

PR_DIALUP 0x016C101E

PR_DIALUP_NAMES 0x016D0102
PR_DID 0x3F800014
PR_DISABLE_ETRN 0x01ED0003
PR_DISABLE_FULL_FIDELITY 0x10F2000B
PR_DISABLE_LOOPBACK 0x01B50003
PR_DISABLE_OUTBOUND_ESMTP 0x01D40003
PR_DISABLE_PERUSER_READ 0x66C5000B
PR_DISABLE_RES_SEARCH_LIST 0x016A0003
PR_DISABLE_REVERSE_RESOLVE 0x01C60003
PR_DISABLE_WINSOCK 0x66180003
PR_DISC_VAL The obsolete precursor of the PR_DISCRETE_VALUES property.
PR_DISCARD_REASON Contains a reason why a message transfer agent (MTA) has discarded a message.
PR_DISCLOSE_RECIPIENTS Contains true if disclosure of this recipient is allowed.
PR_DISCLOSURE_OF_RECIPIENTS Contains true if disclosure of recipients is allowed.
PR_DISCRETE_VALUES Contains true if a nondelivery report applies only to discrete members of a distribution list rather than the entire list.
PR_DISK_SPACE_LOW_WATER_MARK 0x01A80003
PR_DISPATCH_THREADS 0x010A0003
PR_DISPLAY_BCC Contains an ASCII list of the display names of any blind carbon copy (BCC) message recipients, separated by semicolons (;).
PR_DISPLAY_BCC_A Contains an ASCII list of the display names of any blind carbon copy (BCC) message recipients, separated by semicolons (;).
PR_DISPLAY_BCC_W Contains an ASCII list of the display names of any blind carbon copy (BCC) message recipients, separated by semicolons (;).
PR_DISPLAY_CC Contains an ASCII list of the display names of any carbon copy (CC) message recipients, separated by semicolons (;).
PR_DISPLAY_CC_A Contains an ASCII list of the display names of any carbon copy (CC) message recipients, separated by semicolons (;).
PR_DISPLAY_CC_W Contains an ASCII list of the display names of any carbon copy (CC) message recipients, separated by semicolons (;).
PR_DISPLAY_ERRS_ON_CONSOLE 0x018A0003
PR_DISPLAY_MSG_STATS 0x01840003
PR_DISPLAY_NAME Contains the display name of the message store.

PR_DISPLAY_NAME_A Contains the display name of the message store.
PR_DISPLAY_NAME_PREFIX Contains the display name prefix for a given MAPI object.
PR_DISPLAY_NAME_PREFIX_A Contains the display name prefix for a given MAPI object.
PR_DISPLAY_NAME_PREFIX_W Contains the display name prefix for a given MAPI object.
PR_DISPLAY_NAME_W Contains the display name of the message store.
PR_DISPLAY_TO Contains an ASCII list of the display names of the primary (To) message recipients, separated by semicolons (;).
PR_DISPLAY_TO_A Contains an ASCII list of the display names of the primary (To) message recipients, separated by semicolons (;).
PR_DISPLAY_TO_W Contains an ASCII list of the display names of the primary (To) message recipients, separated by semicolons (;).
PR_DISPLAY_TYPE Contains a value used to associate an icon with a particular row of a table.
PR_DL_EXPANSION_HISTORY Contains a history showing how a distribution list has been expanded during message transmission.
PR_DL_EXPANSION_PROHIBITED Contains true if a message transfer agent (MTA) is prohibited from expanding distribution lists.
PR_DL_REPORT_FLAGS 0x3FDB0003
PR_DMS_ENABLED 0x6653000B
PR_DMS_MESSAGE 0x6654000B
PR_DMS_SECURITY_PROTOCOL 0x3DF11102
PR_DMS_UNENCAP_RCPT 0x5805001E
PR_DMS_UNENCAP_SENDER 0x4077001E
PR_DOMAIN_INFO 0x010C101E
PR_DOTSTUFF_STATE 0x60010003
PR_DRAFTID 0x3F820014
PR_DUA_NAME 0x3DE3001E
PR_DUA_PASSWORD 0x3DE4001E
PR_EC_WARNING 0x400F0003
PR_EFORMS_FOR_LOCALE_ENTRYID 0x66240102
PR_EFORMS_LOCALE_ID 0x3FE90003
PR_EFORMS_REGISTRY_ENTRYID Contains the entry identifier of the forms library folder under the non-IPM subtree.
PR_ELC_AUTOCOPY_LABEL 0x4081001E

PR_ELC_AUTOCOPY_TAG 0x67160102

PR_ELC_MOVEDATE 0x67170102

PR_EMAIL_ADDRESS Contains the messaging user's e-mail address.

PR_EMAIL_ADDRESS_A Contains the messaging user's e-mail address.

PR_EMAIL_ADDRESS_W Contains the messaging user's e-mail address.

PR_EMS_AB_ACCESS_CATEGORY 0x80440003

PR_EMS_AB_ACTIVATION_SCHEDULE Contains the activation schedule of a regularly scheduled event for a Microsoft Exchange Server component.

PR_EMS_AB_ACTIVATION_STYLE Contains the style of activation of a regularly scheduled event for a Microsoft Exchange Server component.

PR_EMS_AB_ADC_GLOBAL_NAMES 0x8C70101E

PR_EMS_AB_ADC_GLOBAL_NAMES_A 0x8C70101E

PR_EMS_AB_ADC_GLOBAL_NAMES_W 0x8C70101F

PR_EMS_AB_ADDRESS_ENTRY_DISPLAY_TABLE Contains the MAPI display table for an address entry.

PR_EMS_AB_ADDRESS_ENTRY_DISPLAY_TABLE_MSDOS Contains the MS-DOS format display table for an address entry.

PR_EMS_AB_ADDRESS_SYNTAX Contains the correct syntax to use when encoding the display table properties as a string.

PR_EMS_AB_ADDRESS_TYPE Contains the address type to use when setting up replication to a remote site.

PR_EMS_AB_ADDRESS_TYPE_A Contains the address type to use when setting up replication to a remote site.

PR_EMS_AB_ADDRESS_TYPE_W Contains the address type to use when setting up replication to a remote site.

PR_EMS_AB_ADMD The property determines whether the internal trace information is stripped.

PR_EMS_AB_ADMD_A The property determines whether the internal trace information is stripped.

PR_EMS_AB_ADMD_W The property determines whether the internal trace information is stripped.

PR_EMS_AB_ADMIN_DESCRIPTION Contains a short description of a directory object for the administrator.

PR_EMS_AB_ADMIN_DESCRIPTION_A Contains a short description of a directory object for the administrator.

PR_EMS_AB_ADMIN_DESCRIPTION_W Contains a short description of

a directory object for the administrator.

PR_EMS_AB_ADMIN_DISPLAY_NAME Contains the Administrator display name for a directory Top object.

PR_EMS_AB_ADMIN_DISPLAY_NAME_A Contains the Administrator display name for a directory Top object.

PR_EMS_AB_ADMIN_DISPLAY_NAME_W Contains the Administrator display name for a directory Top object.

PR_EMS_AB_ADMIN_EXTENSION_DLL Contains the name of the Administrator extension DLL associated with an Admin-Extension object.

PR_EMS_AB_ADMIN_EXTENSION_DLL_A Contains the name of the Administrator extension DLL associated with an Admin-Extension object.

PR_EMS_AB_ADMIN_EXTENSION_DLL_W Contains the name of the Administrator extension DLL associated with an Admin-Extension object.

PR_EMS_AB_ALIASED_OBJECT_NAME 0x804D001E

PR_EMS_AB_ALIASED_OBJECT_NAME_A 0x804D001E

PR_EMS_AB_ALIASED_OBJECT_NAME_O 0x804D000D

PR_EMS_AB_ALIASED_OBJECT_NAME_T 0x804D001E

PR_EMS_AB_ALIASED_OBJECT_NAME_W 0x804D001F

PR_EMS_AB_ALT_RECIPIENT Contains the distinguished name of an alternate recipient mailbox that will receive all incoming mail for a mailbox.

PR_EMS_AB_ALT_RECIPIENT_A Contains the distinguished name of an alternate recipient mailbox that will receive all incoming mail for a mailbox.

PR_EMS_AB_ALT_RECIPIENT_BL Contains the backlink to an alternate recipient for a mail recipient.

PR_EMS_AB_ALT_RECIPIENT_BL_A Contains the backlink to an alternate recipient for a mail recipient.

PR_EMS_AB_ALT_RECIPIENT_BL_O Contains the backlink to an alternate recipient for a mail recipient.

PR_EMS_AB_ALT_RECIPIENT_BL_T Contains the backlink to an alternate recipient for a mail recipient.

PR_EMS_AB_ALT_RECIPIENT_BL_W Contains the backlink to an alternate recipient for a mail recipient.

PR_EMS_AB_ALT_RECIPIENT_O Contains the distinguished name of an alternate recipient mailbox that will receive all incoming mail for a mailbox.

PR_EMS_AB_ALT_RECIPIENT_T Contains the distinguished name of an alternate recipient mailbox that will receive all incoming mail for a mailbox.

PR_EMS_AB_ALT_RECIPIENT_W Contains the distinguished name of an alternate recipient mailbox that will receive all incoming mail for a mailbox.

PR_EMS_AB_ANCESTOR_ID 0x80500102

PR_EMS_AB_ANONYMOUS_ACCESS 0x8187000B

PR_EMS_AB_ANONYMOUS_ACCOUNT 0x8C26001E

PR_EMS_AB_ANONYMOUS_ACCOUNT_A 0x8C26001E

PR_EMS_AB_ANONYMOUS_ACCOUNT_W 0x8C26001F

PR_EMS_AB_ASSOC_NT_ACCOUNT Contains the primary Windows NT account associated with a mailbox.

PR_EMS_AB_ASSOC_PROTOCOL_CFG_NNTP 0x81A5001E

PR_EMS_AB_ASSOC_PROTOCOL_CFG_NNTP_A 0x81A5001E

PR_EMS_AB_ASSOC_PROTOCOL_CFG_NNTP_O 0x81A5000D

PR_EMS_AB_ASSOC_PROTOCOL_CFG_NNTP_T 0x81A5001E

PR_EMS_AB_ASSOC_PROTOCOL_CFG_NNTP_W 0x81A5001F

PR_EMS_AB_ASSOC_REMOTE_DXA 0x8051101E

PR_EMS_AB_ASSOC_REMOTE_DXA_A 0x8051101E

PR_EMS_AB_ASSOC_REMOTE_DXA_O 0x8051000D

PR_EMS_AB_ASSOC_REMOTE_DXA_T 0x8051101E

PR_EMS_AB_ASSOC_REMOTE_DXA_W 0x8051101F

PR_EMS_AB_ASSOCIATION_LIFETIME 0x80520003

PR_EMS_AB_ATTRIBUTE_CERTIFICATE 0x8C451102

PR_EMS_AB_AUTH_ORIG_BL 0x8053101E

PR_EMS_AB_AUTH_ORIG_BL_A 0x8053101E

PR_EMS_AB_AUTH_ORIG_BL_O 0x8053000D

PR_EMS_AB_AUTH_ORIG_BL_T 0x8053101E

PR_EMS_AB_AUTH_ORIG_BL_W 0x8053101F

PR_EMS_AB_AUTHENTICATION_TO_USE 0x819A001E

PR_EMS_AB_AUTHENTICATION_TO_USE_A 0x819A001E

PR_EMS_AB_AUTHENTICATION_TO_USE_W 0x819A001F

PR_EMS_AB_AUTHORITY_REVOCATION_LIST 0x80261102

PR_EMS_AB_AUTHORIZED_DOMAIN 0x8054001E

PR_EMS_AB_AUTHORIZED_DOMAIN_A 0x8054001E

PR_EMS_AB_AUTHORIZED_DOMAIN_W 0x8054001F

PR_EMS_AB_AUTHORIZED_PASSWORD 0x80550102
PR_EMS_AB_AUTHORIZED_PASSWORD_CONFIRM 0x81920102
PR_EMS_AB_AUTHORIZED_USER 0x8056001E
PR_EMS_AB_AUTHORIZED_USER_A 0x8056001E
PR_EMS_AB_AUTHORIZED_USER_W 0x8056001F
PR_EMS_AB_AUTOREPLY 0x800B000B
PR_EMS_AB_AUTOREPLY_MESSAGE Contains the message that is sent when the Out of Office rule is applied and the Out of Office Assistant is set.
PR_EMS_AB_AUTOREPLY_MESSAGE_A Contains the message that is sent when the Out of Office rule is applied and the Out of Office Assistant is set.
PR_EMS_AB_AUTOREPLY_MESSAGE_W Contains the message that is sent when the Out of Office rule is applied and the Out of Office Assistant is set.
PR_EMS_AB_AUTOREPLY_SUBJECT Contains the subject line for an Out of Office message.
PR_EMS_AB_AUTOREPLY_SUBJECT_A Contains the subject line for an Out of Office message.
PR_EMS_AB_AUTOREPLY_SUBJECT_W Contains the subject line for an Out of Office message.
PR_EMS_AB_AVAILABLE_AUTHORIZATION_PACKAGES 0x8181101E
PR_EMS_AB_AVAILABLE_AUTHORIZATION_PACKAGES_A 0x8181101E
PR_EMS_AB_AVAILABLE_AUTHORIZATION_PACKAGES_W 0x8181101F
PR_EMS_AB_AVAILABLE_DISTRIBUTIONS 0x818B001E
PR_EMS_AB_AVAILABLE_DISTRIBUTIONS_A 0x818B001E
PR_EMS_AB_AVAILABLE_DISTRIBUTIONS_W 0x818B001F
PR_EMS_AB_BRIDGEHEAD_SERVERS 0x8174101E
PR_EMS_AB_BRIDGEHEAD_SERVERS_A 0x8174101E
PR_EMS_AB_BRIDGEHEAD_SERVERS_O 0x8174000D
PR_EMS_AB_BRIDGEHEAD_SERVERS_T 0x8174101E
PR_EMS_AB_BRIDGEHEAD_SERVERS_W 0x8174101F
PR_EMS_AB_BUSINESS_CATEGORY 0x8057101E
PR_EMS_AB_BUSINESS_CATEGORY_A 0x8057101E

PR_EMS_AB_BUSINESS_CATEGORY_W 0x8057101F
PR_EMS_AB_BUSINESS_ROLES 0x80230102
PR_EMS_AB_CA_CERTIFICATE 0x80031102
PR_EMS_AB_CAN_CREATE_PF 0x8058101E
PR_EMS_AB_CAN_CREATE_PF_A 0x8058101E
PR_EMS_AB_CAN_CREATE_PF_BL 0x8059101E
PR_EMS_AB_CAN_CREATE_PF_BL_A 0x8059101E
PR_EMS_AB_CAN_CREATE_PF_BL_O 0x8059000D
PR_EMS_AB_CAN_CREATE_PF_BL_T 0x8059101E
PR_EMS_AB_CAN_CREATE_PF_BL_W 0x8059101F
PR_EMS_AB_CAN_CREATE_PF_DL 0x805A101E
PR_EMS_AB_CAN_CREATE_PF_DL_A 0x805A101E
PR_EMS_AB_CAN_CREATE_PF_DL_BL 0x805B101E
PR_EMS_AB_CAN_CREATE_PF_DL_BL_A 0x805B101E
PR_EMS_AB_CAN_CREATE_PF_DL_BL_O 0x805B000D
PR_EMS_AB_CAN_CREATE_PF_DL_BL_T 0x805B101E
PR_EMS_AB_CAN_CREATE_PF_DL_BL_W 0x805B101F
PR_EMS_AB_CAN_CREATE_PF_DL_O 0x805A000D
PR_EMS_AB_CAN_CREATE_PF_DL_T 0x805A101E
PR_EMS_AB_CAN_CREATE_PF_DL_W 0x805A101F
PR_EMS_AB_CAN_CREATE_PF_O 0x8058000D
PR_EMS_AB_CAN_CREATE_PF_T 0x8058101E
PR_EMS_AB_CAN_CREATE_PF_W 0x8058101F
PR_EMS_AB_CAN_NOT_CREATE_PF 0x805C101E
PR_EMS_AB_CAN_NOT_CREATE_PF_A 0x805C101E
PR_EMS_AB_CAN_NOT_CREATE_PF_BL 0x805D101E
PR_EMS_AB_CAN_NOT_CREATE_PF_BL_A 0x805D101E
PR_EMS_AB_CAN_NOT_CREATE_PF_BL_O 0x805D000D
PR_EMS_AB_CAN_NOT_CREATE_PF_BL_T 0x805D101E
PR_EMS_AB_CAN_NOT_CREATE_PF_BL_W 0x805D101F
PR_EMS_AB_CAN_NOT_CREATE_PF_DL 0x805E101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_A 0x805E101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_BL 0x805F101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_BL_A 0x805F101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_BL_O 0x805F000D
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_BL_T 0x805F101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_BL_W 0x805F101F

PR_EMS_AB_CAN_NOT_CREATE_PF_DL_O 0x805E000D
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_T 0x805E101E
PR_EMS_AB_CAN_NOT_CREATE_PF_DL_W 0x805E101F
PR_EMS_AB_CAN_NOT_CREATE_PF_O 0x805C000D
PR_EMS_AB_CAN_NOT_CREATE_PF_T 0x805C101E
PR_EMS_AB_CAN_NOT_CREATE_PF_W 0x805C101F
PR_EMS_AB_CAN_PRESERVE_DNS 0x8060000B
PR_EMS_AB_CERTIFICATE_CHAIN_V3 0x8C270102
PR_EMS_AB_CERTIFICATE_REVOCATION_LIST 0x80160102
PR_EMS_AB_CERTIFICATE_REVOCATION_LIST_V1 0x8C290102
PR_EMS_AB_CERTIFICATE_REVOCATION_LIST_V3 0x8C280102
PR_EMS_AB_CHARACTER_SET 0x8185001E
PR_EMS_AB_CHARACTER_SET_A 0x8185001E
PR_EMS_AB_CHARACTER_SET_LIST 0x8182101E
PR_EMS_AB_CHARACTER_SET_LIST_A 0x8182101E
PR_EMS_AB_CHARACTER_SET_LIST_W 0x8182101F
PR_EMS_AB_CHARACTER_SET_W 0x8185001F
PR_EMS_AB_CHILD_RDNS 0xFFF8101E
PR_EMS_AB_CLIENT_ACCESS_ENABLED 0x8C24000B
PR_EMS_AB_CLOCK_ALERT_OFFSET 0x80610003
PR_EMS_AB_CLOCK_ALERT_REPAIR 0x8062000B
PR_EMS_AB_CLOCK_WARNING_OFFSET 0x80630003
PR_EMS_AB_CLOCK_WARNING_REPAIR 0x8064000B
PR_EMS_AB_COMPROMISED_KEY_LIST 0x81C40102
PR_EMS_AB_COMPUTER_NAME Contains the name of the computer running a mailbox agent or gateway service.
PR_EMS_AB_COMPUTER_NAME_A Contains the name of the computer running a mailbox agent or gateway service.
PR_EMS_AB_COMPUTER_NAME_W Contains the name of the computer running a mailbox agent or gateway service.
PR_EMS_AB_CONNECTED_DOMAINS 0x8066101E
PR_EMS_AB_CONNECTED_DOMAINS_A 0x8066101E
PR_EMS_AB_CONNECTED_DOMAINS_W 0x8066101F
PR_EMS_AB_CONNECTION_LIST_FILTER 0x81800102
PR_EMS_AB_CONNECTION_LIST_FILTER_TYPE 0x81B40003
PR_EMS_AB_CONNECTION_TYPE 0x81B3000B
PR_EMS_AB_CONTAINER_INFO 0x80670003

PR_EMS_AB_CONTAINERID 0xFFFD0003
PR_EMS_AB_CONTENT_TYPE 0x81860003
PR_EMS_AB_CONTROL_MSG_FOLDER_ID 0x81880102
PR_EMS_AB_CONTROL_MSG_RULES 0x818A0102
PR_EMS_AB_COST Contains the relative cost for routing messages through a particular site connector.
PR_EMS_AB_COUNTRY_NAME The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_COUNTRY_NAME_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_COUNTRY_NAME_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_CROSS_CERTIFICATE_CRL 0x8C301102
PR_EMS_AB_CROSS_CERTIFICATE_PAIR 0x80251102
PR_EMS_AB_DAP_DETAILS 0x3650000D
PR_EMS_AB_DEFAULT_MESSAGE_FORMAT 0x8C37000B
PR_EMS_AB_DELEGATE_USER 0x8C49000B
PR_EMS_AB_DELIV_CONT_LENGTH Contains the maximum message size (in kilobytes) for a gateway or mail recipient.
PR_EMS_AB_DELIV_EITS Contains deliverable encoded information types (EITs) for a mail recipient, gateway, or message transfer agent (MTA).
PR_EMS_AB_DELIV_EXT_CONT_TYPES Contains deliverable external content types for an object.
PR_EMS_AB_DELIVER_AND_REDIRECT Determines whether the original recipient is to receive a copy of a message that has been redirected to an alternative recipient.
PR_EMS_AB_DELIVERY_MECHANISM Contains the mechanism by which mail is delivered to an object.
PR_EMS_AB_DELTA_REVOCATION_LIST 0x8C461102
PR_EMS_AB_DESCRIPTION Contains an optional description of an object.
PR_EMS_AB_DESCRIPTION_A Contains an optional description of an object.
PR_EMS_AB_DESCRIPTION_W Contains an optional description of an object.
PR_EMS_AB_DESTINATION_INDICATOR 0x8070101E

PR_EMS_AB_DESTINATION_INDICATOR_A 0x8070101E
PR_EMS_AB_DESTINATION_INDICATOR_W 0x8070101F
PR_EMS_AB_DIAGNOSTIC_REG_KEY 0x8071001E
PR_EMS_AB_DIAGNOSTIC_REG_KEY_A 0x8071001E
PR_EMS_AB_DIAGNOSTIC_REG_KEY_W 0x8071001F
PR_EMS_AB_DISABLE_DEFERRED_COMMIT 0x8C23000B
PR_EMS_AB_DISABLED_GATEWAY_PROXY 0x81C3101E
PR_EMS_AB_DISABLED_GATEWAY_PROXY_A 0x81C3101E
PR_EMS_AB_DISABLED_GATEWAY_PROXY_W 0x81C3101F
PR_EMS_AB_DISPLAY_NAME_OVERRIDE Determines whether the display name set by the administrator can be overridden by a non-administrator.
PR_EMS_AB_DISPLAY_NAME_PRINTABLE Contains the printable string version of the display name.
PR_EMS_AB_DISPLAY_NAME_PRINTABLE_A Contains the printable string version of the display name.
PR_EMS_AB_DISPLAY_NAME_PRINTABLE_W Contains the printable string version of the display name.
PR_EMS_AB_DISPLAY_NAME_SUFFIX 0x8C44001E
PR_EMS_AB_DISPLAY_NAME_SUFFIX_A 0x8C44001E
PR_EMS_AB_DISPLAY_NAME_SUFFIX_W 0x8C44001F
PR_EMS_AB_DISPLAY_TYPE_EX 0x8C930003
PR_EMS_AB_DL_MEM_REJECT_PERMS_BL 0x8072101E
PR_EMS_AB_DL_MEM_REJECT_PERMS_BL_A 0x8072101E
PR_EMS_AB_DL_MEM_REJECT_PERMS_BL_O 0x8072000D
PR_EMS_AB_DL_MEM_REJECT_PERMS_BL_T 0x8072101E
PR_EMS_AB_DL_MEM_REJECT_PERMS_BL_W 0x8072101F
PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL 0x8073101E
PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_A 0x8073101E
PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_O 0x8073000D
PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_T 0x8073101E
PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_W 0x8073101F
PR_EMS_AB_DL_MEMBER_RULE 0x80741102
PR_EMS_AB_DMD_NAME 0x8C56001E
PR_EMS_AB_DMD_NAME_A 0x8C56001E
PR_EMS_AB_DMD_NAME_W 0x8C56001F
PR_EMS_AB_DO_OAB_VERSION 0x8C3A0003

PR_EMS_AB_DOMAIN_DEF_ALT_RECIP Contains the recipient to which mail is to be delivered when all routing fails.

PR_EMS_AB_DOMAIN_DEF_ALT_RECIP_A Contains the recipient to which mail is to be delivered when all routing fails.

PR_EMS_AB_DOMAIN_DEF_ALT_RECIP_O Contains the recipient to which mail is to be delivered when all routing fails.

PR_EMS_AB_DOMAIN_DEF_ALT_RECIP_T Contains the recipient to which mail is to be delivered when all routing fails.

PR_EMS_AB_DOMAIN_DEF_ALT_RECIP_W Contains the recipient to which mail is to be delivered when all routing fails.

PR_EMS_AB_DOMAIN_NAME 0x8076001E

PR_EMS_AB_DOMAIN_NAME_A 0x8076001E

PR_EMS_AB_DOMAIN_NAME_W 0x8076001F

PR_EMS_AB_DOS_ENTRYID 0xFFFFD0003

PR_EMS_AB_DSA_SIGNATURE 0x80770102

PR_EMS_AB_DXA_ADMIN_COPY 0x8078000B

PR_EMS_AB_DXA_ADMIN_FORWARD 0x8079000B

PR_EMS_AB_DXA_ADMIN_UPDATE 0x807A0003

PR_EMS_AB_DXA_APPEND_REQCN 0x807B000B

PR_EMS_AB_DXA_CONF_CONTAINER_LIST 0x807C101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_A 0x807C101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_BL 0x8C76101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_BL_A 0x8C76101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_BL_O 0x8C76000D

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_BL_T 0x8C76101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_BL_W 0x8C76101F

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_LINKED 0x8C71101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_LINKED_A 0x8C71101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_LINKED_O 0x8C71000D

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_LINKED_T 0x8C71101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_LINKED_W 0x8C71101F

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_O 0x807C000D

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_T 0x807C101E

PR_EMS_AB_DXA_CONF_CONTAINER_LIST_W 0x807C101F
PR_EMS_AB_DXA_CONF_REQ_TIME 0x807D0040
PR_EMS_AB_DXA_CONF_SEQ 0x807E001E
PR_EMS_AB_DXA_CONF_SEQ_A 0x807E001E
PR_EMS_AB_DXA_CONF_SEQ_USN 0x807F0003
PR_EMS_AB_DXA_CONF_SEQ_W 0x807E001F
PR_EMS_AB_DXA_EXCHANGE_OPTIONS 0x80800003
PR_EMS_AB_DXA_EXPORT_NOW 0x8081000B
PR_EMS_AB_DXA_FLAGS 0x80820003
PR_EMS_AB_DXA_IMP_SEQ 0x8083001E
PR_EMS_AB_DXA_IMP_SEQ_A 0x8083001E
PR_EMS_AB_DXA_IMP_SEQ_TIME 0x80840040
PR_EMS_AB_DXA_IMP_SEQ_USN 0x80850003
PR_EMS_AB_DXA_IMP_SEQ_W 0x8083001F
PR_EMS_AB_DXA_IMPORT_NOW 0x8086000B
PR_EMS_AB_DXA_IN_TEMPLATE_MAP 0x8087101E
PR_EMS_AB_DXA_IN_TEMPLATE_MAP_A 0x8087101E
PR_EMS_AB_DXA_IN_TEMPLATE_MAP_W 0x8087101F
PR_EMS_AB_DXA_LOCAL_ADMIN 0x8088001E
PR_EMS_AB_DXA_LOCAL_ADMIN_A 0x8088001E
PR_EMS_AB_DXA_LOCAL_ADMIN_O 0x8088000D
PR_EMS_AB_DXA_LOCAL_ADMIN_T 0x8088001E
PR_EMS_AB_DXA_LOCAL_ADMIN_W 0x8088001F
PR_EMS_AB_DXA_LOGGING_LEVEL 0x80890003
PR_EMS_AB_DXA_NATIVE_ADDRESS_TYPE 0x808A001E
PR_EMS_AB_DXA_NATIVE_ADDRESS_TYPE_A 0x808A001E
PR_EMS_AB_DXA_NATIVE_ADDRESS_TYPE_W 0x808A001F
PR_EMS_AB_DXA_OUT_TEMPLATE_MAP 0x808B101E
PR_EMS_AB_DXA_OUT_TEMPLATE_MAP_A 0x808B101E
PR_EMS_AB_DXA_OUT_TEMPLATE_MAP_W 0x808B101F
PR_EMS_AB_DXA_PASSWORD 0x808C001E
PR_EMS_AB_DXA_PASSWORD_A 0x808C001E
PR_EMS_AB_DXA_PASSWORD_W 0x808C001F
PR_EMS_AB_DXA_PREV_EXCHANGE_OPTIONS 0x808D0003
PR_EMS_AB_DXA_PREV_EXPORT_NATIVE_ONLY 0x808E000B
PR_EMS_AB_DXA_PREV_IN_EXCHANGE_SENSITIVITY
0x808F0003

PR_EMS_AB_DXA_PREV_REMOTE_ENTRIES 0x8090001E
PR_EMS_AB_DXA_PREV_REMOTE_ENTRIES_A 0x8090001E
PR_EMS_AB_DXA_PREV_REMOTE_ENTRIES_O 0x8090000D
PR_EMS_AB_DXA_PREV_REMOTE_ENTRIES_T 0x8090001E
PR_EMS_AB_DXA_PREV_REMOTE_ENTRIES_W 0x8090001F
PR_EMS_AB_DXA_PREV_REPLICATION_SENSITIVITY 0x80910003
PR_EMS_AB_DXA_PREV_TEMPLATE_OPTIONS 0x80920003
PR_EMS_AB_DXA_PREV_TYPES 0x80930003
PR_EMS_AB_DXA_RECIPIENT_CP 0x8094001E
PR_EMS_AB_DXA_RECIPIENT_CP_A 0x8094001E
PR_EMS_AB_DXA_RECIPIENT_CP_W 0x8094001F
PR_EMS_AB_DXA_REMOTE_CLIENT 0x8095001E
PR_EMS_AB_DXA_REMOTE_CLIENT_A 0x8095001E
PR_EMS_AB_DXA_REMOTE_CLIENT_O 0x8095000D
PR_EMS_AB_DXA_REMOTE_CLIENT_T 0x8095001E
PR_EMS_AB_DXA_REMOTE_CLIENT_W 0x8095001F
PR_EMS_AB_DXA_REQ_SEQ 0x8096001E
PR_EMS_AB_DXA_REQ_SEQ_A 0x8096001E
PR_EMS_AB_DXA_REQ_SEQ_TIME 0x80970040
PR_EMS_AB_DXA_REQ_SEQ_USN 0x80980003
PR_EMS_AB_DXA_REQ_SEQ_W 0x8096001F
PR_EMS_AB_DXA_REQNAME 0x8099001E
PR_EMS_AB_DXA_REQNAME_A 0x8099001E
PR_EMS_AB_DXA_REQNAME_W 0x8099001F
PR_EMS_AB_DXA_SVR_SEQ 0x809A001E
PR_EMS_AB_DXA_SVR_SEQ_A 0x809A001E
PR_EMS_AB_DXA_SVR_SEQ_TIME 0x809B0040
PR_EMS_AB_DXA_SVR_SEQ_USN 0x809C0003
PR_EMS_AB_DXA_SVR_SEQ_W 0x809A001F
PR_EMS_AB_DXA_TASK 0x809D0003
PR_EMS_AB_DXA_TEMPLATE_OPTIONS 0x809E0003
PR_EMS_AB_DXA_TEMPLATE_TIMESTAMP 0x809F0040
PR_EMS_AB_DXA_TYPES 0x80A00003
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST 0x80A1101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_A 0x80A1101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_BL 0x8C77101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_BL_A 0x8C77101E

PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_BL_O 0x8C77000D
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_BL_T 0x8C77101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_BL_W 0x8C77101F
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_LINKED
0x8C72101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_LINKED_A
0x8C72101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_LINKED_O
0x8C72000D
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_LINKED_T
0x8C72101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_LINKED_W
0x8C72101F
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_O 0x80A1000D
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_T 0x80A1101E
PR_EMS_AB_DXA_UNCONF_CONTAINER_LIST_W 0x80A1101F
PR_EMS_AB_EMPLOYEE_NUMBER 0x8C67001E
PR_EMS_AB_EMPLOYEE_NUMBER_A 0x8C67001E
PR_EMS_AB_EMPLOYEE_NUMBER_W 0x8C67001F
PR_EMS_AB_EMPLOYEE_TYPE 0x8C69001E
PR_EMS_AB_EMPLOYEE_TYPE_A 0x8C69001E
PR_EMS_AB_EMPLOYEE_TYPE_W 0x8C69001F
PR_EMS_AB_ENABLE_COMPATIBILITY 0x8C32000B
PR_EMS_AB_ENABLED 0x8C21000B
PR_EMS_AB_ENABLED_AUTHORIZATION_PACKAGES 0x8184101E
PR_EMS_AB_ENABLED_AUTHORIZATION_PACKAGES_A
0x8184101E
PR_EMS_AB_ENABLED_AUTHORIZATION_PACKAGES_W
0x8184101F
PR_EMS_AB_ENABLED_PROTOCOL_CFG 0x81A8000B
PR_EMS_AB_ENABLED_PROTOCOLS 0x817F0003
PR_EMS_AB_ENCAPSULATION_METHOD Contains the default
encapsulation instructions to be used for recipients on a gateway.
PR_EMS_AB_ENCRYPT 0x80A3000B
PR_EMS_AB_ENCRYPT_ALG_LIST_NA 0x8040101E
PR_EMS_AB_ENCRYPT_ALG_LIST_NA_A 0x8040101E
PR_EMS_AB_ENCRYPT_ALG_LIST_NA_W 0x8040101F

PR_EMS_AB_ENCRYPT_ALG_LIST_OTHER 0x8041101E
PR_EMS_AB_ENCRYPT_ALG_LIST_OTHER_A 0x8041101E
PR_EMS_AB_ENCRYPT_ALG_LIST_OTHER_W 0x8041101F
PR_EMS_AB_ENCRYPT_ALG_SELECTED_NA 0x8043001E
PR_EMS_AB_ENCRYPT_ALG_SELECTED_NA_A 0x8043001E
PR_EMS_AB_ENCRYPT_ALG_SELECTED_NA_W 0x8043001F
PR_EMS_AB_ENCRYPT_ALG_SELECTED_OTHER 0x803D001E
PR_EMS_AB_ENCRYPT_ALG_SELECTED_OTHER_A 0x803D001E
PR_EMS_AB_ENCRYPT_ALG_SELECTED_OTHER_W 0x803D001F
PR_EMS_AB_EXPAND_DLS_LOCALLY 0x80A4000B
PR_EMS_AB_EXPIRATION_TIME Contains the expiration time for a mailbox or distribution list.
PR_EMS_AB_EXPORT_CONTAINERS 0x80A5101E
PR_EMS_AB_EXPORT_CONTAINERS_A 0x80A5101E
PR_EMS_AB_EXPORT_CONTAINERS_O 0x80A5000D
PR_EMS_AB_EXPORT_CONTAINERS_T 0x80A5101E
PR_EMS_AB_EXPORT_CONTAINERS_W 0x80A5101F
PR_EMS_AB_EXPORT_CUSTOM_RECIPIENTS 0x80A6000B
PR_EMS_AB_EXTENDED_CHARS_ALLOWED 0x80A7000B
PR_EMS_AB_EXTENSION_ATTRIBUTE_1 0x802D001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_1_A 0x802D001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_1_W 0x802D001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_10 0x8036001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_10_A 0x8036001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_10_W 0x8036001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_11 0x8C57001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_11_A 0x8C57001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_11_W 0x8C57001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_12 0x8C58001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_12_A 0x8C58001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_12_W 0x8C58001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_13 0x8C59001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_13_A 0x8C59001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_13_W 0x8C59001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_14 0x8C60001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_14_A 0x8C60001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_14_W 0x8C60001F

PR_EMS_AB_EXTENSION_ATTRIBUTE_15 0x8C61001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_15_A 0x8C61001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_15_W 0x8C61001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_2 0x802E001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_2_A 0x802E001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_2_W 0x802E001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_3 0x802F001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_3_A 0x802F001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_3_W 0x802F001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_4 0x8030001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_4_A 0x8030001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_4_W 0x8030001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_5 0x8031001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_5_A 0x8031001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_5_W 0x8031001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_6 0x8032001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_6_A 0x8032001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_6_W 0x8032001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_7 0x8033001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_7_A 0x8033001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_7_W 0x8033001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_8 0x8034001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_8_A 0x8034001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_8_W 0x8034001F
PR_EMS_AB_EXTENSION_ATTRIBUTE_9 0x8035001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_9_A 0x8035001E
PR_EMS_AB_EXTENSION_ATTRIBUTE_9_W 0x8035001F
PR_EMS_AB_EXTENSION_DATA Contains a list of data sections

specific to an extension.

PR_EMS_AB_EXTENSION_NAME Contains the name of an Admin-Extension object that corresponds to the Administrator extension DLL that adds property pages to an object.

PR_EMS_AB_EXTENSION_NAME_A Contains the name of an Admin-Extension object that corresponds to the Administrator extension DLL that adds property pages to an object.

PR_EMS_AB_EXTENSION_NAME_INHERITED Contains the name of an Admin-Extension object.

PR_EMS_AB_EXTENSION_NAME_INHERITED_A Contains the name of an Admin-Extension object.

PR_EMS_AB_EXTENSION_NAME_INHERITED_W Contains the name of an Admin-Extension object.

PR_EMS_AB_EXTENSION_NAME_W Contains the name of an Admin-Extension object that corresponds to the Administrator extension DLL that adds property pages to an object.

PR_EMS_AB_FACSIMILE_TELEPHONE_NUMBER The property is for X.500 compatibility and is not used by Microsoft Exchange Server.

PR_EMS_AB_FILE_VERSION Contains the file version stamp for DLLs used by the object.

PR_EMS_AB_FILTER_LOCAL_ADDRESSES Determines if an address matches a local address space (ADMD, Country/region, PRMD, Organization, or Organization Units [1-4]). If a local mail recipient cannot be found in the directory, a nondelivery report is generated for the message.

PR_EMS_AB_FOLDER_PATHNAME Contains the full path name of the folder.

PR_EMS_AB_FOLDER_PATHNAME_A Contains the full path name of the folder.

PR_EMS_AB_FOLDER_PATHNAME_W Contains the full path name of the folder.

PR_EMS_AB_FOLDERS_CONTAINER Contains the distinguished name of the container into which new public folders are to be created.

PR_EMS_AB_FOLDERS_CONTAINER_A Contains the distinguished name of the container into which new public folders are to be created.

PR_EMS_AB_FOLDERS_CONTAINER_O Contains the distinguished name of the container into which new public folders are to be created.

PR_EMS_AB_FOLDERS_CONTAINER_T Contains the distinguished name of the container into which new public folders are to be created.

PR_EMS_AB_FOLDERS_CONTAINER_W Contains the distinguished name of the container into which new public folders are to be created.

PR_EMS_AB_FORM_DATA 0x8C650102

PR_EMS_AB_FORWARDING_ADDRESS 0x8C64001E

PR_EMS_AB_FORWARDING_ADDRESS_A 0x8C64001E

PR_EMS_AB_FORWARDING_ADDRESS_W 0x8C64001F

PR_EMS_AB_GARBAGE_COLL_PERIOD Contains the number of hours representing the interval at which garbage is collected.

PR_EMS_AB_GATEWAY_LOCAL_CRED 0x80B0001E
PR_EMS_AB_GATEWAY_LOCAL_CRED_A 0x80B0001E
PR_EMS_AB_GATEWAY_LOCAL_CRED_W 0x80B0001F
PR_EMS_AB_GATEWAY_LOCAL_DESIG 0x80B1001E
PR_EMS_AB_GATEWAY_LOCAL_DESIG_A 0x80B1001E
PR_EMS_AB_GATEWAY_LOCAL_DESIG_W 0x80B1001F
PR_EMS_AB_GATEWAY_PROXY Contains a list of proxy addresses that is unique for a domain.
PR_EMS_AB_GATEWAY_PROXY_A Contains a list of proxy addresses that is unique for a domain.
PR_EMS_AB_GATEWAY_PROXY_W Contains a list of proxy addresses that is unique for a domain.
PR_EMS_AB_GATEWAY_ROUTING_TREE 0x80B30102
PR_EMS_AB_GENERATION_QUALIFIER 0x8C53001E
PR_EMS_AB_GENERATION_QUALIFIER_A 0x8C53001E
PR_EMS_AB_GENERATION_QUALIFIER_W 0x8C53001F
PR_EMS_AB_GROUP_BY_ATTR_1 0x81B7001E
PR_EMS_AB_GROUP_BY_ATTR_1_A 0x81B7001E
PR_EMS_AB_GROUP_BY_ATTR_1_W 0x81B7001F
PR_EMS_AB_GROUP_BY_ATTR_2 0x81B8001E
PR_EMS_AB_GROUP_BY_ATTR_2_A 0x81B8001E
PR_EMS_AB_GROUP_BY_ATTR_2_W 0x81B8001F
PR_EMS_AB_GROUP_BY_ATTR_3 0x81B9001E
PR_EMS_AB_GROUP_BY_ATTR_3_A 0x81B9001E
PR_EMS_AB_GROUP_BY_ATTR_3_W 0x81B9001F
PR_EMS_AB_GROUP_BY_ATTR_4 0x81BA001E
PR_EMS_AB_GROUP_BY_ATTR_4_A 0x81BA001E
PR_EMS_AB_GROUP_BY_ATTR_4_W 0x81BA001F
PR_EMS_AB_GROUP_BY_ATTR_VALUE_DN 0x8C1A001E
PR_EMS_AB_GROUP_BY_ATTR_VALUE_DN_A 0x8C1A001E
PR_EMS_AB_GROUP_BY_ATTR_VALUE_DN_O 0x8C1A000D
PR_EMS_AB_GROUP_BY_ATTR_VALUE_DN_T 0x8C1A001E
PR_EMS_AB_GROUP_BY_ATTR_VALUE_DN_W 0x8C1A001F
PR_EMS_AB_GROUP_BY_ATTR_VALUE_STR 0x8C19001E
PR_EMS_AB_GROUP_BY_ATTR_VALUE_STR_A 0x8C19001E
PR_EMS_AB_GROUP_BY_ATTR_VALUE_STR_W 0x8C19001F
PR_EMS_AB_GWART_LAST_MODIFIED 0x80B40040

PR_EMS_AB_HAS_FULL_REPLICA_NCS 0x80B5101E
PR_EMS_AB_HAS_FULL_REPLICA_NCS_A 0x80B5101E
PR_EMS_AB_HAS_FULL_REPLICA_NCS_O 0x80B5000D
PR_EMS_AB_HAS_FULL_REPLICA_NCS_T 0x80B5101E
PR_EMS_AB_HAS_FULL_REPLICA_NCS_W 0x80B5101F
PR_EMS_AB_HAS_MASTER_NCS 0x80B6101E
PR_EMS_AB_HAS_MASTER_NCS_A 0x80B6101E
PR_EMS_AB_HAS_MASTER_NCS_O 0x80B6000D
PR_EMS_AB_HAS_MASTER_NCS_T 0x80B6101E
PR_EMS_AB_HAS_MASTER_NCS_W 0x80B6101F
PR_EMS_AB_HELP_DATA16 Contains the binary Help information template for a 16-bit client.
PR_EMS_AB_HELP_DATA32 Contains the binary Help information for the template for the 32-bit client.
PR_EMS_AB_HELP_FILE_NAME Contains the name of the Help file for the Display-Template object.
PR_EMS_AB_HELP_FILE_NAME_A Contains the name of the Help file for the Display-Template object.
PR_EMS_AB_HELP_FILE_NAME_W Contains the name of the Help file for the Display-Template object.
PR_EMS_AB_HEURISTICS 0x80B70003
PR_EMS_AB_HIDE_DL_MEMBERSHIP Determines whether the individual members of a distribution list are to be listed (and able to be viewed by other users) or unlisted.
PR_EMS_AB_HIDE_FROM_ADDRESS_BOOK Contains a flag that indicates whether the information for a Mail-Recipient object is displayed in the address book.
PR_EMS_AB_HIERARCHY_PATH 0xFFFF9001E
PR_EMS_AB_HIERARCHY_PATH_A 0xFFFF9001E
PR_EMS_AB_HIERARCHY_PATH_W 0xFFFF9001F
PR_EMS_AB_HOME_MDB Contains the distinguished name of the home information store used by a mail recipient or gateway.
PR_EMS_AB_HOME_MDB_A Contains the distinguished name of the home information store used by a mail recipient or gateway.
PR_EMS_AB_HOME_MDB_BL Contains a backlink to the list of the users associated with a server.
PR_EMS_AB_HOME_MDB_BL_A Contains a backlink to the list of the

users associated with a server.

PR_EMS_AB_HOME_MDB_BL_O Contains a backlink to the list of the users associated with a server.

PR_EMS_AB_HOME_MDB_BL_T Contains a backlink to the list of the users associated with a server.

PR_EMS_AB_HOME_MDB_BL_W Contains a backlink to the list of the users associated with a server.

PR_EMS_AB_HOME_MDB_O Contains the distinguished name of the home information store used by a mail recipient or gateway.

PR_EMS_AB_HOME_MDB_T Contains the distinguished name of the home information store used by a mail recipient or gateway.

PR_EMS_AB_HOME_MDB_W Contains the distinguished name of the home information store used by a mail recipient or gateway.

PR_EMS_AB_HOME_MTA 0x8007001E

PR_EMS_AB_HOME_MTA_A 0x8007001E

PR_EMS_AB_HOME_MTA_O 0x8007000D

PR_EMS_AB_HOME_MTA_T 0x8007001E

PR_EMS_AB_HOME_MTA_W 0x8007001F

PR_EMS_AB_HOME_PUBLIC_SERVER Contains the name of the home public server for mailboxes on an information store.

PR_EMS_AB_HOME_PUBLIC_SERVER_A Contains the name of the home public server for mailboxes on an information store.

PR_EMS_AB_HOME_PUBLIC_SERVER_O Contains the name of the home public server for mailboxes on an information store.

PR_EMS_AB_HOME_PUBLIC_SERVER_T Contains the name of the home public server for mailboxes on an information store.

PR_EMS_AB_HOME_PUBLIC_SERVER_W Contains the name of the home public server for mailboxes on an information store.

PR_EMS_AB_HOUSE_IDENTIFIER 0x8C54001E

PR_EMS_AB_HOUSE_IDENTIFIER_A 0x8C54001E

PR_EMS_AB_HOUSE_IDENTIFIER_W 0x8C54001F

PR_EMS_AB_HTTP_PUB_AB_ATTRIBUTES 0x81A9101E

PR_EMS_AB_HTTP_PUB_AB_ATTRIBUTES_A 0x81A9101E

PR_EMS_AB_HTTP_PUB_AB_ATTRIBUTES_W 0x81A9101F

PR_EMS_AB_HTTP_PUB_GAL 0x819B000B

PR_EMS_AB_HTTP_PUB_GAL_LIMIT 0x819C0003

PR_EMS_AB_HTTP_PUB_PF 0x819E1102

PR_EMS_AB_HTTP_SERVERS 0x81AB101E
PR_EMS_AB_HTTP_SERVERS_A 0x81AB101E
PR_EMS_AB_HTTP_SERVERS_W 0x81AB101F
PR_EMS_AB_IMPORT_CONTAINER 0x80BA001E
PR_EMS_AB_IMPORT_CONTAINER_A 0x80BA001E
PR_EMS_AB_IMPORT_CONTAINER_O 0x80BA000D
PR_EMS_AB_IMPORT_CONTAINER_T 0x80BA001E
PR_EMS_AB_IMPORT_CONTAINER_W 0x80BA001F
PR_EMS_AB_IMPORT_SENSITIVITY 0x80BB0003
PR_EMS_AB_IMPORTED_FROM The property is used by directory
synchronization agents to identify objects that they imported.
PR_EMS_AB_IMPORTED_FROM_A The property is used by directory
synchronization agents to identify objects that they imported.
PR_EMS_AB_IMPORTED_FROM_W The property is used by directory
synchronization agents to identify objects that they imported.
PR_EMS_AB_INBOUND_ACCEPT_ALL 0x8C20000B
PR_EMS_AB_INBOUND_DN 0x8C1E001E
PR_EMS_AB_INBOUND_DN_A 0x8C1E001E
PR_EMS_AB_INBOUND_DN_O 0x8C1E000D
PR_EMS_AB_INBOUND_DN_T 0x8C1E001E
PR_EMS_AB_INBOUND_DN_W 0x8C1E001F
PR_EMS_AB_INBOUND_HOST 0x818E101E
PR_EMS_AB_INBOUND_HOST_A 0x818E101E
PR_EMS_AB_INBOUND_HOST_W 0x818E101F
PR_EMS_AB_INBOUND_NEWSFEED 0x8193001E
PR_EMS_AB_INBOUND_NEWSFEED_A 0x8193001E
PR_EMS_AB_INBOUND_NEWSFEED_TYPE 0x8C1F000B
PR_EMS_AB_INBOUND_NEWSFEED_W 0x8193001F
PR_EMS_AB_INBOUND_SITES 0x80BC101E
PR_EMS_AB_INBOUND_SITES_A 0x80BC101E
PR_EMS_AB_INBOUND_SITES_O 0x80BC000D
PR_EMS_AB_INBOUND_SITES_T 0x80BC101E
PR_EMS_AB_INBOUND_SITES_W 0x80BC101F
PR_EMS_AB_INCOMING_MSG_SIZE_LIMIT 0x81900003
PR_EMS_AB_INCOMING_PASSWORD 0x81AF0102
PR_EMS_AB_INSADMIN 0x81C5001E
PR_EMS_AB_INSADMIN_A 0x81C5001E

PR_EMS_AB_INSADMIN_O 0x81C5000D
PR_EMS_AB_INSADMIN_T 0x81C5001E
PR_EMS_AB_INSADMIN_W 0x81C5001F
PR_EMS_AB_INSTANCE_TYPE 0x80BD0003
PR_EMS_AB_INTERNATIONAL_ISDN_NUMBER The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_INTERNATIONAL_ISDN_NUMBER_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_INTERNATIONAL_ISDN_NUMBER_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_INVOCATION_ID 0x80BF0102
PR_EMS_AB_IS_DELETED The property is set to true when an object has been deleted, but not completely removed from the system. An object in this state is called a tombstone. Tombstones are replicated to other servers to inform them that a directory object has been deleted.
PR_EMS_AB_IS_MASTER 0xFFFB000B
PR_EMS_AB_IS_MEMBER_OF_DL Contains the distinguished names of all distribution lists of which the object is a member.
PR_EMS_AB_IS_MEMBER_OF_DL_A Contains the distinguished names of all distribution lists of which the object is a member.
PR_EMS_AB_IS_MEMBER_OF_DL_O Contains the distinguished names of all distribution lists of which the object is a member.
PR_EMS_AB_IS_MEMBER_OF_DL_T Contains the distinguished names of all distribution lists of which the object is a member.
PR_EMS_AB_IS_MEMBER_OF_DL_W Contains the distinguished names of all distribution lists of which the object is a member.
PR_EMS_AB_IS_SINGLE_VALUED 0x80C1000B
PR_EMS_AB_KCC_STATUS 0x80C21102
PR_EMS_AB_KM_SERVER 0x800D001E
PR_EMS_AB_KM_SERVER_A 0x800D001E
PR_EMS_AB_KM_SERVER_O 0x800D000D
PR_EMS_AB_KM_SERVER_T 0x800D001E
PR_EMS_AB_KM_SERVER_W 0x800D001F
PR_EMS_AB_KNOWLEDGE_INFORMATION 0x80C3101E
PR_EMS_AB_KNOWLEDGE_INFORMATION_A 0x80C3101E
PR_EMS_AB_KNOWLEDGE_INFORMATION_W 0x80C3101F
PR_EMS_AB_LABELEDURI 0x8C51001E

PR_EMS_AB_LABELEDURI_A 0x8C51001E
PR_EMS_AB_LABELEDURI_W 0x8C51001F
PR_EMS_AB_LANGUAGE 0x81780003
PR_EMS_AB_LANGUAGE_ISO639 0x8C6C001E
PR_EMS_AB_LANGUAGE_ISO639_A 0x8C6C001E
PR_EMS_AB_LANGUAGE_ISO639_W 0x8C6C001F
PR_EMS_AB_LDAP_DISPLAY_NAME 0x8171101E
PR_EMS_AB_LDAP_DISPLAY_NAME_A 0x8171101E
PR_EMS_AB_LDAP_DISPLAY_NAME_W 0x8171101F
PR_EMS_AB_LDAP_SEARCH_CFG 0x8C1D0003
PR_EMS_AB_LINE_WRAP The property can be used by gateways to save the maximum allowed message line length.
PR_EMS_AB_LINK_ID 0x80C50003
PR_EMS_AB_LIST_PUBLIC_FOLDERS 0x8C50000B
PR_EMS_AB_LOCAL_BRIDGE_HEAD 0x80C6001E
PR_EMS_AB_LOCAL_BRIDGE_HEAD_A 0x80C6001E
PR_EMS_AB_LOCAL_BRIDGE_HEAD_ADDRESS 0x80C7001E
PR_EMS_AB_LOCAL_BRIDGE_HEAD_ADDRESS_A 0x80C7001E
PR_EMS_AB_LOCAL_BRIDGE_HEAD_ADDRESS_W 0x80C7001F
PR_EMS_AB_LOCAL_BRIDGE_HEAD_W 0x80C6001F
PR_EMS_AB_LOCAL_INITIAL_TURN 0x80C8000B
PR_EMS_AB_LOCAL_SCOPE 0x80C9101E
PR_EMS_AB_LOCAL_SCOPE_A 0x80C9101E
PR_EMS_AB_LOCAL_SCOPE_O 0x80C9000D
PR_EMS_AB_LOCAL_SCOPE_T 0x80C9101E
PR_EMS_AB_LOCAL_SCOPE_W 0x80C9101F
PR_EMS_AB_LOG_FILENAME 0x80CA001E
PR_EMS_AB_LOG_FILENAME_A 0x80CA001E
PR_EMS_AB_LOG_FILENAME_W 0x80CA001F
PR_EMS_AB_LOG_ROLLOVER_INTERVAL 0x80CB0003
PR_EMS_AB_MAIL_DROP 0x8C63001E
PR_EMS_AB_MAIL_DROP_A 0x8C63001E
PR_EMS_AB_MAIL_DROP_W 0x8C63001F
PR_EMS_AB_MAINTAIN_AUTOREPLY_HISTORY 0x80CC000B
PR_EMS_AB_MANAGER Contains the mail address for a mailbox owner's manager, expressed as a distinguished name.
PR_EMS_AB_MANAGER_A Contains the mail address for a mailbox

owner's manager, expressed as a distinguished name.

PR_EMS_AB_MANAGER_O Contains the mail address for a mailbox owner's manager, expressed as a distinguished name.

PR_EMS_AB_MANAGER_T Contains the mail address for a mailbox owner's manager, expressed as a distinguished name.

PR_EMS_AB_MANAGER_W Contains the mail address for a mailbox owner's manager, expressed as a distinguished name.

PR_EMS_AB_MAPI_DISPLAY_TYPE 0x80CD0003

PR_EMS_AB_MAPI_ID 0x80CE0003

PR_EMS_AB_MAXIMUM_OBJECT_ID 0x81690102

PR_EMS_AB_MDB_BACKOFF_INTERVAL Contains the number of minutes the information store waits before resending a message to the gateway.

PR_EMS_AB_MDB_MSG_TIME_OUT_PERIOD Contains the number of minutes a message can remain unread by a gateway before the information store will generate a nondelivery report.

PR_EMS_AB_MDB_OVER_QUOTA_LIMIT Contains the maximum amount of storage that the information store allocates to an object.

PR_EMS_AB_MDB_STORAGE_QUOTA Contains the amount of storage that the information store allocates to an object before generating a warning.

PR_EMS_AB_MDB_UNREAD_LIMIT Contains the maximum number of unread messages allowed in a gateway mailbox.

PR_EMS_AB_MDB_USE_DEFAULTS Determines whether a mailbox or public folder uses the storage quota set on the information store or the storage quota set on the object itself.

PR_EMS_AB_MEMBER Contains the list of members of a distribution list.

PR_EMS_AB_MEMBER_A Contains the list of members of a distribution list.

PR_EMS_AB_MEMBER_O Contains the list of members of a distribution list.

PR_EMS_AB_MEMBER_T Contains the list of members of a distribution list.

PR_EMS_AB_MEMBER_W Contains the list of members of a distribution list.

PR_EMS_AB_MESSAGE_TRACKING_ENABLED Determines whether

this message transfer agent or information store should keep message-tracking information.

PR_EMS_AB_MIME_TYPES 0x8C1C0102
PR_EMS_AB_MODERATED 0x81AC000B
PR_EMS_AB_MODERATOR 0x8199001E
PR_EMS_AB_MODERATOR_A 0x8199001E
PR_EMS_AB_MODERATOR_W 0x8199001F
PR_EMS_AB_MONITOR_CLOCK 0x80D6000B
PR_EMS_AB_MONITOR_SERVERS 0x80D7000B
PR_EMS_AB_MONITOR_SERVICES 0x80D8000B
PR_EMS_AB_MONITORED_CONFIGURATIONS 0x80D9101E
PR_EMS_AB_MONITORED_CONFIGURATIONS_A 0x80D9101E
PR_EMS_AB_MONITORED_CONFIGURATIONS_O 0x80D9000D
PR_EMS_AB_MONITORED_CONFIGURATIONS_T 0x80D9101E
PR_EMS_AB_MONITORED_CONFIGURATIONS_W 0x80D9101F
PR_EMS_AB_MONITORED_SERVERS 0x80DA101E
PR_EMS_AB_MONITORED_SERVERS_A 0x80DA101E
PR_EMS_AB_MONITORED_SERVERS_O 0x80DA000D
PR_EMS_AB_MONITORED_SERVERS_T 0x80DA101E
PR_EMS_AB_MONITORED_SERVERS_W 0x80DA101F
PR_EMS_AB_MONITORED_SERVICES 0x80DB101E
PR_EMS_AB_MONITORED_SERVICES_A 0x80DB101E
PR_EMS_AB_MONITORED_SERVICES_W 0x80DB101F
PR_EMS_AB_MONITORING_ALERT_DELAY 0x80DC0003
PR_EMS_AB_MONITORING_ALERT_UNITS 0x80DD0003
PR_EMS_AB_MONITORING_AVAILABILITY_STYLE 0x80DE0003
PR_EMS_AB_MONITORING_AVAILABILITY_WINDOW 0x80DF0102
PR_EMS_AB_MONITORING_CACHED_VIA_MAIL 0x80E0101E
PR_EMS_AB_MONITORING_CACHED_VIA_MAIL_A 0x80E0101E
PR_EMS_AB_MONITORING_CACHED_VIA_MAIL_O 0x80E0000D
PR_EMS_AB_MONITORING_CACHED_VIA_MAIL_T 0x80E0101E
PR_EMS_AB_MONITORING_CACHED_VIA_MAIL_W 0x80E0101F
PR_EMS_AB_MONITORING_CACHED_VIA_RPC 0x80E1101E
PR_EMS_AB_MONITORING_CACHED_VIA_RPC_A 0x80E1101E
PR_EMS_AB_MONITORING_CACHED_VIA_RPC_O 0x80E1000D
PR_EMS_AB_MONITORING_CACHED_VIA_RPC_T 0x80E1101E
PR_EMS_AB_MONITORING_CACHED_VIA_RPC_W 0x80E1101F

PR_EMS_AB_MONITORING_ESCALATION_PROCEDURE
0x80E21102
PR_EMS_AB_MONITORING_HOTSITE_POLL_INTERVAL
0x80E30003
PR_EMS_AB_MONITORING_HOTSITE_POLL_UNITS 0x80E40003
PR_EMS_AB_MONITORING_MAIL_UPDATE_INTERVAL
0x80E50003
PR_EMS_AB_MONITORING_MAIL_UPDATE_UNITS 0x80E60003
PR_EMS_AB_MONITORING_NORMAL_POLL_INTERVAL
0x80E70003
PR_EMS_AB_MONITORING_NORMAL_POLL_UNITS 0x80E80003
PR_EMS_AB_MONITORING_RECIPIENTS 0x80E9101E
PR_EMS_AB_MONITORING_RECIPIENTS_A 0x80E9101E
PR_EMS_AB_MONITORING_RECIPIENTS_NDR 0x80EA101E
PR_EMS_AB_MONITORING_RECIPIENTS_NDR_A 0x80EA101E
PR_EMS_AB_MONITORING_RECIPIENTS_NDR_O 0x80EA000D
PR_EMS_AB_MONITORING_RECIPIENTS_NDR_T 0x80EA101E
PR_EMS_AB_MONITORING_RECIPIENTS_NDR_W 0x80EA101F
PR_EMS_AB_MONITORING_RECIPIENTS_O 0x80E9000D
PR_EMS_AB_MONITORING_RECIPIENTS_T 0x80E9101E
PR_EMS_AB_MONITORING_RECIPIENTS_W 0x80E9101F
PR_EMS_AB_MONITORING_RPC_UPDATE_INTERVAL 0x80EB0003
PR_EMS_AB_MONITORING_RPC_UPDATE_UNITS 0x80EC0003
PR_EMS_AB_MONITORING_WARNING_DELAY 0x80ED0003
PR_EMS_AB_MONITORING_WARNING_UNITS 0x80EE0003
PR_EMS_AB_MTA_LOCAL_CRED 0x80EF001E
PR_EMS_AB_MTA_LOCAL_CRED_A 0x80EF001E
PR_EMS_AB_MTA_LOCAL_CRED_W 0x80EF001F
PR_EMS_AB_MTA_LOCAL_DESIG 0x80F0001E
PR_EMS_AB_MTA_LOCAL_DESIG_A 0x80F0001E
PR_EMS_AB_MTA_LOCAL_DESIG_W 0x80F0001F
PR_EMS_AB_N_ADDRESS 0x80F10102
PR_EMS_AB_N_ADDRESS_TYPE 0x80F20003
PR_EMS_AB_NETWORK_ADDRESS Contains a list of the names by
which a server is known to the various transports in use by the network.
PR_EMS_AB_NETWORK_ADDRESS_A Contains a list of the names by
which a server is known to the various transports in use by the network.

PR_EMS_AB_NETWORK_ADDRESS_W Contains a list of the names by which a server is known to the various transports in use by the network.

PR_EMS_AB_NEWSFEED_TYPE 0x81940003

PR_EMS_AB_NEWSGROUP 0x8198001E

PR_EMS_AB_NEWSGROUP_A 0x8198001E

PR_EMS_AB_NEWSGROUP_LIST 0x81960102

PR_EMS_AB_NEWSGROUP_W 0x8198001F

PR_EMS_AB_NNTP_CHARACTER_SET 0x817D001E

PR_EMS_AB_NNTP_CHARACTER_SET_A 0x817D001E

PR_EMS_AB_NNTP_CHARACTER_SET_W 0x817D001F

PR_EMS_AB_NNTP_CONTENT_FORMAT 0x8176001E

PR_EMS_AB_NNTP_CONTENT_FORMAT_A 0x8176001E

PR_EMS_AB_NNTP_CONTENT_FORMAT_W 0x8176001F

PR_EMS_AB_NNTP_DISTRIBUTIONS 0x8197101E

PR_EMS_AB_NNTP_DISTRIBUTIONS_A 0x8197101E

PR_EMS_AB_NNTP_DISTRIBUTIONS_FLAG 0x81A4000B

PR_EMS_AB_NNTP_DISTRIBUTIONS_W 0x8197101F

PR_EMS_AB_NNTP_NEWSFEEDS 0x81A6101E

PR_EMS_AB_NNTP_NEWSFEEDS_A 0x81A6101E

PR_EMS_AB_NNTP_NEWSFEEDS_O 0x81A6000D

PR_EMS_AB_NNTP_NEWSFEEDS_T 0x81A6101E

PR_EMS_AB_NNTP_NEWSFEEDS_W 0x81A6101F

PR_EMS_AB_NT_MACHINE_NAME 0x80F3001E

PR_EMS_AB_NT_MACHINE_NAME_A 0x80F3001E

PR_EMS_AB_NT_MACHINE_NAME_W 0x80F3001F

PR_EMS_AB_NT_SECURITY_DESCRIPTOR Contains the Windows NT access rights for this object.

PR_EMS_AB_NUM_OF_OPEN_RETRIES 0x80F40003

PR_EMS_AB_NUM_OF_TRANSFER_RETRIES 0x80F50003

PR_EMS_AB_OBJ_DIST_NAME 0x803C001E

PR_EMS_AB_OBJ_DIST_NAME_A 0x803C001E

PR_EMS_AB_OBJ_DIST_NAME_O 0x803C000D

PR_EMS_AB_OBJ_DIST_NAME_T 0x803C001E

PR_EMS_AB_OBJ_DIST_NAME_W 0x803C001F

PR_EMS_AB_OBJ_VIEW_CONTAINERS 0x81C7101E

PR_EMS_AB_OBJ_VIEW_CONTAINERS_A 0x81C7101E

PR_EMS_AB_OBJ_VIEW_CONTAINERS_O 0x81C7000D

PR_EMS_AB_OBJ_VIEW_CONTAINERS_T 0x81C7101E
PR_EMS_AB_OBJ_VIEW_CONTAINERS_W 0x81C7101F
PR_EMS_AB_OBJECT_CLASS_CATEGORY 0x80F60003
PR_EMS_AB_OBJECT_GUID 0x8C6D1102
PR_EMS_AB_OBJECT_OID 0xFFFA0102
PR_EMS_AB_OBJECT_VERSION 0x80F70003
PR_EMS_AB_OFF_LINE_AB_CONTAINERS 0x80F8101E
PR_EMS_AB_OFF_LINE_AB_CONTAINERS_A 0x80F8101E
PR_EMS_AB_OFF_LINE_AB_CONTAINERS_O 0x80F8000D
PR_EMS_AB_OFF_LINE_AB_CONTAINERS_T 0x80F8101E
PR_EMS_AB_OFF_LINE_AB_CONTAINERS_W 0x80F8101F
PR_EMS_AB_OFF_LINE_AB_SCHEDULE 0x80F90102
PR_EMS_AB_OFF_LINE_AB_SERVER 0x80FA001E
PR_EMS_AB_OFF_LINE_AB_SERVER_A 0x80FA001E
PR_EMS_AB_OFF_LINE_AB_SERVER_O 0x80FA000D
PR_EMS_AB_OFF_LINE_AB_SERVER_T 0x80FA001E
PR_EMS_AB_OFF_LINE_AB_SERVER_W 0x80FA001F
PR_EMS_AB_OFF_LINE_AB_STYLE 0x80FB0003
PR_EMS_AB_OID_TYPE 0x80FC0003
PR_EMS_AB_OM_OBJECT_CLASS 0x80FD0102
PR_EMS_AB_OM_SYNTAX 0x80FE0003
PR_EMS_AB_OOF_REPLY_TO_ORIGINATOR Determines whether Out of Office replies will be sent to the user who sends mail to a distribution list.
PR_EMS_AB_OPEN_RETRY_INTERVAL 0x81000003
PR_EMS_AB_ORGANIZATION_NAME The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ORGANIZATION_NAME_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ORGANIZATION_NAME_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ORGANIZATIONAL_UNIT_NAME The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ORGANIZATIONAL_UNIT_NAME_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ORGANIZATIONAL_UNIT_NAME_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.

PR_EMS_AB_ORIGINAL_DISPLAY_TABLE 0x81030102
PR_EMS_AB_ORIGINAL_DISPLAY_TABLE_MSDOS 0x81040102
PR_EMS_AB_OTHER_RECIPS 0xF000000D
PR_EMS_AB_OUTBOUND_HOST 0x818D0102
PR_EMS_AB_OUTBOUND_HOST_TYPE 0x81B0000B
PR_EMS_AB_OUTBOUND_NEWSFEED 0x8195001E
PR_EMS_AB_OUTBOUND_NEWSFEED_A 0x8195001E
PR_EMS_AB_OUTBOUND_NEWSFEED_W 0x8195001F
PR_EMS_AB_OUTBOUND_SITES 0x8105101E
PR_EMS_AB_OUTBOUND_SITES_A 0x8105101E
PR_EMS_AB_OUTBOUND_SITES_O 0x8105000D
PR_EMS_AB_OUTBOUND_SITES_T 0x8105101E
PR_EMS_AB_OUTBOUND_SITES_W 0x8105101F
PR_EMS_AB_OUTGOING_MSG_SIZE_LIMIT 0x818F0003
PR_EMS_AB_OVERRIDE_NNTP_CONTENT_FORMAT 0x81C6000B
PR_EMS_AB_OWA_SERVER 0x8C66001E
PR_EMS_AB_OWA_SERVER_A 0x8C66001E
PR_EMS_AB_OWA_SERVER_W 0x8C66001F
PR_EMS_AB_OWNER Contains the distinguished name of the mailbox that owns the object.
PR_EMS_AB_OWNER_A Contains the distinguished name of the mailbox that owns the object.
PR_EMS_AB_OWNER_BL Contains the backlink to the owner of a distribution list.
PR_EMS_AB_OWNER_BL_A Contains the backlink to the owner of a distribution list.
PR_EMS_AB_OWNER_BL_O Contains the backlink to the owner of a distribution list.
PR_EMS_AB_OWNER_BL_T Contains the backlink to the owner of a distribution list.
PR_EMS_AB_OWNER_BL_W Contains the backlink to the owner of a distribution list.
PR_EMS_AB_OWNER_O Contains the distinguished name of the mailbox that owns the object.
PR_EMS_AB_OWNER_T Contains the distinguished name of the mailbox that owns the object.
PR_EMS_AB_OWNER_W Contains the distinguished name of the

mailbox that owns the object.

PR_EMS_AB_P_SELECTOR 0x81060102

PR_EMS_AB_P_SELECTOR_INBOUND 0x81070102

PR_EMS_AB_PARENT_ENTRYID 0xFFFC0102

PR_EMS_AB_PER_MSG_DIALOG_DISPLAY_TABLE Contains a MAPI display table object describing a per-message options dialog.

PR_EMS_AB_PER_RECIP_DIALOG_DISPLAY_TABLE Contains a MAPI display table object describing a per-recipients options dialog.

PR_EMS_AB_PERIOD_REP_SYNC_TIMES 0x810A0102

PR_EMS_AB_PERIOD_REPL_STAGGER 0x810B0003

PR_EMS_AB_PERSONAL_TITLE 0x8C6B001E

PR_EMS_AB_PERSONAL_TITLE_A 0x8C6B001E

PR_EMS_AB_PERSONAL_TITLE_W 0x8C6B001F

PR_EMS_AB_PF_CONTACTS Contains the distinguished name of contact(s) of the folder.

PR_EMS_AB_PF_CONTACTS_A Contains the distinguished name of contact(s) of the folder.

PR_EMS_AB_PF_CONTACTS_O Contains the distinguished name of contact(s) of the folder.

PR_EMS_AB_PF_CONTACTS_T Contains the distinguished name of contact(s) of the folder.

PR_EMS_AB_PF_CONTACTS_W Contains the distinguished name of contact(s) of the folder.

PR_EMS_AB_PHONETIC_COMPANY_NAME 0x8C91001E

PR_EMS_AB_PHONETIC_COMPANY_NAME_A 0x8C91001E

PR_EMS_AB_PHONETIC_COMPANY_NAME_W 0x8C91001F

PR_EMS_AB_PHONETIC_DEPARTMENT_NAME 0x8C90001E

PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_A 0x8C90001E

PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_W 0x8C90001F

PR_EMS_AB_PHONETIC_DISPLAY_NAME 0x8C92001E

PR_EMS_AB_PHONETIC_DISPLAY_NAME_A 0x8C92001E

PR_EMS_AB_PHONETIC_DISPLAY_NAME_W 0x8C92001F

PR_EMS_AB_PHONETIC_GIVEN_NAME 0x8C8E001E

PR_EMS_AB_PHONETIC_GIVEN_NAME_A 0x8C8E001E

PR_EMS_AB_PHONETIC_GIVEN_NAME_W 0x8C8E001F

PR_EMS_AB_PHONETIC_SURNAME 0x8C8F001E

PR_EMS_AB_PHONETIC_SURNAME_A 0x8C8F001E

PR_EMS_AB_PHONETIC_SURNAME_W 0x8C8F001F
PR_EMS_AB_POP_CHARACTER_SET 0x8179001E
PR_EMS_AB_POP_CHARACTER_SET_A 0x8179001E
PR_EMS_AB_POP_CHARACTER_SET_W 0x8179001F
PR_EMS_AB_POP_CONTENT_FORMAT 0x8177001E
PR_EMS_AB_POP_CONTENT_FORMAT_A 0x8177001E
PR_EMS_AB_POP_CONTENT_FORMAT_W 0x8177001F
PR_EMS_AB_PORT_NUMBER 0x81B50003
PR_EMS_AB_POSTAL_ADDRESS Contains the mailing address of an object.
PR_EMS_AB_PREFERRED_DELIVERY_METHOD The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_PRESERVE_INTERNET_CONTENT 0x8C22000B
PR_EMS_AB_PRMD Refers to the X.400 administrative messaging domain (ADMD) associated with an object.
PR_EMS_AB_PRMD_A Refers to the X.400 administrative messaging domain (ADMD) associated with an object.
PR_EMS_AB_PRMD_W Refers to the X.400 administrative messaging domain (ADMD) associated with an object.
PR_EMS_AB_PROMO_EXPIRATION 0x81C20040
PR_EMS_AB_PROTOCOL_SETTINGS 0x81B6101E
PR_EMS_AB_PROTOCOL_SETTINGS_A 0x81B6101E
PR_EMS_AB_PROTOCOL_SETTINGS_W 0x81B6101F
PR_EMS_AB_PROXY_ADDRESSES Contains a list of foreign system addresses for this recipient.
PR_EMS_AB_PROXY_ADDRESSES_A Contains a list of foreign system addresses for this recipient.
PR_EMS_AB_PROXY_ADDRESSES_W Contains a list of foreign system addresses for this recipient.
PR_EMS_AB_PROXY_GENERATION_ENABLED 0x81B1000B
PR_EMS_AB_PROXY_GENERATOR_DLL Contains the name of a proxy generation DLL.
PR_EMS_AB_PROXY_GENERATOR_DLL_A Contains the name of a proxy generation DLL.
PR_EMS_AB_PROXY_GENERATOR_DLL_W Contains the name of a proxy generation DLL.
PR_EMS_AB_PUBLIC_DELEGATES Contains a list of users allowed to

send mail on behalf of the mailbox owner.

PR_EMS_AB_PUBLIC_DELEGATES_A Contains a list of users allowed to send mail on behalf of the mailbox owner.

PR_EMS_AB_PUBLIC_DELEGATES_BL Contains a list of users on behalf of which the mailbox owner can send mail.

PR_EMS_AB_PUBLIC_DELEGATES_BL_A Contains a list of users on behalf of which the mailbox owner can send mail.

PR_EMS_AB_PUBLIC_DELEGATES_BL_O Contains a list of users on behalf of which the mailbox owner can send mail.

PR_EMS_AB_PUBLIC_DELEGATES_BL_T Contains a list of users on behalf of which the mailbox owner can send mail.

PR_EMS_AB_PUBLIC_DELEGATES_BL_W Contains a list of users on behalf of which the mailbox owner can send mail.

PR_EMS_AB_PUBLIC_DELEGATES_O Contains a list of users allowed to send mail on behalf of the mailbox owner.

PR_EMS_AB_PUBLIC_DELEGATES_T Contains a list of users allowed to send mail on behalf of the mailbox owner.

PR_EMS_AB_PUBLIC_DELEGATES_W Contains a list of users allowed to send mail on behalf of the mailbox owner.

PR_EMS_AB_QUOTA_NOTIFICATION_SCHEDULE 0x81110102

PR_EMS_AB_QUOTA_NOTIFICATION_STYLE 0x81120003

PR_EMS_AB_RANGE_LOWER 0x81130003

PR_EMS_AB_RANGE_UPPER 0x81140003

PR_EMS_AB_RAS_ACCOUNT 0x81AD001E

PR_EMS_AB_RAS_ACCOUNT_A 0x81AD001E

PR_EMS_AB_RAS_ACCOUNT_W 0x81AD001F

PR_EMS_AB_RAS_CALLBACK_NUMBER 0x8115001E

PR_EMS_AB_RAS_CALLBACK_NUMBER_A 0x8115001E

PR_EMS_AB_RAS_CALLBACK_NUMBER_W 0x8115001F

PR_EMS_AB_RAS_PASSWORD 0x81AE0102

PR_EMS_AB_RAS_PHONE_NUMBER 0x8116001E

PR_EMS_AB_RAS_PHONE_NUMBER_A 0x8116001E

PR_EMS_AB_RAS_PHONE_NUMBER_W 0x8116001F

PR_EMS_AB_RAS_PHONEBOOK_ENTRY_NAME 0x8117001E

PR_EMS_AB_RAS_PHONEBOOK_ENTRY_NAME_A 0x8117001E

PR_EMS_AB_RAS_PHONEBOOK_ENTRY_NAME_W 0x8117001F

PR_EMS_AB_RAS_REMOTE_SRVR_NAME 0x8118001E

PR_EMS_AB_RAS_REMOTE_SRVR_NAME_A 0x8118001E
PR_EMS_AB_RAS_REMOTE_SRVR_NAME_W 0x8118001F
PR_EMS_AB_REFERRAL_LIST 0x81A3101E
PR_EMS_AB_REFERRAL_LIST_A 0x81A3101E
PR_EMS_AB_REFERRAL_LIST_W 0x81A3101F
PR_EMS_AB_REGISTERED_ADDRESS 0x81191102
PR_EMS_AB_REMOTE_BRIDGE_HEAD 0x811A001E
PR_EMS_AB_REMOTE_BRIDGE_HEAD_A 0x811A001E
PR_EMS_AB_REMOTE_BRIDGE_HEAD_ADDRESS 0x811B001E
PR_EMS_AB_REMOTE_BRIDGE_HEAD_ADDRESS_A 0x811B001E
PR_EMS_AB_REMOTE_BRIDGE_HEAD_ADDRESS_W 0x811B001F
PR_EMS_AB_REMOTE_BRIDGE_HEAD_W 0x811A001F
PR_EMS_AB_REMOTE_OUT_BH_SERVER 0x811C001E
PR_EMS_AB_REMOTE_OUT_BH_SERVER_A 0x811C001E
PR_EMS_AB_REMOTE_OUT_BH_SERVER_O 0x811C000D
PR_EMS_AB_REMOTE_OUT_BH_SERVER_T 0x811C001E
PR_EMS_AB_REMOTE_OUT_BH_SERVER_W 0x811C001F
PR_EMS_AB_REMOTE_SITE 0x811D001E
PR_EMS_AB_REMOTE_SITE_A 0x811D001E
PR_EMS_AB_REMOTE_SITE_O 0x811D000D
PR_EMS_AB_REMOTE_SITE_T 0x811D001E
PR_EMS_AB_REMOTE_SITE_W 0x811D001F
PR_EMS_AB_REPLICATED_OBJECT_VERSION 0x8C620003
PR_EMS_AB_REPLICATION_MAIL_MSG_SIZE 0x81680003
PR_EMS_AB_REPLICATION_SENSITIVITY 0x811E0003
PR_EMS_AB_REPLICATION_SIGNATURE 0x8C6E0102
PR_EMS_AB_REPLICATION_STAGGER 0x811F0003

PR_EMS_AB_REPORT_TO_ORIGINATOR Specifies whether the originator of a message is informed that the message submitted to a distribution list is too big.

PR_EMS_AB_REPORT_TO_OWNER Specifies whether the owner of a distribution list is informed that an oversized message has been submitted to the distribution list.

PR_EMS_AB_REPORTS Contains a list of direct reports.

PR_EMS_AB_REPORTS_A Contains a list of direct reports.

PR_EMS_AB_REPORTS_O Contains a list of direct reports.

PR_EMS_AB_REPORTS_T Contains a list of direct reports.

PR_EMS_AB_REPORTS_W Contains a list of direct reports.
PR_EMS_AB_REQ_SEQ 0x81220003
PR_EMS_AB_REQUIRE_SSL 0x8C25000B
PR_EMS_AB_RESPONSIBLE_LOCAL_DXA 0x8123001E
PR_EMS_AB_RESPONSIBLE_LOCAL_DXA_A 0x8123001E
PR_EMS_AB_RESPONSIBLE_LOCAL_DXA_O 0x8123000D
PR_EMS_AB_RESPONSIBLE_LOCAL_DXA_T 0x8123001E
PR_EMS_AB_RESPONSIBLE_LOCAL_DXA_W 0x8123001F
PR_EMS_AB_RETURN_EXACT_MSG_SIZE 0x8C52000B
PR_EMS_AB_RID_SERVER 0x8124001E
PR_EMS_AB_RID_SERVER_A 0x8124001E
PR_EMS_AB_RID_SERVER_O 0x8124000D
PR_EMS_AB_RID_SERVER_T 0x8124001E
PR_EMS_AB_RID_SERVER_W 0x8124001F
PR_EMS_AB_ROLE_OCCUPANT The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ROLE_OCCUPANT_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ROLE_OCCUPANT_O The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ROLE_OCCUPANT_T The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ROLE_OCCUPANT_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_ROOT_NEWSGROUPS_FOLDER_ID 0x81B20102
PR_EMS_AB_ROUTING_LIST Contains a list of entries describing the address types supported by a connector or gateway. The set of supported address types is called the connector's address space.
PR_EMS_AB_ROUTING_LIST_A Contains a list of entries describing the address types supported by a connector or gateway. The set of supported address types is called the connector's address space.
PR_EMS_AB_ROUTING_LIST_W Contains a list of entries describing the address types supported by a connector or gateway. The set of supported address types is called the connector's address space.
PR_EMS_AB_RTS_CHECKPOINT_SIZE 0x81270003
PR_EMS_AB_RTS_RECOVERY_TIMEOUT 0x81280003
PR_EMS_AB_RTS_WINDOW_SIZE 0x81290003

PR_EMS_AB_RUNS_ON 0x812A101E
PR_EMS_AB_RUNS_ON_A 0x812A101E
PR_EMS_AB_RUNS_ON_O 0x812A000D
PR_EMS_AB_RUNS_ON_T 0x812A101E
PR_EMS_AB_RUNS_ON_W 0x812A101F
PR_EMS_AB_S_SELECTOR 0x812B0102
PR_EMS_AB_S_SELECTOR_INBOUND 0x812C0102
PR_EMS_AB_SCHEMA_FLAGS 0x81730003
PR_EMS_AB_SCHEMA_VERSION 0x817C1003
PR_EMS_AB_SEARCH_FLAGS 0x812D0003
PR_EMS_AB_SEARCH_GUIDE 0x812E1102
PR_EMS_AB_SECURITY_POLICY 0x8C471102
PR_EMS_AB_SECURITY_PROTOCOL 0x80371102
PR_EMS_AB_SEE_ALSO The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_SEE_ALSO_A The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_SEE_ALSO_O The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_SEE_ALSO_T The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_SEE_ALSO_W The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_SEND_EMAIL_MESSAGE 0x8C31000B
PR_EMS_AB_SEND_TNEF 0x8191000B
PR_EMS_AB_SENIORITY_INDEX 0x8C9C0003
PR_EMS_AB_SERIAL_NUMBER 0x8130101E
PR_EMS_AB_SERIAL_NUMBER_A 0x8130101E
PR_EMS_AB_SERIAL_NUMBER_W 0x8130101F
PR_EMS_AB_SERVER 0xFFFE001E
PR_EMS_AB_SERVER_A 0xFFFE001E
PR_EMS_AB_SERVER_W 0xFFFE001F
PR_EMS_AB_SERVICE_ACTION_FIRST 0x81310003
PR_EMS_AB_SERVICE_ACTION_OTHER 0x81320003
PR_EMS_AB_SERVICE_ACTION_SECOND 0x81330003
PR_EMS_AB_SERVICE_RESTART_DELAY 0x81340003
PR_EMS_AB_SERVICE_RESTART_MESSAGE 0x8135001E

PR_EMS_AB_SERVICE_RESTART_MESSAGE_A 0x8135001E
PR_EMS_AB_SERVICE_RESTART_MESSAGE_W 0x8135001F
PR_EMS_AB_SESSION_DISCONNECT_TIMER 0x81360003
PR_EMS_AB_SITE_AFFINITY 0x8137101E
PR_EMS_AB_SITE_AFFINITY_A 0x8137101E
PR_EMS_AB_SITE_AFFINITY_W 0x8137101F
PR_EMS_AB_SITE_FOLDER_GUID 0x81660102
PR_EMS_AB_SITE_FOLDER_SERVER 0x8167001E
PR_EMS_AB_SITE_FOLDER_SERVER_A 0x8167001E
PR_EMS_AB_SITE_FOLDER_SERVER_O 0x8167000D
PR_EMS_AB_SITE_FOLDER_SERVER_T 0x8167001E
PR_EMS_AB_SITE_FOLDER_SERVER_W 0x8167001F
PR_EMS_AB_SITE_PROXY_SPACE 0x8138101E
PR_EMS_AB_SITE_PROXY_SPACE_A 0x8138101E
PR_EMS_AB_SITE_PROXY_SPACE_W 0x8138101F
PR_EMS_AB_SMIME_ALG_LIST_NA 0x8C33101E
PR_EMS_AB_SMIME_ALG_LIST_NA_A 0x8C33101E
PR_EMS_AB_SMIME_ALG_LIST_NA_W 0x8C33101F
PR_EMS_AB_SMIME_ALG_LIST_OTHER 0x8C34101E
PR_EMS_AB_SMIME_ALG_LIST_OTHER_A 0x8C34101E
PR_EMS_AB_SMIME_ALG_LIST_OTHER_W 0x8C34101F
PR_EMS_AB_SMIME_ALG_SELECTED_NA 0x8C35001E
PR_EMS_AB_SMIME_ALG_SELECTED_NA_A 0x8C35001E
PR_EMS_AB_SMIME_ALG_SELECTED_NA_W 0x8C35001F
PR_EMS_AB_SMIME_ALG_SELECTED_OTHER 0x8C36001E
PR_EMS_AB_SMIME_ALG_SELECTED_OTHER_A 0x8C36001E
PR_EMS_AB_SMIME_ALG_SELECTED_OTHER_W 0x8C36001F
PR_EMS_AB_SPACE_LAST_COMPUTED 0x81390040
PR_EMS_AB_STREET_ADDRESS Contains the street address of the
object.
PR_EMS_AB_STREET_ADDRESS_A Contains the street address of the
object.
PR_EMS_AB_STREET_ADDRESS_W Contains the street address of the
object.
PR_EMS_AB_SUB_REFS 0x813B101E
PR_EMS_AB_SUB_REFS_A 0x813B101E
PR_EMS_AB_SUB_REFS_O 0x813B000D

PR_EMS_AB_SUB_REFS_T 0x813B101E
PR_EMS_AB_SUB_REFS_W 0x813B101F
PR_EMS_AB_SUB_SITE 0x817B001E
PR_EMS_AB_SUB_SITE_A 0x817B001E
PR_EMS_AB_SUB_SITE_W 0x817B001F
PR_EMS_AB_SUBMISSION_CONT_LENGTH 0x813C0003
PR_EMS_AB_SUPPORT_SMIME_SIGNATURES 0x8C48000B
PR_EMS_AB_SUPPORTED_ALGORITHMS 0x8C550102
PR_EMS_AB_SUPPORTED_APPLICATION_CONTEXT 0x813D1102
PR_EMS_AB_SUPPORTING_STACK 0x813E101E
PR_EMS_AB_SUPPORTING_STACK_A 0x813E101E
PR_EMS_AB_SUPPORTING_STACK_BL 0x813F101E
PR_EMS_AB_SUPPORTING_STACK_BL_A 0x813F101E
PR_EMS_AB_SUPPORTING_STACK_BL_O 0x813F000D
PR_EMS_AB_SUPPORTING_STACK_BL_T 0x813F101E
PR_EMS_AB_SUPPORTING_STACK_BL_W 0x813F101F
PR_EMS_AB_SUPPORTING_STACK_O 0x813E000D
PR_EMS_AB_SUPPORTING_STACK_T 0x813E101E
PR_EMS_AB_SUPPORTING_STACK_W 0x813E101F
PR_EMS_AB_T_SELECTOR 0x81400102
PR_EMS_AB_T_SELECTOR_INBOUND 0x81410102
PR_EMS_AB_TAGGED_X509_CERT 0x8C6A1102
PR_EMS_AB_TARGET_ADDRESS Contains the foreign system e-mail address of a custom recipient.
PR_EMS_AB_TARGET_ADDRESS_A Contains the foreign system e-mail address of a custom recipient.
PR_EMS_AB_TARGET_ADDRESS_W Contains the foreign system e-mail address of a custom recipient.
PR_EMS_AB_TARGET_MTA 0x8142101E
PR_EMS_AB_TARGET_MTA_A 0x8142101E
PR_EMS_AB_TARGET_MTA_W 0x8142101F
PR_EMS_AB_TELEPHONE_NUMBER 0x8012101E
PR_EMS_AB_TELEPHONE_NUMBER_A 0x8012101E
PR_EMS_AB_TELEPHONE_NUMBER_W 0x8012101F
PR_EMS_AB_TELEPHONE_PERSONAL_PAGER 0x8C68001E
PR_EMS_AB_TELEPHONE_PERSONAL_PAGER_A 0x8C68001E
PR_EMS_AB_TELEPHONE_PERSONAL_PAGER_W 0x8C68001F

PR_EMS_AB_TELETEX_TERMINAL_IDENTIFIER The property is for X.500 compatibility and is not used by Microsoft Exchange Server.

PR_EMS_AB_TEMP_ASSOC_THRESHOLD 0x81440003

PR_EMS_AB_TOMBSTONE_LIFETIME Contains the number of days that a tombstone will exist before expiring.

PR_EMS_AB_TRACKING_LOG_PATH_NAME Contains the path name to where the message tracking logs are kept.

PR_EMS_AB_TRACKING_LOG_PATH_NAME_A Contains the path name to where the message tracking logs are kept.

PR_EMS_AB_TRACKING_LOG_PATH_NAME_W Contains the path name to where the message tracking logs are kept.

PR_EMS_AB_TRANS_RETRY_MINS 0x81470003

PR_EMS_AB_TRANS_TIMEOUT_MINS 0x81480003

PR_EMS_AB_TRANSFER_RETRY_INTERVAL Contains the number of seconds the message transfer agent waits before resending a message.

PR_EMS_AB_TRANSFER_TIMEOUT_NON_URGENT Contains the maximum transfer timeout (in minutes) to transfer a nonurgent message.

PR_EMS_AB_TRANSFER_TIMEOUT_NORMAL Contains the maximum time per kilobyte to transfer a normal message.

PR_EMS_AB_TRANSFER_TIMEOUT_URGENT Contains the maximum time per kilobyte to transfer an urgent message.

PR_EMS_AB_TRANSLATION_TABLE_USED 0x814D0003

PR_EMS_AB_TRANSPORT_EXPEDITED_DATA 0x814E000B

PR_EMS_AB_TRUST_LEVEL 0x814F0003

PR_EMS_AB_TURN_REQUEST_THRESHOLD 0x81500003

PR_EMS_AB_TWO_WAY_ALTERNATE_FACILITY 0x8151000B

PR_EMS_AB_TYPE 0x8C38001E

PR_EMS_AB_TYPE_A 0x8C38001E

PR_EMS_AB_TYPE_W 0x8C38001F

PR_EMS_AB_UNAUTH_ORIG_BL 0x8152101E

PR_EMS_AB_UNAUTH_ORIG_BL_A 0x8152101E

PR_EMS_AB_UNAUTH_ORIG_BL_O 0x8152000D

PR_EMS_AB_UNAUTH_ORIG_BL_T 0x8152101E

PR_EMS_AB_UNAUTH_ORIG_BL_W 0x8152101F

PR_EMS_AB_UNMERGED_ATTRIBUTES 0x8C6F1102

PR_EMS_AB_USE_SERVER_VALUES 0x817E000B

PR_EMS_AB_USE_SITE_VALUES 0x8183000B

PR_EMS_AB_USENET_SITE_NAME 0x8189001E
PR_EMS_AB_USENET_SITE_NAME_A 0x8189001E
PR_EMS_AB_USENET_SITE_NAME_W 0x8189001F
PR_EMS_AB_USER_PASSWORD The property is for X.500 compatibility and is not used by Microsoft Exchange Server.
PR_EMS_AB_USN_CHANGED Contains the update sequence number (USN) for an object at the time it was changed.
PR_EMS_AB_USN_CREATED Contains the update sequence number (USN) for the object at the time it was created.
PR_EMS_AB_USN_DSA_LAST_OBJ_REMOVED 0x81550003
PR_EMS_AB_USN_INTERSITE 0x817A0003
PR_EMS_AB_USN_LAST_OBJ_REM 0x81560003
PR_EMS_AB_USN_SOURCE Contains the
PR_EMS_AB_USN_CHANGED property that the object had on the server from which it was replicated.
PR_EMS_AB_VIEW_CONTAINER_1 0x81BF001E
PR_EMS_AB_VIEW_CONTAINER_1_A 0x81BF001E
PR_EMS_AB_VIEW_CONTAINER_1_W 0x81BF001F
PR_EMS_AB_VIEW_CONTAINER_2 0x81C0001E
PR_EMS_AB_VIEW_CONTAINER_2_A 0x81C0001E
PR_EMS_AB_VIEW_CONTAINER_2_W 0x81C0001F
PR_EMS_AB_VIEW_CONTAINER_3 0x81C1001E
PR_EMS_AB_VIEW_CONTAINER_3_A 0x81C1001E
PR_EMS_AB_VIEW_CONTAINER_3_W 0x81C1001F
PR_EMS_AB_VIEW_DEFINITION 0x8C1B1102
PR_EMS_AB_VIEW_FLAGS 0x8C180003
PR_EMS_AB_VIEW_SITE 0x81BE001E
PR_EMS_AB_VIEW_SITE_A 0x81BE001E
PR_EMS_AB_VIEW_SITE_W 0x81BE001F
PR_EMS_AB_VOICE_MAIL_FLAGS 0x8C401102
PR_EMS_AB_VOICE_MAIL_GREETINGS 0x8C3F101E
PR_EMS_AB_VOICE_MAIL_GREETINGS_A 0x8C3F101E
PR_EMS_AB_VOICE_MAIL_GREETINGS_W 0x8C3F101F
PR_EMS_AB_VOICE_MAIL_PASSWORD 0x8C3D001E
PR_EMS_AB_VOICE_MAIL_PASSWORD_A 0x8C3D001E
PR_EMS_AB_VOICE_MAIL_PASSWORD_W 0x8C3D001F
PR_EMS_AB_VOICE_MAIL_RECORDED_NAME 0x8C3E0102

PR_EMS_AB_VOICE_MAIL_RECORDING_LENGTH 0x8C431003
PR_EMS_AB_VOICE_MAIL_SPEED 0x8C420003
PR_EMS_AB_VOICE_MAIL_SYSTEM_GUID 0x8C3B0102
PR_EMS_AB_VOICE_MAIL_USER_ID 0x8C3C001E
PR_EMS_AB_VOICE_MAIL_USER_ID_A 0x8C3C001E
PR_EMS_AB_VOICE_MAIL_USER_ID_W 0x8C3C001F
PR_EMS_AB_VOICE_MAIL_VOLUME 0x8C410003
PR_EMS_AB_WWW_HOME_PAGE 0x8175001E
PR_EMS_AB_WWW_HOME_PAGE_A 0x8175001E
PR_EMS_AB_WWW_HOME_PAGE_W 0x8175001F
PR_EMS_AB_X121_ADDRESS 0x8158101E
PR_EMS_AB_X121_ADDRESS_A 0x8158101E
PR_EMS_AB_X121_ADDRESS_W 0x8158101F
PR_EMS_AB_X25_CALL_USER_DATA_INCOMING 0x81590102
PR_EMS_AB_X25_CALL_USER_DATA_OUTGOING 0x815A0102
PR_EMS_AB_X25_FACILITIES_DATA_INCOMING 0x815B0102
PR_EMS_AB_X25_FACILITIES_DATA_OUTGOING 0x815C0102
PR_EMS_AB_X25_LEASED_LINE_PORT 0x815D0102
PR_EMS_AB_X25_LEASED_OR_SWITCHED 0x815E000B
PR_EMS_AB_X25_REMOTE_MTA_PHONE 0x815F001E
PR_EMS_AB_X25_REMOTE_MTA_PHONE_A 0x815F001E
PR_EMS_AB_X25_REMOTE_MTA_PHONE_W 0x815F001F
PR_EMS_AB_X400_ATTACHMENT_TYPE 0x81600102
PR_EMS_AB_X400_SELECTOR_SYNTAX 0x81610003
PR_EMS_AB_X500_ACCESS_CONTROL_LIST 0x81620102
PR_EMS_AB_X500_NC 0x81A2001E
PR_EMS_AB_X500_NC_A 0x81A2001E
PR_EMS_AB_X500_NC_W 0x81A2001F
PR_EMS_AB_X500_RDN 0x81A1001E
PR_EMS_AB_X500_RDN_A 0x81A1001E
PR_EMS_AB_X500_RDN_W 0x81A1001F
PR_EMS_AB_X509_CERT 0x8C6A1102
PR_EMS_AB_XMIT_TIMEOUT_NON_URGENT 0x81630003
PR_EMS_AB_XMIT_TIMEOUT_NORMAL 0x81640003
PR_EMS_AB_XMIT_TIMEOUT_URGENT 0x81650003
PR_ENABLE_MESSAGE_TRACKING 0x01A60003
PR_ENABLE_MIMEWRAP 0x01650003

PR_ENABLE_REROUTING 0x01D00003
PR_ENABLE_SECURE_CONNECTIONS 0x01700003
PR_ENABLE_VRFY 0x01D50003
PR_END_ATTACH 0x400E0003
PR_END_BCC_RECIP 0x40060003
PR_END_CC_RECIP 0x40050003
PR_END_DATE Contains the ending date and time of an appointment as managed by a scheduling application.
PR_END_EMBED 0x40020003
PR_END_FOLDER 0x400B0003
PR_END_MESSAGE 0x400D0003
PR_END_P1_RECIP 0x40070003
PR_END_RECIP 0x40040003
PR_ENTRYID Contains a MAPI entry identifier used to open and edit properties of a particular MAPI object.
PR_ER_FLAG 0x40650003
PR_EVENT_SCRIPT 0x7102001E
PR_EVENTS_ROOT_FOLDER_ENTRYID 0x667A0102
PR_EXCEPTION_ENDTIME 0x7FFC0040
PR_EXCEPTION_STARTTIME 0x7FFB0040
PR_EXCESS_STORAGE_USED Contains the amount of storage actually used by a user who has exceeded the storage quota.
PR_EXPAND_BEGIN_TIME 0x36180040
PR_EXPAND_END_TIME 0x36190040
PR_EXPANDED_BEGIN_TIME 0x361A0040
PR_EXPANDED_END_TIME 0x361B0040
PR_EXPIRY_NUMBER Contains the number of time units that must pass before an unread message expires.
PR_EXPIRY_TIME Contains the date and time at which the messaging system can invalidate the content of a message.
PR_EXPIRY_TYPE 0x7CD10003
PR_EXPIRY_UNITS Contains the time unit to be used in calculating the time for a message to expire.
PR_EXPLICIT_CONVERSION Contains a value that indicates that a message sender has requested a message content conversion for a particular recipient.
PR_EXSMTP_XEXCH50_RESERVED2 0x406F0102

PR_EXTENDED_ACL_DATA 0x3FFE0102
PR_EXTENDED_RULE_ACTIONS 0x0E990102
PR_EXTENDED_RULE_CONDITION 0x0E9A0102
PR_EXTENDED_RULE_SIZE_LIMIT 0x0E9B0003
PR_EXTENSION_DLL 0x01D3001E
PR_FAST_TRANSFER 0x662F000D
PR_FAV_AUTOSUBFOLDERS 0x7D010003
PR_FAV_DEL_SUBS 0x7D080102
PR_FAV_DISPLAY_ALIAS 0x7C00001F
PR_FAV_DISPLAY_ALIAS_A 0x7C01001E
PR_FAV_DISPLAY_ALIAS_W 0x7C01001F
PR_FAV_DISPLAY_NAME 0x7C00001F
PR_FAV_DISPLAY_NAME_A 0x7C00001E
PR_FAV_DISPLAY_NAME_W 0x7C00001F
PR_FAV_GUID_MAP 0x7D050102
PR_FAV_INHERIT_AUTO 0x7D070003
PR_FAV_KNOWN_DELS_OLD 0x7D060102
PR_FAV_KNOWN_SUBS 0x7D040102
PR_FAV_LEVEL_MASK 0x7D030003
PR_FAV_PARENT_SOURCE_KEY 0x7D020102
PR_FAV_PUBLIC_SOURCE_KEY 0x7C020102
PR_FAVORITES_DEFAULT_NAME 0x6635001E
PR_FID 0x67480014
PR_FID_MID 0x664C0102
PR_FID_VID 0x664C0102
PR_FILE_SIZE 0x67470003
PR_FILE_SIZE_EXTENDED 0x67470014
PR_FILTERING_HOOKS Was originally meant to contain hook identifiers.
PR_FINDER_ENTRYID Contains the entry identifier for the folder in
which search results are typically created.
PR_FLAG_COMPLETE 0x10910040
PR_FLAG_ICON 0x10950003
PR_FLAG_STATUS 0x10900003
PR_FLAT_URL_NAME 0x670E001E
PR_FLAT_URL_NAME_A 0x670E001E
PR_FLAT_URL_NAME_W 0x670E001F
PR_FOLDER_ASSOCIATED_CONTENTS Contains an embedded

contents table object that provides information about the associated contents table.

PR_FOLDER_CHILD_COUNT Contains the number of subfolders contained within a public folder object.

PR_FOLDER_DESIGN_FLAGS Contains a reason for the status of the folder.

PR_FOLDER_DN Contains the DN of the folder.

PR_FOLDER_DN_A Contains the DN of the folder.

PR_FOLDER_DN_W Contains the DN of the folder.

PR_FOLDER_FLAGS Contains the type of folder that was requested in a call to the IMAPIFolder.CreateFolder method.

PR_FOLDER_OP_RATE 0x66B90003

PR_FOLDER_PATHNAME Contains the complete path name to the folder. Multiple strings are separated by a backslash (\) except for the All Public Folders folder and the Favorites folder, which have no path. All paths begin with a backslash (\).

PR_FOLDER_PATHNAME_A Contains the complete path name to the folder. Multiple strings are separated by a backslash (\) except for the All Public Folders folder and the Favorites folder, which have no path. All paths begin with a backslash (\).

PR_FOLDER_PATHNAME_W Contains the complete path name to the folder. Multiple strings are separated by a backslash (\) except for the All Public Folders folder and the Favorites folder, which have no path. All paths begin with a backslash (\).

PR_FOLDER_TYPE Contains a constant that indicates the folder type.

PR_FOLDER_VIEWS_ONLY 0x36E10003

PR_FOLDER_WEBVIEWINFO 0x36DF0102

PR_FOLDER_XVIEWINFO_E 0x36E00102

PR_FORCE_CLIENT_REFRESH 0x65A1000B

PR_FOREIGN_ID Contains the foreign message identifier of a message.

PR_FOREIGN_REPORT_ID Contains an identifier from the foreign system that is assigned to a gateway report received from a foreign system.

PR_FOREIGN_SUBJECT_ID Contains a subject identifier assigned to a gateway report received from a foreign system.

PR_FORM_CATEGORY Contains the category of a form.

PR_FORM_CATEGORY_A Contains the category of a form.

PR_FORM_CATEGORY_SUB Contains the subcategory of a form, as

defined by a client application.

PR_FORM_CATEGORY_SUB_A Contains the subcategory of a form, as defined by a client application.

PR_FORM_CATEGORY_SUB_W Contains the subcategory of a form, as defined by a client application.

PR_FORM_CATEGORY_W Contains the category of a form.

PR_FORM_CLSID Contains the 128-bit OLE globally unique identifier (GUID) of a form.

PR_FORM_CONTACT_NAME Contains the name of a contact for information concerning a form.

PR_FORM_CONTACT_NAME_A Contains the name of a contact for information concerning a form.

PR_FORM_CONTACT_NAME_W Contains the name of a contact for information concerning a form.

PR_FORM_DESIGNER_GUID Contains the unique identifier for the object used to design a form.

PR_FORM_DESIGNER_NAME Contains the display name for the object used to design the form.

PR_FORM_DESIGNER_NAME_A Contains the display name for the object used to design the form.

PR_FORM_DESIGNER_NAME_W Contains the display name for the object used to design the form.

PR_FORM_HIDDEN Contains true if a form is to be suppressed from display by compose menus and dialog boxes.

PR_FORM_HOST_MAP Contains a host map of available forms.

PR_FORM_MESSAGE_BEHAVIOR Contains true if a message should be composed in the current folder.

PR_FORM_VERSION Contains the version of a form.

PR_FORM_VERSION_A Contains the version of a form.

PR_FORM_VERSION_W Contains the version of a form.

PR_FREE_BUSY_FOR_LOCAL_SITE_ENTRYID Contains the entry identifier of a folder containing Schedule+ information giving free/busy information for users within a site. This information is represented by messages in a folder.

PR_FREEBUSY_ALL_EVENTS 0x68501102

PR_FREEBUSY_ALL_MONTHS 0x684F1003

PR_FREEBUSY_BUSY_EVENTS 0x68541102

PR_FREEBUSY_BUSY_MONTHS 0x68531003
PR_FREEBUSY_EMAIL_ADDRESS 0x6849001F
PR_FREEBUSY_END_RANGE 0x68480003
PR_FREEBUSY_ENTRYIDS 0x36E41102
PR_FREEBUSY_LAST_MODIFIED 0x68680040
PR_FREEBUSY_NUM_MONTHS 0x68690003
PR_FREEBUSY_OOF_EVENTS 0x68561102
PR_FREEBUSY_OOF_MONTHS 0x68551003
PR_FREEBUSY_START_RANGE 0x68470003
PR_FREEBUSY_TENTATIVE_EVENTS 0x68521102
PR_FREEBUSY_TENTATIVE_MONTHS 0x68511003
PR_FROM_I_HAVE 0x3FFF000B
PR_FTP_SITE Contains the recipient's File Transfer Protocol (FTP) site address.
PR_FTP_SITE_A Contains the recipient's File Transfer Protocol (FTP) site address.
PR_FTP_SITE_W Contains the recipient's File Transfer Protocol (FTP) site address.
PR_FX_DEL_PROP 0x40160003
PR_GATEWAY_NAME 0x010E001E
PR_GENDER Contains the recipient's gender.
PR_GENERATE_EXCHANGE_VIEWS 0x36E9000B
PR_GENERATION Contains a generational abbreviation that follows the full name of the recipient.
PR_GENERATION_A Contains a generational abbreviation that follows the full name of the recipient.
PR_GENERATION_W Contains a generational abbreviation that follows the full name of the recipient.
PR_GET_PROPS_EXCLUDE_PROP_ID_LIST 0x667E0102
PR_GIVEN_NAME Contains the first name of the recipient.
PR_GIVEN_NAME_A Contains the first name of the recipient.
PR_GIVEN_NAME_W Contains the first name of the recipient.
PR_GOVERNMENT_ID_NUMBER Contains a government identifier for the recipient.
PR_GOVERNMENT_ID_NUMBER_A Contains a government identifier for the recipient.
PR_GOVERNMENT_ID_NUMBER_W Contains a government identifier

for the recipient.

PR_GW_ADMIN_OPERATIONS The property is used to pass instructions between gateway administration tools and gateways.

PR_GW_MTSIN_ENTRYID Contains the entry identifier for a gateway's MTS-IN folder.

PR_GW_MTSOUT_ENTRYID Contains the entry identifier for a gateway's MTS-OUT folder.

PR_HANDLER_CLSID 0x7104001E

PR_HANDLER_LOG 0x7106101F

PR_HANDLER_LOG_A 0x7106101E

PR_HANDLER_LOG_MAX 0x71070003

PR_HANDLER_LOG_W 0x7106101F

PR_HANDLER_PROGID 0x7105001E

PR_HANDLER_PROGID_A 0x7105001E

PR_HANDLER_PROGID_W 0x7105001F

PR_HAS_ATTACH_FROM_IMAIL 0x665A000B

PR_HAS_DAMS 0x3FEA000B

PR_HAS_MODERATOR_RULES 0x663F000B

PR_HAS_NAMED_PROPERTIES Determines whether a message has named properties on it.

PR_HAS_RULES Determines whether there are rules set in the rule table on a folder.

PR_HASATTACH Contains at least one attachment.

PR_HEADER_FOLDER_ENTRYID Was originally meant to contain the entry identifier that a remote transport provider furnishes for its header folder.

PR_HIERARCHY_CHANGE_NUM 0x663E0003

PR_HIERARCHY_SERVER 0x6633001E

PR_HIERARCHY_SYNCHRONIZER The property is used with the MAPI OpenProperty function to retrieve the IExchangeExportChanges interface. This interface is for exporting only a folder's hierarchy changes, not its contents changes.

PR_HOBBIES Contains the names of the recipient's hobbies.

PR_HOBBIES_A Contains the names of the recipient's hobbies.

PR_HOBBIES_W Contains the names of the recipient's hobbies.

PR_HOME_ADDRESS_CITY Contains the name of the city in the messaging user's home address.

PR_HOME_ADDRESS_CITY_A Contains the name of the city in the messaging user's home address.

PR_HOME_ADDRESS_CITY_W Contains the name of the city in the messaging user's home address.

PR_HOME_ADDRESS_COUNTRY Contains the name of the country in the messaging user's home address.

PR_HOME_ADDRESS_COUNTRY_A Contains the name of the country in the messaging user's home address.

PR_HOME_ADDRESS_COUNTRY_W Contains the name of the country in the messaging user's home address.

PR_HOME_ADDRESS_POST_OFFICE_BOX Contains the post office box number in the messaging user's home address.

PR_HOME_ADDRESS_POST_OFFICE_BOX_A Contains the post office box number in the messaging user's home address.

PR_HOME_ADDRESS_POST_OFFICE_BOX_W Contains the post office box number in the messaging user's home address.

PR_HOME_ADDRESS_POSTAL_CODE Contains the postal code in the messaging user's home address.

PR_HOME_ADDRESS_POSTAL_CODE_A Contains the postal code in the messaging user's home address.

PR_HOME_ADDRESS_POSTAL_CODE_W Contains the postal code in the messaging user's home address.

PR_HOME_ADDRESS_STATE_OR_PROVINCE Contains the name of the state or province in the messaging user's home address.

PR_HOME_ADDRESS_STATE_OR_PROVINCE_A Contains the name of the state or province in the messaging user's home address.

PR_HOME_ADDRESS_STATE_OR_PROVINCE_W Contains the name of the state or province in the messaging user's home address.

PR_HOME_ADDRESS_STREET Contains the street address in the messaging user's home address.

PR_HOME_ADDRESS_STREET_A Contains the street address in the messaging user's home address.

PR_HOME_ADDRESS_STREET_W Contains the street address in the messaging user's home address.

PR_HOME_DSA 0x0110001E

PR_HOME_FAX_NUMBER Contains the telephone number of the recipient's home fax machine.

PR_HOME_FAX_NUMBER_A Contains the telephone number of the recipient's home fax machine.
PR_HOME_FAX_NUMBER_W Contains the telephone number of the recipient's home fax machine.
PR_HOME_TELEPHONE_NUMBER Contains the primary telephone number of the recipient's home.
PR_HOME_TELEPHONE_NUMBER_A Contains the primary telephone number of the recipient's home.
PR_HOME_TELEPHONE_NUMBER_W Contains the primary telephone number of the recipient's home.
PR_HOME2_TELEPHONE_NUMBER Contains a secondary telephone number at the recipient's home.
PR_HOME2_TELEPHONE_NUMBER_A Contains a secondary telephone number at the recipient's home.
PR_HOME2_TELEPHONE_NUMBER_A_MV 0x3A2F101E
PR_HOME2_TELEPHONE_NUMBER_MV 0x3A2F101E
PR_HOME2_TELEPHONE_NUMBER_W Contains a secondary telephone number at the recipient's home.
PR_HOME2_TELEPHONE_NUMBER_W_MV 0x3A2F101F
PR_HONOR_SENDER_FIELD 0x01770003
PR_HOST_ADDRESS 0x669F001E
PR_HTML Contains the Hypertext Markup Language (HTML) version of the message text.
PR_HTTP_DIRECTORY_PORT 0x662F0002
PR_HTTP_EXCHANGE_PORT 0x662D0002
PR_HTTP_REFERRAL_PORT 0x66310002
PR_IAB_ADDITIONAL_INFO 0x6620001E
PR_IAB_ADDITIONAL_INFO_SOURCE 0x6610001E
PR_IAB_ADDRTYPE 0x6605001E
PR_IAB_CONNECTION_TYPE 0x6630001E
PR_IAB_DEBUGWIN 0x660F001E
PR_IAB_DIAGTRACING 0x660D001E
PR_IAB_DISPLAY_NAME_SOURCE 0x6611001E
PR_IAB_DISTINGUISHED_NAME 0x6621001E
PR_IAB_EMAIL_ADDRESS_SOURCE 0x6606001E
PR_IAB_ERRLOGGING 0x660C001E
PR_IAB_LOGFILE 0x660B001E

PR_IAB_REMOTE_SERVER 0x6600001E
PR_IAB_SEARCH_BASE 0x6603001E
PR_IAB_SEARCH_FILTER 0x6604001E
PR_IAB_SERVER_PORT 0x6601001E
PR_IAB_SIZE_LIMIT 0x6608001E
PR_IAB_SIZE_LIMIT_LOW 0x660A001E
PR_IAB_TIME_LIMIT 0x6607001E
PR_IAB_TIME_LIMIT_LOW 0x6609001E
PR_IAB_TRACELEVEL 0x660E001E
PR_IAB_USER_NAME 0x6602001E
PR_IAB_USER_PASSWORD 0x67F1001E
PR_ICON Contains a bitmap of a full size icon for a form.
PR_ICON_INDEX 0x10800003
PR_ICS_CHANGE_KEY 0x66550102
PR_ICS_NOTIF 0x67500003
PR_ICS_STREAM 0x71030102
PR_IDENTITY_DISPLAY Contains the display name for a service provider's identity as defined within a messaging system.
PR_IDENTITY_DISPLAY_A Contains the display name for a service provider's identity as defined within a messaging system.
PR_IDENTITY_DISPLAY_W Contains the display name for a service provider's identity as defined within a messaging system.
PR_IDENTITY_ENTRYID Contains the entry identifier for a service provider's identity as defined within a messaging system.
PR_IDENTITY_SEARCH_KEY Contains the search key for a service provider's identity as defined within a messaging system.
PR_IDSET_GIVEN 0x40170003
PR_IFS_INTERNAL_DATA 0x10C80102
PR_IGNORE_COMMA_IN_FROM 0x01A00003
PR_IMAIL_CONTENT Contains the message text.
PR_IMAIL_IMAP4_CONTENT 0x66500003
PR_IMAIL_URL_CONTENT 0x66510003
PR_IMAP_INTERNAL_DATE 0x65F50040
PR_IMAP_LAST_ARTICLE_ID 0x67520003
PR_IMPLICIT_CONVERSION_PROHIBITED Contains true if a message transfer agent (MTA) is prohibited from making implicit message text conversions.

PR_IMPLIED_RESTRICTIONS 0x667F1102
PR_IMPORTANCE Contains a value indicating the message sender's opinion of the importance of a message.
PR_IN_CONFLICT The property indicates which embedded message attachments represent conflicting versions of a message in conflict.
PR_IN_OST 0x6704000B
PR_IN_REPLY_TO_ID 0x1042001E
PR_IN_REPLY_TO_ID_A 0x1042001E
PR_IN_REPLY_TO_ID_W 0x1042001F
PR_IN_TRANSIT 0x6618000B
PR_IN_TRANSIT_STATUS 0x66180003
PR_INBOUND_CANONICALIZATION 0x017C0003
PR_INBOUND_NEWSFEED_DN 0x668D001E
PR_INBOUND_THREADS 0x01120003
PR_INCOMPLETE_COPY Contains true if this message is an incomplete copy of another message.
PR_INCR_SYNC_CHG 0x40120003
PR_INCR_SYNC_DEL 0x40130003
PR_INCR_SYNC_END 0x40140003
PR_INCR_SYNC_MSG 0x40150003
PR_INET_MAIL_OVERRIDE_FORMAT 0x59020003
PR_INITIAL_DETAILS_PANE Contains the property page in a property sheet to be displayed first.
PR_INITIALS Contains the initials for parts of the full name of the recipient.
PR_INITIALS_A Contains the initials for parts of the full name of the recipient.
PR_INITIALS_W Contains the initials for parts of the full name of the recipient.
PR_INQ_HIGH_WATER_MARK 0x01AB0003
PR_INQ_RESTART_WATER_MARK 0x01AC0003
PR_INST_ID 0x674D0014
PR_INSTANCE_KEY Contains a value that uniquely identifies a row in a table.
PR_INSTANCE_NUM 0x674E0003
PR_INTERNAL_POST_REPLY 0x3FD50102
PR_INTERNAL_TRACE_INFO 0x666A0102

PR_INTERNET_ADDRESS_CONVERSION 0x66190003
PR_INTERNET_ADDRESSING_OPTIONS 0x66170003
PR_INTERNET_APPROVED 0x1030001E
PR_INTERNET_APPROVED_A 0x1030001E
PR_INTERNET_APPROVED_W 0x1030001F
PR_INTERNET_ARTICLE_NUMBER 0x0E230003
PR_INTERNET_BODY_STRUCTURE 0x66200102
PR_INTERNET_BODYPART_CONTENT 0x662E0102
PR_INTERNET_BODYPART_CONTENT_BODY 0x662F001E
PR_INTERNET_BODYPART_HEADERS 0x6621001E
PR_INTERNET_BODYPART_LINES 0x66300003
PR_INTERNET_BODYPART_SIZE 0x662D0003
PR_INTERNET_CHARSET 0x669A001E
PR_INTERNET_CLIENT_HOST_IP_NAME 0x6631001E
PR_INTERNET_CONTENT 0x66590102
PR_INTERNET_CONTENT_DESCRIPTION 0x662B001E
PR_INTERNET_CONTENT_DISPOSITION 0x6626001E
PR_INTERNET_CONTENT_DISPOSITION_PARAMETERS
0x6627101E
PR_INTERNET_CONTENT_EA 0x66590104
PR_INTERNET_CONTENT_HANDLE 0x66590103
PR_INTERNET_CONTENT_ID 0x662A001E
PR_INTERNET_CONTENT_LANGUAGE 0x6629001E
PR_INTERNET_CONTENT_MD5 0x66280003
PR_INTERNET_CONTENT_PARAMETERS 0x6625101E
PR_INTERNET_CONTENT_SUBTYPE 0x6624001E
PR_INTERNET_CONTENT_TRANSFER_ENCODING 0x662C001E
PR_INTERNET_CONTENT_TYPE 0x6623001E
PR_INTERNET_CONTROL 0x1031001E
PR_INTERNET_CONTROL_A 0x1031001E
PR_INTERNET_CONTROL_W 0x1031001F
PR_INTERNET_CONVERSION_CALLER_VERSION 0x6603001E
PR_INTERNET_CONVERSION_HINTS 0x66010003
PR_INTERNET_CONVERSION_OUTPUT_STREAM 0x66020003
PR_INTERNET_CONVERSION_STREAM 0x66020003
PR_INTERNET_CONVOBJ_FLAGS 0x66140003
PR_INTERNET_CPID 0x3FDE0003

PR_INTERNET_DISTRIBUTION 0x1032001E
PR_INTERNET_DISTRIBUTION_A 0x1032001E
PR_INTERNET_DISTRIBUTION_W 0x1032001F
PR_INTERNET_EXTERNAL_NEWS_ITEM 0x65700003
PR_INTERNET_FOLLOWUP_TO 0x1033001E
PR_INTERNET_FOLLOWUP_TO_A 0x1033001E
PR_INTERNET_FOLLOWUP_TO_W 0x1033001F
PR_INTERNET_FONT 0x661D0003
PR_INTERNET_FREE_DOC_INFO 0x67200102
PR_INTERNET_HEADER_LENGTH 0x66160003
PR_INTERNET_LAST_ERROR 0x661C0003
PR_INTERNET_LINES 0x10340003
PR_INTERNET_MDNS 0x66A5000B
PR_INTERNET_MESSAGE_FORMAT 0x66100003
PR_INTERNET_MESSAGE_HEADERS 0x661F101E
PR_INTERNET_MESSAGE_ID 0x1035001E
PR_INTERNET_MESSAGE_ID_A 0x1035001E
PR_INTERNET_MESSAGE_ID_W 0x1035001F
PR_INTERNET_MESSAGE_INFO 0x66C70102
PR_INTERNET_MESSAGE_OPTIONS 0x66180003
PR_INTERNET_MESSAGE_TEXT_FORMAT 0x66110003
PR_INTERNET_MIME_HEADERS 0x6622001E
PR_INTERNET_NEWSGROUP_NAME 0x66A7001E
PR_INTERNET_NEWSGROUPS 0x1036001E
PR_INTERNET_NEWSGROUPS_A 0x1036001E
PR_INTERNET_NEWSGROUPS_W 0x1036001F
PR_INTERNET_NNTP_PATH 0x1038001E
PR_INTERNET_NNTP_PATH_A 0x1038001E
PR_INTERNET_NNTP_PATH_W 0x1038001F
PR_INTERNET_ORGANIZATION 0x1037001E
PR_INTERNET_ORGANIZATION_A 0x1037001E
PR_INTERNET_ORGANIZATION_W 0x1037001F
PR_INTERNET_PARSE_STATE 0x66C60102
PR_INTERNET_PRECEDENCE 0x1041001E
PR_INTERNET_PRECEDENCE_A 0x1041001E
PR_INTERNET_PRECEDENCE_W 0x1041001F
PR_INTERNET_REFERENCES 0x1039001E

PR_INTERNET_REFERENCES_A 0x1039001E
PR_INTERNET_REFERENCES_W 0x1039001F
PR_INTERNET_REQUEST_HEADERS 0x661E0003
PR_INTERNET_REQUEST_LINES 0x66150003
PR_INTERNET_RFC821_FROM 0x661B001E
PR_INTERNET_SENT_REPRESENTING_NAME 0x40690102
PR_INTERNET_SITE_ADDRESS 0x661D001E
PR_INTERNET_SUBJECT 0x40680102
PR_INTERNET_TEMPORARY_FILENAME 0x661A001E
PR_INTERNET_TRANSMIT_INFO 0x66080003
PR_INTERNET_WRAPPING_LENGTH 0x66120003
PR_IP_ACCESS 0x0114101E
PR_IP_ACCESS_ATTRIBUTES 0x01F3101E
PR_IPM_APPOINTMENT_ENTRYID 0x36D00102
PR_IPM_CONTACT_ENTRYID 0x36D10102
PR_IPM_DAF_ENTRYID Contains the message store object entry identifier of a deferred action folder (DAF).
PR_IPM_DRAFTS_ENTRYID 0x36D70102
PR_IPM_FAVORITES_ENTRYID Contains the entry identifier for the Favorites folder.
PR_IPM_ID Was originally meant to contain an X.400 identifier of an interpersonal message.
PR_IPM_INBOX_ENTRYID 0x35E80102
PR_IPM_JOURNAL_ENTRYID 0x36D20102
PR_IPM_JUNK_ENTRYID 0x36D81102
PR_IPM_NOTE_ENTRYID 0x36D30102
PR_IPM_OUTBOX_ENTRYID Contains the entry identifier of the standard interpersonal message (IPM) Outbox folder.
PR_IPM_OUTBOX_SEARCH_KEY Was originally meant to contain the search key of the standard Outbox folder.
PR_IPM_PUBLIC_FOLDERS_ENTRYID Contains the entry identifier of the top-level folder for the IPM subtree.
PR_IPM_RETURN_REQUESTED Contains true if this message should be returned with a report.
PR_IPM_SENTMAIL_ENTRYID Contains the entry identifier of the standard IPM Sent Items folder.
PR_IPM_SENTMAIL_SEARCH_KEY Was originally meant to contain the

search key of the standard Sent Items folder.

PR_IPM_SUBTREE_ENTRYID Contains the entry identifier of the root of the IPM folder subtree in the message store's folder tree.

PR_IPM_SUBTREE_SEARCH_KEY Was originally meant to contain the search key of the interpersonal message (IPM) root folder.

PR_IPM_TASK_ENTRYID 0x36D40102

PR_IPM_WASTEBASKET_ENTRYID Contains the entry identifier of the standard IPM Deleted Items folder.

PR_IPM_WASTEBASKET_SEARCH_KEY Was originally meant to contain the search key of the standard Deleted Items folder.

PR_IS_NEWSGROUP 0x6697000B

PR_IS_NEWSGROUP_ANCHOR 0x6696000B

PR_ISDN_NUMBER Contains the recipient's ISDN-capable telephone number.

PR_ISDN_NUMBER_A Contains the recipient's ISDN-capable telephone number.

PR_ISDN_NUMBER_W Contains the recipient's ISDN-capable telephone number.

PR_ITEM_LEVEL_ACL 0x3D24000B

PR_JOURNAL_RECIPIENT_LIST 0x406C0102

PR_KEEP_CLEARPROPS 0x3DDC000B

PR_KEYWORD Contains a keyword identifying the recipient to the recipient's system administrator.

PR_KEYWORD_A Contains a keyword identifying the recipient to the recipient's system administrator.

PR_KEYWORD_W Contains a keyword identifying the recipient to the recipient's system administrator.

PR_LANGUAGE Contains a value indicating the language in which the messaging user is writing messages.

PR_LANGUAGE_A Contains a value indicating the language in which the messaging user is writing messages.

PR_LANGUAGE_W Contains a value indicating the language in which the messaging user is writing messages.

PR_LANGUAGES Contains an ASCII list of the languages incorporated in a message.

PR_LANGUAGES_A Contains an ASCII list of the languages incorporated in a message.

PR_LANGUAGES_W Contains an ASCII list of the languages incorporated in a message.

PR_LAST_ACCESS_TIME Contains the time of the last access to the object (server, folder, etc).

PR_LAST_CN_BROADCAST Contains the 22 byte (16-byte GUID + 6-byte Globcnt) change number of change most recently broadcast to other replicas.

PR_LAST_CONFLICT 0x3FC90102

PR_LAST_DATA_RECEIVAL_TIME Contains the last time when data was received from this server.

PR_LAST_FULL_BACKUP 0x66850040

PR_LAST_LOGOFF_TIME Contains the date and time that a mail user last logged off.

PR_LAST_LOGON_ATTEMPT 0x3DED0040

PR_LAST_LOGON_TIME Contains the date and time that the mail user last logged on.

PR_LAST_MODIFICATION_TIME Contains the date and time the object or subobject was last modified.

PR_LAST_MODIFIER_ENTRYID Contains the entry identifier of the last person to modify a message.

PR_LAST_MODIFIER_NAME Contains the display name of the last person to modify a message.

PR_LAST_MODIFIER_SID 0x0E590102

PR_LAST_MODIFIER_SID_AS_XML 0x0E6D001E

PR_LAST_OP_TIME 0x66DF0040

PR_LAST_SHORT_CN_BROADCAST 0x66F40102

PR_LAST_TRANSMISSION_TIME This indicates the length of time (in seconds) it took for the last mail to arrive from this server. If we are not exchanging messages with this server successfully, this property will be missing.

PR_LAST_VERB_EXECUTED 0x10810003

PR_LAST_VERB_EXECUTION_TIME 0x10820040

PR_LATEST_DELIVERY_TIME Contains the latest date and time when a message transfer agent (MTA) should deliver a message.

PR_LIST_HELP 0x1043001E

PR_LIST_HELP_A 0x1043001E

PR_LIST_HELP_W 0x1043001F

PR_LIST_SUBSCRIBE 0x1044001E
PR_LIST_SUBSCRIBE_A 0x1044001E
PR_LIST_SUBSCRIBE_W 0x1044001F
PR_LIST_UNSUBSCRIBE 0x1045001E
PR_LIST_UNSUBSCRIBE_A 0x1045001E
PR_LIST_UNSUBSCRIBE_W 0x1045001F
PR_LOCAL_COMMIT_TIME 0x67090040
PR_LOCAL_COMMIT_TIME_MAX 0x670A0040
PR_LOCAL_HOST_NAME 0x6600001E
PR_LOCAL_N_ADDRESS 0x3DD80102
PR_LOCAL_P_SELECTOR 0x3DD50102
PR_LOCAL_S_SELECTOR 0x3DD60102
PR_LOCAL_T_SELECTOR 0x3DD70102
PR_LOCALE_ID Contains the locale identifier of a logged-on mailbox user.
PR_LOCALITY Contains the name of the recipient's locality, such as the town or city.
PR_LOCALITY_A Contains the name of the recipient's locality, such as the town or city.
PR_LOCALITY_W Contains the name of the recipient's locality, such as the town or city.
PR_LOCATION Contains the location of the recipient in a format that is useful to the recipient's organization.
PR_LOCATION_A Contains the location of the recipient in a format that is useful to the recipient's organization.
PR_LOCATION_W Contains the location of the recipient in a format that is useful to the recipient's organization.
PR_LOCK_BRANCH_ID 0x38000014
PR_LOCK_DEPTH 0x38080003
PR_LOCK_ENLISTMENT_CONTEXT 0x38040102
PR_LOCK_EXPIRY_TIME 0x380A0040
PR_LOCK_GLID 0x380B0102
PR_LOCK_NULL_URL_W 0x380C001F
PR_LOCK_PERSISTENT 0x3807000B
PR_LOCK_RESOURCE_DID 0x38020014
PR_LOCK_RESOURCE_FID 0x38010014
PR_LOCK_RESOURCE_MID 0x38030014

PR_LOCK_RESOURCE_VID 0x38030014
PR_LOCK_SCOPE 0x38060002
PR_LOCK_TIMEOUT 0x38090003
PR_LOCK_TRANSIENT_ID 0x38070102
PR_LOCK_TYPE 0x38050002
PR_LOGFILE_DIRECTORY 0x3DEB001E
PR_LOGFILE_MAX_SIZE 0x3DEC0003
PR_LOGON_COUNT Contains the number of logons the connection has.
PR_LOGON_FAILURES 0x3DEE0003
PR_LOGON_FLAGS Contains the type of logon.
PR_LOGON_TIME Contains the time of logon.
PR_LONGTERM_ENTRYID_FROM_TABLE The property is used by the information store to return long-term MAPI entry identifiers within contents tables.
PR_LTID 0x67580102
PR_MAIL_PERMISSION Contains true if the messaging user is allowed to send and receive messages.
PR_MAILBEAT_BOUNCE_SERVER 0x6800001E
PR_MAILBEAT_REPLY_PROCESSED 0x68090040
PR_MAILBEAT_REPLY_RECEIVED 0x68080040
PR_MAILBEAT_REPLY_SENT 0x68060040
PR_MAILBEAT_REPLY_SUBMIT 0x68070040
PR_MAILBEAT_REQUEST_PROCESSED 0x68040040
PR_MAILBEAT_REQUEST_RECEIVED 0x68030040
PR_MAILBEAT_REQUEST_SENT 0x68010040
PR_MAILBEAT_REQUEST_SUBMIT 0x68020040
PR_MAILBEAT_SECURITY 0x6810001E
PR_MAILBOX_DISPLAY_NAME Contains display name of the logged on mailbox.
PR_MAILBOX_DISPLAY_NAME_A Contains display name of the logged on mailbox.
PR_MAILBOX_DISPLAY_NAME_W Contains display name of the logged on mailbox.
PR_MAILBOX_DN Contains the DN of the logged on mailbox.
PR_MAILBOX_DN_A Contains the DN of the logged on mailbox.
PR_MAILBOX_DN_W Contains the DN of the logged on mailbox.
PR_MAILBOX_NAME 0x3DE10102

PR_MAILBOX_OWNER_ENTRYID Contains the address book entry identifier for the owner of a mailbox.

PR_MAILBOX_OWNER_NAME Contains the name of the owner of a mailbox.

PR_MANAGER_NAME Contains the name of the recipient's manager.

PR_MANAGER_NAME_A Contains the name of the recipient's manager.

PR_MANAGER_NAME_W Contains the name of the recipient's manager.

PR_MAPI_DEFERRED_ERRORS 0x01940003

PR_MAPPING_SIGNATURE Contains the mapping signature for named properties of a particular MAPI object.

PR_MARK_INTERNET 0x016E0003

PR_MAX_CACHED_VIEWS 0x0E680003

PR_MAX_CONN_INBOUND 0x01160003

PR_MAX_CONN_OUTBOUND 0x01180003

PR_MAX_CONN_PER_HOST 0x011C0003

PR_MAX_DIALUP_BATCH_SIZE 0x01FB0003

PR_MAX_HOPS 0x011D0003

PR_MAX_INDICES 0x0E5E0003

PR_MAX_MSG_BATCH_COUNT 0x011A0003

PR_MAX_RECEIVED_HEADERS 0x66040003

PR_MAX_RECIPIENTS 0x01200003

PR_MAX_SUBMIT_MESSAGE_SIZE 0x666D0003

PR_MDB_DEFERRED_DELIVERY_T 0x3FEC0003

PR_MDB_DEFERRED_DELIVERY_V 0x3FEB0003

PR_MDB_PROVIDER Contains a provider-defined Guid structure that indicates the type of the message store.

PR_MEMBER_ENTRYID Contains a MAPI entry identifier used to open and edit properties of a particular MAPI object.

PR_MEMBER_ID Contains the identifier of a table member that has the described rights on a Microsoft Exchange Server folder or mailbox.

PR_MEMBER_NAME Contains the display name of a member of the ACL table.

PR_MEMBER_RIGHTS Contains a set of bits indicating the rights of this member on a folder or mailbox.

PR_MERGE_MIDSET_DELETED 0x0E7A0102

PR_MESSAGE_ATTACHMENTS Contains a table of restrictions that can be applied to a contents table to find all messages that contain attachment

subobjects meeting the restrictions.

PR_MESSAGE_BIFINFO 0x406A0102

PR_MESSAGE_CC_ME Contains true if this messaging user is specifically named as a carbon copy (CC) recipient of this message and is not part of a distribution list.

PR_MESSAGE_CLASS Contains a text string that identifies the sender-defined message class, such as IPM.Note.

PR_MESSAGE_CLASS_A Contains a text string that identifies the sender-defined message class, such as IPM.Note.

PR_MESSAGE_CLASS_W Contains a text string that identifies the sender-defined message class, such as IPM.Note.

PR_MESSAGE_CODEPAGE 0x3FFD0003

PR_MESSAGE_DELIVERY_ID Contains a message transfer system (MTS) identifier for a message delivered to a client application.

PR_MESSAGE_DELIVERY_TIME Contains the date and time a message was delivered.

PR_MESSAGE_DOWNLOAD_TIME Contains the estimated time to download a message from a remote server to a local message store.

PR_MESSAGE_FLAGS Contains a bitmask of flags indicating the origin and current state of a message.

PR_MESSAGE_LOCALE_ID Contains the language client used to create the message.

PR_MESSAGE_PROCESSED 0x65E8000B

PR_MESSAGE_RECIP_ME Contains true if this messaging user is specifically named as a primary (To), carbon copy (CC), or blind carbon copy (BCC) recipient of this message and is not part of a distribution list.

PR_MESSAGE_RECIPIENTS Contains a table of restrictions that can be applied to a contents table to find all messages that contain recipient subobjects meeting the restrictions.

PR_MESSAGE_SECURITY_LABEL Contains a security label for a message.

PR_MESSAGE_SITE_NAME 0x65E7001E

PR_MESSAGE_SITE_NAME_A 0x65E7001E

PR_MESSAGE_SITE_NAME_W 0x65E7001F

PR_MESSAGE_SIZE Contains the sum, in bytes, of the sizes of all properties on a message object.

PR_MESSAGE_SIZE_EXTENDED Contains the sum (in bytes) of the

sizes of all properties on a message object.

PR_MESSAGE_SUBMISSION_ID Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

PR_MESSAGE_SUBMISSION_ID_FROM_CLIENT Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

PR_MESSAGE_TO_ME Contains true if this messaging user is specifically named as a primary (To) recipient of this message and is not part of a distribution list.

PR_MESSAGE_TOKEN Contains an ASN.1 security token for a message.

PR_MESSAGE_TRACKING 0x011E0003

PR_MESSAGING_OP_RATE 0x66B80003

PR_MFI_CERTIFICATE 0x3DF20102

PR_MFI_DN 0x3DF4001E

PR_MFI_EMAIL_ADDRESS 0x3DF3001E

PR_MHS_COMMON_NAME Contains the common name of a messaging user for use in a message header.

PR_MHS_COMMON_NAME_A Contains the common name of a messaging user for use in a message header.

PR_MHS_COMMON_NAME_W Contains the common name of a messaging user for use in a message header.

PR_MID 0x674A0014

PR_MIDDLE_NAME Contains the recipient's middle name.

PR_MIDDLE_NAME_A Contains the recipient's middle name.

PR_MIDDLE_NAME_W Contains the recipient's middle name.

PR_MIDSET_DELETED Set of ID's of messages which do not exist in the folder.

PR_MIME_HANDLER_CLASSIDS 0x0E5E1048

PR_MIME_SIZE 0x67460003

PR_MIME_SIZE_EXTENDED 0x67460014

PR_MIME_TYPES 0x0122101E

PR_MINI_ICON Contains a bitmap of a half-size icon for a form.

PR_MM_ACP127_MESSAGE_ID 0x7003001E

PR_MM_ACP127_NOTIF_REQUEST 0x70040002

PR_MM_ADATP3_REFNO 0x70050002

PR_MM_CODRESS_FORMAT 0x70060002

PR_MM_COPY_PRECEDENCE 0x70070002

PR_MM_DISTRIBUTION_SIC 0x7008001E

PR_MM_EXEMPTED_ADDRESSES 0x70150102
PR_MM_EXTENDED_AUTH_INFO 0x70090040
PR_MM_HANDLING_INSTRUCTIONS 0x700A001E
PR_MM_ID 0x7017001E
PR_MM_MESSAGE_INSTRUCTIONS 0x700B001E
PR_MM_MESSAGE_TYPE 0x700C0002
PR_MM_MESSAGE_TYPE_ID 0x700D001E
PR_MM_ORIGINATOR_PLAD 0x700E001E
PR_MM_ORIGINATOR_REFERENCE 0x700F001E
PR_MM_OTHER_RECIPS_CC 0x7010001E
PR_MM_OTHER_RECIPS_TO 0x7011001E
PR_MM_PILOT_FORWARDED 0x7012001E
PR_MM_PRIMARY_PRECEDENCE 0x70130002
PR_MM_REPLY_REQUESTED 0x7CDC0002
PR_MM_USE_ADATP3 0x7014000B
PR_MM_USE_BILATERAL 0x7016000B
PR_MOBILE_TELEPHONE_NUMBER Contains the recipient's mobile telephone number.
PR_MOBILE_TELEPHONE_NUMBER_A Contains the recipient's mobile telephone number.
PR_MOBILE_TELEPHONE_NUMBER_W Contains the recipient's mobile telephone number.
PR_MODIFIER_FLAGS 0x405A0003
PR_MODIFY_VERSION Was originally meant to contain the message store version current at the time the message was last modified.
PR_MOVE_TO_FOLDER_ENTRYID Contains the entry identifier of the folder for the deferred action.
PR_MOVE_TO_STORE_ENTRYID Contains the entry identifier of the information store for the deferred action.
PR_MS_PROVIDER_UID 0x3DDF0102
PR_MSG_BODY_ID 0x3FDD0003
PR_MSG_EDITOR_FORMAT 0x59090003
PR_MSG_FOLD_TIME 0x66540040
PR_MSG_FOLDER_TEMPLATE_RES_10 0x6719001F
PR_MSG_FOLDER_TEMPLATE_RES_11 0x671A001F
PR_MSG_FOLDER_TEMPLATE_RES_12 0x671B001F
PR_MSG_FOLDER_TEMPLATE_RES_2 0x67110003

PR_MSG_FOLDER_TEMPLATE_RES_4 0x6713000B
PR_MSG_FOLDER_TEMPLATE_RES_5 0x6714000B
PR_MSG_FOLDER_TEMPLATE_RES_6 0x6715000B
PR_MSG_FOLDER_TEMPLATE_RES_7 0x67160102
PR_MSG_FOLDER_TEMPLATE_RES_8 0x67170102
PR_MSG_FOLDER_TEMPLATE_RES_9 0x67180102
PR_MSG_IN_OST 0x6704000B
PR_MSG_STATUS Contains a bitmask of property tags that define the status of a message.
PR_MSGTRACKING_ORG_GUID 0x406B0102
PR_MSP_ENCRYPTER_CERT 0x7CD8001E
PR_MSP_ENCRYPTER_DN 0x7CD7001E
PR_MSP_ROLE 0x3DD4001E
PR_MSP_SEQ_SIGNER_CERT 0x7CD6001E
PR_MSP_SEQ_SIGNER_DN 0x7CD5001E
PR_MSP_SIGN_DEFAULT 0x3DE7000B
PR_MSP_SIGNER_CERT 0x7CD4001E
PR_MSP_SIGNER_DN 0x7CD3001E
PR_MTS_ID Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).
PR_MTS_REPORT_ID Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).
PR_MTS_SUBJECT_ID The property appears on delivery and nondelivery reports generated by gateways. It contains the X.400 message identifier of the original message to which the report refers.
PR_MV_PKM_OPERATION_REQ 0x3F8E101F
PR_MV_PKM_VERSION_LABELS 0x3F92101F
PR_MV_PKM_VERSION_STATUS 0x3F93101F
PR_NDR_DIAG_CODE Contains a diagnostic code that forms part of a nondelivery report.
PR_NDR_REASON_CODE Contains an encoded reason for nondelivery that forms part of a nondelivery report.
PR_NDR_STATUS_CODE 0x0C200003
PR_NEW_ATTACH 0x40000003
PR_NEW_FX_FOLDER 0x40110102
PR_NEW_SUBS_GET_AUTO_ADD 0x65E6000B
PR_NEWSFEED_INFO 0x66A60102

PR_NEWSGROUP_COMPONENT 0x66A5001E
PR_NEWSGROUP_NAME 0x0E24001E
PR_NEWSGROUP_NAME_A 0x0E24001E
PR_NEWSGROUP_NAME_W 0x0E24001F
PR_NEWSGROUP_ROOT_FOLDER_ENTRYID 0x668C0102
PR_NEXT_BACKFILL_TIME Time at which the server will examine backfill list again.
PR_NEXT_BROADCAST_TIME Time at which the server will scan for changes to send to the rest of the replicas.
PR_NICKNAME Contains the recipient's nickname.
PR_NICKNAME_A Contains the recipient's nickname.
PR_NICKNAME_W Contains the recipient's nickname.
PR_NID 0x6716001E
PR_NNTP_ARTICLE_FOLDER_ENTRYID 0x668A0102
PR_NNTP_CONTROL_FOLDER_ENTRYID 0x668B0102
PR_NNTP_XREF 0x1040001E
PR_NNTP_XREF_A 0x1040001E
PR_NNTP_XREF_W 0x1040001F
PR_NO_EXCEPTION_HANDLING 0x01900003
PR_NON_IPM_SUBTREE_ENTRYID Contains the entry identifier of a top-level folder for the non-IPM subtree.
PR_NON_RECEIPT_NOTIFICATION_REQUESTED Contains true if a message sender wants notification of non-receipt for a specified recipient.
PR_NON_RECEIPT_REASON Contains reasons why a message was not received that forms part of a nondelivery report.
PR_NON_URGENT_MESSAGE_FREQ 0x01240003
PR_NON_URGENT_MESSAGE_TIMEOUT 0x01260003
PR_NON_WIN32_ACL 0x3D23000B
PR_NON_XMT_SECURITY_ROLE_1 0x0E7C0102
PR_NON_XMT_SECURITY_ROLE_1_AS_XML 0x0E7C001E
PR_NON_XMT_SECURITY_ROLE_2 0x0E7D0102
PR_NON_XMT_SECURITY_ROLE_2_AS_XML 0x0E7D001E
PR_NON_XMT_SECURITY_ROLE_3 0x0E7E0102
PR_NON_XMT_SECURITY_ROLE_3_AS_XML 0x0E7E001E
PR_NON_XMT_SECURITY_ROLE_4 0x0E7F0102
PR_NON_XMT_SECURITY_ROLE_4_AS_XML 0x0E7F001E
PR_NON_XMT_SECURITY_ROLE_5 0x0E800102

PR_NON_XMT_SECURITY_ROLE_5_AS_XML 0x0E80001E
PR_NON_XMT_SECURITY_ROLE_6 0x0E810102
PR_NON_XMT_SECURITY_ROLE_6_AS_XML 0x0E81001E
PR_NON_XMT_SECURITY_ROLE_7 0x0E820102
PR_NON_XMT_SECURITY_ROLE_7_AS_XML 0x0E82001E
PR_NON_XMT_SECURITY_ROLE_8 0x0E830102
PR_NON_XMT_SECURITY_ROLE_8_AS_XML 0x0E83001E
PR_NORMAL_MESSAGE_FREQ 0x01280003
PR_NORMAL_MESSAGE_SIZE Contains the total size of all normal messages in a folder.
PR_NORMAL_MESSAGE_SIZE_EXTENDED Contains the total size of all normal messages in a folder.
PR_NORMAL_MESSAGE_TIMEOUT 0x012A0003
PR_NORMAL_MSG_W_ATTACH_COUNT Contains the total number of normal messages with attachment.
PR_NORMALIZED_SUBJECT Contains the message subject with any prefix removed.
PR_NORMALIZED_SUBJECT_A Contains the message subject with any prefix removed.
PR_NORMALIZED_SUBJECT_W Contains the message subject with any prefix removed.
PR_NOT_822_RENDERABLE 0x6753000B

PR_NT_SECURITY_DESCRIPTOR Contains the NT Security Descriptors of the users or groups that can access the folder.
PR_NT_SECURITY_DESCRIPTOR_AS_XML 0x0E6A001E
PR_NT_SECURITY_DESCRIPTOR_AS_XML_A 0x0E6A001E
PR_NT_SECURITY_DESCRIPTOR_AS_XML_W 0x0E6A001F
PR_NT_USER_NAME Contains the Windows NT user account name of the last user to log on to the information store.
PR_NTSD_MODIFICATION_TIME 0x3FD60040
PR_NULL Represents a null value or setting of a property or reserves array space.
PR_OBJECT_TYPE Provides file type information for a non-Windows attachment.
PR_OBSOLETED_IPMS Contains the identifiers of messages that this message supersedes

PR_OFFICE_LOCATION Contains the recipient's office location.
PR_OFFICE_LOCATION_A Contains the recipient's office location.
PR_OFFICE_LOCATION_W Contains the recipient's office location.
PR_OFFICE_TELEPHONE_NUMBER Contains the primary telephone number of the recipient's place of business.
PR_OFFICE_TELEPHONE_NUMBER_A Contains the primary telephone number of the recipient's place of business.
PR_OFFICE_TELEPHONE_NUMBER_W Contains the primary telephone number of the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER Contains a secondary telephone number at the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER_A Contains a secondary telephone number at the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER_A_MV Contains a secondary telephone number at the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER_MV Contains a secondary telephone number at the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER_W Contains a secondary telephone number at the recipient's place of business.
PR_OFFICE2_TELEPHONE_NUMBER_W_MV Contains a secondary telephone number at the recipient's place of business.
PR_OFFLINE_ADDRBOOK_ENTRYID Contains the entry identifier of an offline address book.
PR_OFFLINE_CONNECTION_TYPE 0x67190003
PR_OFFLINE_FLAGS Contains the folder availability flag.
PR_OFFLINE_FOLDER 0x7C050003
PR_OFFLINE_MESSAGE_ENTRYID Contains the entry identifier of an offline message.
PR_OFFLINE_MODEM_NUMBER 0x6710001E
PR_OFFLINE_RETRIEVE_ALL_REMOTE_MAIL 0x6729000B
PR_OFFLINE_RETRIEVE_FILTER 0x67270102
PR_OFFLINE_RETRIEVE_FILTER_VALUES 0x67280102
PR_OLDEST_DELETED_ON 0x66420040
PR_OOF_REPLY_TYPE 0x40800003
PR_OOF_STATE Contains whether the Out of Office Assistant is enabled.
PR_OPEN_ACL_TABLE_COUNT Contains the total number of opened ACL tables.

PR_OPEN_ATTACH_COUNT Contains the total number of opened attachments.

PR_OPEN_ATTACH_TABLE_COUNT Contains the total number of opened attachment tables.

PR_OPEN_CONTENT_CATEG_AND_RESTRICTED_COUNT Contains the total number of opened categorized and restricted contents.

PR_OPEN_CONTENT_CATEG_COUNT Contains the total number of opened categorized contents.

PR_OPEN_CONTENT_COUNT Contains the total number of opened contents.

PR_OPEN_CONTENT_REGULAR_COUNT Contains the total number of opened regular contents.

PR_OPEN_CONTENT_RESTRICTED_COUNT Contains the total number of opened restricted contents.

PR_OPEN_FOLDER_COUNT Contains the total number of opened folders.

PR_OPEN_FXDESTSTREAM_COUNT Contains the total number of opened Fast Destination Streams.

PR_OPEN_FXSRCSTREAM_COUNT Contains the total number of opened Fast Source Streams.

PR_OPEN_HIERARCHY_COUNT Contains the total number of opened hierarchies.

PR_OPEN_MESSAGE_COUNT Contains the total number of opened messages.

PR_OPEN_NOTIFY_COUNT Contains the total number of opened notifications.

PR_OPEN_RULES_TABLE_COUNT Contains the total number opened Rules tables.

PR_OPEN_STREAMS_COUNT Contains the total number of opened streams.

PR_ORADDRESS 0x3DE20102

PR_ORG 0x6706001E

PR_ORG_ADDR_TYPE 0x403D001F

PR_ORG_EMAIL_ADDR 0x403E001F

PR_ORG_UNIT 0x012E001E

PR_ORG_UNIT_NAME 0x3BFE001E

PR_ORGANIZATION 0x012C001E

PR_ORGANIZATION_NAME 0x3BFF001E

PR_ORGANIZATIONAL_ID_NUMBER Contains an identifier for the recipient used within the recipient's organization.

PR_ORGANIZATIONAL_ID_NUMBER_A Contains an identifier for the recipient used within the recipient's organization.

PR_ORGANIZATIONAL_ID_NUMBER_W Contains an identifier for the recipient used within the recipient's organization.

PR_ORIG_ENTRYID 0x300F0102

PR_ORIG_MESSAGE_CLASS Contains the class of the original message for use in a report.

PR_ORIG_MESSAGE_CLASS_A Contains the class of the original message for use in a report.

PR_ORIG_MESSAGE_CLASS_W Contains the class of the original message for use in a report.

PR_ORIGIN_CHECK Contains a binary verification value enabling a delivery report recipient to verify the origin of the original message.

PR_ORIGIN_ID 0x664D0102

PR_ORIGINAL_AUTHOR_ADDRTYPE Contains the address type of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_ADDRTYPE_A Contains the address type of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_ADDRTYPE_W Contains the address type of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_EMAIL_ADDRESS Contains the e-mail address of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_EMAIL_ADDRESS_A Contains the e-mail address of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_EMAIL_ADDRESS_W Contains the e-mail address of the author of the first version of a message. That is ? the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_ENTRYID Contains the entry identifier of the author of the first version of a message, that is, the message before being

forwarded or replied to.

PR_ORIGINAL_AUTHOR_FLAGS 0x405D0003

PR_ORIGINAL_AUTHOR_NAME Contains the display name of the author of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_NAME_A Contains the display name of the author of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_NAME_W Contains the display name of the author of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_SEARCH_KEY Contains the search key of the author of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_AUTHOR_SID 0x0E550102

PR_ORIGINAL_AUTHOR_SID_AS_XML 0x0E76001E

PR_ORIGINAL_DELIVERY_TIME Contains a copy of the original message's delivery date and time in a thread.

PR_ORIGINAL_DISPLAY_BCC Contains the display names of any blind carbon copy (BCC) recipients of the original message.

PR_ORIGINAL_DISPLAY_BCC_A Contains the display names of any blind carbon copy (BCC) recipients of the original message.

PR_ORIGINAL_DISPLAY_BCC_W Contains the display names of any blind carbon copy (BCC) recipients of the original message.

PR_ORIGINAL_DISPLAY_CC Contains the display names of any carbon copy (CC) recipients of the original message.

PR_ORIGINAL_DISPLAY_CC_A Contains the display names of any carbon copy (CC) recipients of the original message.

PR_ORIGINAL_DISPLAY_CC_W Contains the display names of any carbon copy (CC) recipients of the original message.

PR_ORIGINAL_DISPLAY_NAME Contains the original display name for an entry copied from an address book to a personal address book or other writable address book.

PR_ORIGINAL_DISPLAY_NAME_A Contains the original display name for an entry copied from an address book to a personal address book or other writable address book.

PR_ORIGINAL_DISPLAY_NAME_W Contains the original display name

for an entry copied from an address book to a personal address book or other writable address book.

PR_ORIGINAL_DISPLAY_TO Contains the display names of the primary (To) recipients of the original message.

PR_ORIGINAL_DISPLAY_TO_A Contains the display names of the primary (To) recipients of the original message.

PR_ORIGINAL_DISPLAY_TO_W Contains the display names of the primary (To) recipients of the original message.

PR_ORIGINAL_EITS Contains a copy of the original encoded information types (EITs) for message text.

PR_ORIGINAL_ENTRYID Contains the original entry identifier for an entry copied from an address book to a personal address book or other writable address book.

PR_ORIGINAL_SEARCH_KEY Contains the original search key for an entry copied from an address book to a personal address book or other writable address book.

PR_ORIGINAL_SENDER_ADDRTYPE Contains the address type of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_ADDRTYPE_A Contains the address type of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_ADDRTYPE_W Contains the address type of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_EMAIL_ADDRESS Contains the e-mail address of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_EMAIL_ADDRESS_A Contains the e-mail address of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_EMAIL_ADDRESS_W Contains the e-mail address of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_ENTRYID Contains the entry identifier of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_FLAGS 0x401D0003

PR_ORIGINAL_SENDER_NAME Contains the display name of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_NAME_A Contains the display name of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_NAME_W Contains the display name of the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_SEARCH_KEY Contains the search key for the sender of the first version of a message, that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENDER_SID 0x0E4F0102

PR_ORIGINAL_SENDER_SID_AS_XML 0x0E70001E

PR_ORIGINAL_SENSITIVITY Contains the sensitivity value assigned by the sender of the first version of a message ? that is, the message before being forwarded or replied to.

PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE Contains the address type of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_A Contains the address type of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_W Contains the address type of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS Contains the e-mail address of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_A Contains the e-mail address of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_W Contains the e-mail address of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_ENTRYID Contains the entry

identifier of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_FLAGS 0x401E0003

PR_ORIGINAL_SENT_REPRESENTING_NAME Contains the display name of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_NAME_A Contains the display name of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_NAME_W Contains the display name of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_SEARCH_KEY Contains the search key of the messaging user on whose behalf the original message was sent.

PR_ORIGINAL_SENT_REPRESENTING_SID 0x0E500102

PR_ORIGINAL_SENT_REPRESENTING_SID_AS_XML 0x0E71001E

PR_ORIGINAL_SUBJECT Contains the subject of an original message for use in a report about the message.

PR_ORIGINAL_SUBJECT_A Contains the subject of an original message for use in a report about the message.

PR_ORIGINAL_SUBJECT_W Contains the subject of an original message for use in a report about the message.

PR_ORIGINAL_SUBMIT_TIME Contains the original submission date and time of the message in the report.

PR_ORIGINALLY_INTENDED_RECIP_ADDRTYPE Contains the address type of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIP_ADDRTYPE_A Contains the address type of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIP_ADDRTYPE_W Contains the address type of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIP_EMAIL_ADDRESS Contains the e-mail address of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIP_EMAIL_ADDRESS_A Contains the e-mail address of the originally intended recipient of an autoforwarded

message.

PR_ORIGINALLY_INTENDED_RECIP_EMAIL_ADDRESS_W

Contains the e-mail address of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIP_ENTRYID Contains the entry identifier of the originally intended recipient of an autoforwarded message.

PR_ORIGINALLY_INTENDED_RECIPIENT_NAME Contains the encoded name of the originally intended recipient of an autoforwarded message.

PR_ORIGINATING_MTA_CERTIFICATE Contains an identifier for the message transfer agent (MTA) that originated the message.

PR_ORIGINATOR_ADDR Contains the address of a message originator.

PR_ORIGINATOR_ADDRTYPE Contains the address type of a message originator.

PR_ORIGINATOR_AND_DL_EXPANSION_HISTORY Contains information about a message originator and a distribution list expansion history.

PR_ORIGINATOR_CERTIFICATE Contains an ASN.1 certificate for the message originator.

PR_ORIGINATOR_DELIVERY_REPORT_REQUESTED Contains true if a message sender requests a delivery report for a particular recipient from the messaging system before the message is placed in the message store.

PR_ORIGINATOR_ENTRYID Contains the entry identifier of a message source.

PR_ORIGINATOR_FLAGS 0x405B0003

PR_ORIGINATOR_NAME Contains the display name of a message source.

PR_ORIGINATOR_NON_DELIVERY_REPORT_REQUESTED Contains true if a message sender requests a nondelivery report for a particular recipient.

PR_ORIGINATOR_REQUESTED_ALTERNATE_RECIPIENT Contains an entry identifier for an alternate recipient designated by the sender.

PR_ORIGINATOR_RETURN_ADDRESS Contains the binary-encoded return address of the message originator.

PR_ORIGINATOR_SEARCH_KEY 0x40610102

PR_ORIGINATOR_SID 0x0E530102

PR_ORIGINATOR_SID_AS_XML 0x0E74001E

PR_OST_ENCRYPTION 0x67020003

PR_OST_OSTID 0x7C040102

PR_OST_VALIDATED 0x7C03000B

PR_OTHER_ADDRESS_CITY Contains the name of the city in the messaging user's other address.

PR_OTHER_ADDRESS_CITY_A Contains the name of the city in the messaging user's other address.

PR_OTHER_ADDRESS_CITY_W Contains the name of the city in the messaging user's other address.

PR_OTHER_ADDRESS_COUNTRY Contains the name of the country in the messaging user's other address.

PR_OTHER_ADDRESS_COUNTRY_A Contains the name of the country in the messaging user's other address.

PR_OTHER_ADDRESS_COUNTRY_W Contains the name of the country in the messaging user's other address.

PR_OTHER_ADDRESS_POST_OFFICE_BOX Contains the post office box number in the messaging user's other address.

PR_OTHER_ADDRESS_POST_OFFICE_BOX_A Contains the post office box number in the messaging user's other address.

PR_OTHER_ADDRESS_POST_OFFICE_BOX_W Contains the post office box number in the messaging user's other address.

PR_OTHER_ADDRESS_POSTAL_CODE Contains the postal code in the messaging user's other address.

PR_OTHER_ADDRESS_POSTAL_CODE_A Contains the postal code in the messaging user's other address.

PR_OTHER_ADDRESS_POSTAL_CODE_W Contains the postal code in the messaging user's other address.

PR_OTHER_ADDRESS_STATE_OR_PROVINCE Contains the name of the state or province in the messaging user's other address.

PR_OTHER_ADDRESS_STATE_OR_PROVINCE_A Contains the name of the state or province in the messaging user's other address.

PR_OTHER_ADDRESS_STATE_OR_PROVINCE_W Contains the name of the state or province in the messaging user's other address.

PR_OTHER_ADDRESS_STREET Contains the street address in the messaging user's other address.

PR_OTHER_ADDRESS_STREET_A Contains the street address in the messaging user's other address.

PR_OTHER_ADDRESS_STREET_W Contains the street address in the messaging user's other address.

PR_OTHER_OP_RATE 0x66BE0003

PR_OTHER_TELEPHONE_NUMBER Contains an alternate telephone number for the recipient.

PR_OTHER_TELEPHONE_NUMBER_A Contains an alternate telephone number for the recipient.

PR_OTHER_TELEPHONE_NUMBER_W Contains an alternate telephone number for the recipient.

PR_OU1 0x6707001E

PR_OU2 0x6708001E

PR_OU3 0x6709001E

PR_OU4 0x670A001E

PR_OUT_CLEANUP_INTERVAL 0x01E00003

PR_OUT_FORCED_RELOAD_INTERVAL 0x01E30003

PR_OUT_LAZY_DELETE_DEPTH 0x01E70003

PR_OUT_LAZY_MOVE_DEPTH 0x01E60003

PR_OUT_MAX_MSG_RATE 0x01E40003

PR_OUT_MAX_RELOAD_DELAY 0x01E10003

PR_OUT_MIN_RELOAD_INTERVAL 0x01E20003

PR_OUT_RELOAD_LOOP_WAIT 0x01E50003

PR_OUTBOUND_NEWSFEED_DN 0x668E001E

PR_OUTBOUND_THREADS 0x01300003

PR_OUTLOOK_2003_ENTRYIDS 0x36D81102

PR_OUTLOOK_AUTOARCHIVE_AUTO_ARCHIVE_FILE 0x0325001E

PR_OUTLOOK_AUTOARCHIVE_DELETE_EXPIRED_MESSAGES 0x0322000B

PR_OUTLOOK_AUTOARCHIVE_DO_AUTO_ARCHIVE 0x0320000B

PR_OUTLOOK_AUTOARCHIVE_INCLUDE_DONT_AGE_ME 0x033C000B

PR_OUTLOOK_AUTOARCHIVE_NUMBER_OF_DAYS_FOR_AUTO_ARCHIVE 0x03240003

PR_OUTLOOK_AUTOARCHIVE_PROMPT_FOR_AUTO_ARCHIVE 0x0321000B

PR_OUTLOOK_GENERAL_AFTER_MOVE_MESSAGE 0x013B0003

PR_OUTLOOK_GENERAL_AUTO_NAME_CHECK 0x0332000B

PR_OUTLOOK_GENERAL_COMMA_ADDRESS_SEPARATOR

0x0350000B

PR_OUTLOOK_GENERAL_CONFIRM_ON_DELETE 0x0111000B

PR_OUTLOOK_GENERAL_EMPTY_WASTEBASKET 0x0115000B

PR_OUTLOOK_GENERAL_REMOVE_SCHEDULE_PLUS 0x0344000B

PR_OUTLOOK_GENERAL_SELECT_ENTIRE_WORD 0x0118000B

PR_OUTLOOK_GENERAL_USE_SCHEDULE_PLUS 0x032B000B

PR_OUTLOOK_MAIL_ARRIVES_CHANGE_POINTER_ON_NEW_MAIL 0x023F000B

PR_OUTLOOK_MAIL_ARRIVES_NOTIFY_WITH_DIALOG_ON_NEW_MAIL 0x0240000B

PR_OUTLOOK_MAIL_ARRIVES_PLAY_SOUND_WHEN_NEW_MAIL 0x023E000B

PR_OUTLOOK_SENDING_ADD_SIG_TO_NEW_MESSAGE 0x0338000B

PR_OUTLOOK_SENDING_ADD_SIG_TO_REPLY_MESSAGE 0x0339000B

PR_OUTLOOK_SENDING_CLOSE_ORIGINAL_MESSAGE 0x0132000B

PR_OUTLOOK_SENDING_DEFAULT_PRIORITY 0x01400003

PR_OUTLOOK_SENDING_DEFAULT_SENSITIVITY 0x014F0003

PR_OUTLOOK_SENDING_GEN_DELIVERY_RECEIPT 0x014C000B

PR_OUTLOOK_SENDING_GEN_READ_RECEIPT 0x0141000B

PR_OUTLOOK_SENDING_INCLUDE_ORG_MESSAGE 0x0130000B

PR_OUTLOOK_SENDING_INDENT_ORG_MESSAGE 0x0131000B

PR_OUTLOOK_SENDING_MARK_MY_COMMENTS_WITH 0x0319000B

PR_OUTLOOK_SENDING_SAVE_FORWARDS 0x0205000B

PR_OUTLOOK_SENDING_SAVE_REPLIES 0x0208000B

PR_OUTLOOK_SENDING_SAVE_SENT_MAIL 0x0142000B

PR_OUTLOOK_SENDING_SHOW_BCC 0x014B000B

PR_OUTLOOK_SENDING_SHOWFROM 0x014D000B

PR_OUTQ_HIGH_WATER_MARK 0x01A90003

PR_OUTQ_RESTART_WATER_MARK 0x01AA0003

PR_OVERALL_AGE_LIMIT 0x66990003

PR_OVERALL_MSG_AGE_LIMIT 0x66930003

PR_OWA_URL 0x10F1001E

PR_OWN_STORE_ENTRYID Contains the entry identifier of a transport's

tightly coupled message store.

PR_OWNER_APPT_ID Contains an identifier for an appointment in the owner's schedule.

PR_OWNER_COUNT Contains the number of owners of a public folder.

PR_OWNER_NAME 0x66FE001E

PR_P1_CONTENT 0x11000102

PR_P1_CONTENT_TYPE 0x11010102

PR_P7_PASSWORD 0x3DE80102

PR_P772_DEFAULT 0x3DD2000B

PR_PACKED_NAME_PROPS 0x361C0102

PR_PACKET_RATE 0x66FF0003

PR_PAGER_TELEPHONE_NUMBER Contains the recipient's pager telephone number.

PR_PAGER_TELEPHONE_NUMBER_A Contains the recipient's pager telephone number.

PR_PAGER_TELEPHONE_NUMBER_W Contains the recipient's pager telephone number.

PR_PARENT_CATEG_ID 0x674C0014

PR_PARENT_DISPLAY Contains the display name of the folder in which a message was found during a search.

PR_PARENT_DISPLAY_A Contains the display name of the folder in which a message was found during a search.

PR_PARENT_DISPLAY_W Contains the display name of the folder in which a message was found during a search.

PR_PARENT_ENTRYID Contains the entry identifier of the folder containing a folder or message.

PR_PARENT_FID 0x67490014

PR_PARENT_KEY Was originally meant to contain a value used in correlating conversation threads.

PR_PARENT_SOURCE_KEY Contains the PR_SOURCE_KEY property of the parent folder of a folder.

PR_PARENT_URL_NAME 0x670D001E

PR_PARENT_URL_NAME_A 0x670D001E

PR_PARENT_URL_NAME_W 0x670D001F

PR_PCL_EXPORT 0x675A0102

PR_PERSONAL_FREEBUSY 0x686C0102

PR_PERSONAL_HOME_PAGE Contains the web address (URL) of the recipient's personal home page.

PR_PERSONAL_HOME_PAGE_A Contains the web address (URL) of the recipient's personal home page.

PR_PERSONAL_HOME_PAGE_W Contains the web address (URL) of the recipient's personal home page.

PR_PF_ADMIN_DESCRIPTION_A 0x671C001E

PR_PF_ADMIN_DESCRIPTION_W 0x671C001F

PR_PF_CONTACTS_GUID 0x0E600102

PR_PF_CONTACTS_NTDN 0x0E60101E

PR_PF_DISALLOW_MDB_WIDE_EXPIRY 0x6723000B

PR_PF_DISPLAY_NAME Contains the display name of the public folder.

PR_PF_DISPLAY_NAME_W Contains the display name of the public folder.

PR_PF_MSG_AGE_LIMIT Contains the default age limit for this folder, for this replica.

PR_PF_MSG_SIZE_LIMIT 0x67220003

PR_PF_OVER_HARD_QUOTA_LIMIT 0x67210003

PR_PF_PLATINUM_HOME_MDB 0x671E000B

PR_PF_PROXY 0x671D0102

PR_PF_PROXY_REQUIRED 0x671F000B

PR_PF_QUOTA_STYLE 0x67790003

PR_PF_REPLICA_MDB 0x406D0102

PR_PF_STORAGE_QUOTA 0x677B0003

PR_PHYSICAL_DELIVERY_BUREAU_FAX_DELIVERY Contains true if the messaging system should use a fax bureau for physical delivery of this message.

PR_PHYSICAL_DELIVERY_MODE Contains a bitmask of flags defining the physical delivery mode (for example, special delivery) for a message designated for a specific recipient.

PR_PHYSICAL_DELIVERY_REPORT_REQUEST Contains the mode of a report to be delivered to a particular message recipient upon completion of physical message delivery or delivery by the message handling system.

PR_PHYSICAL_FORWARDING_ADDRESS Contains the physical forwarding address of a message recipient and is used only with message reports.

PR_PHYSICAL_FORWARDING_ADDRESS_REQUESTED Contains

true if a message sender requests the message transfer agent to attach a physical forwarding address for a message recipient.

PR_PHYSICAL_FORWARDING_PROHIBITED Contains true if a message sender prohibits physical message forwarding for a specific recipient.

PR_PHYSICAL_RENDITION_ATTRIBUTES Contains an ASN.1 object identifier used for rendering message attachments.

PR_PKM_DOC_INTERNAL_STATE 0x3F8F001F

PR_PKM_DOC_STATUS 0x3F8D001F

PR_PKM_INTERNAL_DATA 0x3F940102

PR_PKM_LAST_UNAPPROVED_VID 0x3F910102

PR_POST_DIAL_SLEEP 0x01FA0003

PR_POST_FOLDER_ENTRIES 0x103B0102

PR_POST_FOLDER_NAMES 0x103C001E

PR_POST_FOLDER_NAMES_A 0x103C001E

PR_POST_FOLDER_NAMES_W 0x103C001F

PR_POST_OFFICE_BOX Contains the number or identifier of the recipient's post office box.

PR_POST_OFFICE_BOX_A Contains the number or identifier of the recipient's post office box.

PR_POST_OFFICE_BOX_W Contains the number or identifier of the recipient's post office box.

PR_POST_REPLY_DENIED 0x103F000B

PR_POST_REPLY_FOLDER_ENTRIES 0x103D0102

PR_POST_REPLY_FOLDER_NAMES 0x103E001E

PR_POST_REPLY_FOLDER_NAMES_A 0x103E001E

PR_POST_REPLY_FOLDER_NAMES_W 0x103E001F

PR_POSTAL_ADDRESS Contains the recipient's postal address.

PR_POSTAL_ADDRESS_A Contains the recipient's postal address.

PR_POSTAL_ADDRESS_W Contains the recipient's postal address.

PR_POSTAL_CODE Contains the postal code for the recipient's postal address.

PR_POSTAL_CODE_A Contains the postal code for the recipient's postal address.

PR_POSTAL_CODE_W Contains the postal code for the recipient's postal address.

PR_PREDECESSOR_CHANGE_LIST Contains a list of change keys,

including the current PR_CHANGE_KEY.

PR_PREFERRED_BY_NAME Contains the name that the recipient prefers to be called.

PR_PREFERRED_BY_NAME_A Contains the name that the recipient prefers to be called.

PR_PREFERRED_BY_NAME_W Contains the name that the recipient prefers to be called.

PR_PREPROCESS Contains true if the message requires preprocessing.

PR_PREVENT_MSG_CREATE 0x65F4000B

PR_PREVIEW 0x3FD9001E

PR_PREVIEW_A 0x3FD9001E

PR_PREVIEW_UNREAD 0x3FD8001E

PR_PREVIEW_UNREAD_A 0x3FD8001E

PR_PREVIEW_UNREAD_W 0x3FD8001F

PR_PREVIEW_W 0x3FD9001F

PR_PRIMARY_CAPABILITY Obsolete address book property.

PR_PRIMARY_FAX_NUMBER Contains the telephone number of the recipient's primary fax machine.

PR_PRIMARY_FAX_NUMBER_A Contains the telephone number of the recipient's primary fax machine.

PR_PRIMARY_FAX_NUMBER_W Contains the telephone number of the recipient's primary fax machine.

PR_PRIMARY_TELEPHONE_NUMBER Contains the recipient's primary telephone number.

PR_PRIMARY_TELEPHONE_NUMBER_A Contains the recipient's primary telephone number.

PR_PRIMARY_TELEPHONE_NUMBER_W Contains the recipient's primary telephone number.

PR_PRIORITY Contains the relative priority of a message.

PR_PRMD 0x670B001E

PR_PROCESS_MEETING_REQUESTS 0x686D000B

PR_PROCESSED 0x710A000B

PR_PROFESSION Contains the name of the recipient's line of business.

PR_PROFESSION_A Contains the name of the recipient's line of business.

PR_PROFESSION_W Contains the name of the recipient's line of business.

PR_PROFILE_AB_FILES_PATH Contains contains the offline address book path.

PR_PROFILE_ABP_ALLOW_RECONNECT 0x66390003
PR_PROFILE_ABP_MTHREAD_TIMEOUT_SECS 0x663A0003
PR_PROFILE_ADDR_INFO 0x66870102
PR_PROFILE_ADDR_TIMESTAMP 0x66860014
PR_PROFILE_ALLPUB_COMMENT 0x6617001E
PR_PROFILE_ALLPUB_DISPLAY_NAME 0x6616001E
PR_PROFILE_AUTH_PACKAGE 0x66190003
PR_PROFILE_BINDING_ORDER 0x6609001E
PR_PROFILE_CONFIG_FLAGS The property is used to configure a service of Microsoft Exchange Server.
PR_PROFILE_CONNECT_FLAGS The property specifies how to connect to a server.
PR_PROFILE_DISPLAYNAME_SET 0x66880003
PR_PROFILE_EXCHANGE_ACCOUNT_NAME 0x6620001F
PR_PROFILE_FAVFLD_COMMENT 0x6615001E
PR_PROFILE_FAVFLD_DISPLAY_NAME 0x660F001E
PR_PROFILE_HOME_SERVER Contains the name of a home server.
PR_PROFILE_HOME_SERVER_ADDRS 0x6613101E
PR_PROFILE_HOME_SERVER_DN Contains the distinguished name of a home server.
PR_PROFILE_MAILBOX Contains the e-mail address for a provider (transport or store).
PR_PROFILE_MAX_RESTRICT The property restricts the maximum number of names the address book will return.
PR_PROFILE_MOAB 0x667B001E
PR_PROFILE_MOAB_GUID 0x667C001E
PR_PROFILE_MOAB_SEQ 0x667D0003
PR_PROFILE_NAME Contains the name of the profile.
PR_PROFILE_NAME_A Contains the name of the profile.
PR_PROFILE_NAME_W Contains the name of the profile.
PR_PROFILE_OFFLINE_INFO Contains the path to an offline store.
PR_PROFILE_OFFLINE_STORE_PATH Contains the path to an offline store.
PR_PROFILE_OFFLINE_STORE_PATH_A 0x6610001E
PR_PROFILE_OFFLINE_STORE_PATH_W 0x6610001F
PR_PROFILE_OPEN_FLAGS Determines the flags used for a specific information store.

PR_PROFILE_OPTIONS_DATA 0x66890102
PR_PROFILE_RECONNECT_INTERVAL 0x661A0003
PR_PROFILE_SECURE_MAILBOX 0x67F00102
PR_PROFILE_SERVER Contains the name of the server where an information store is located.
PR_PROFILE_SERVER_DN Contains the distinguished name of the server where an information store is located.
PR_PROFILE_SERVER_VERSION 0x661B0003
PR_PROFILE_TRANSPORT_FLAGS Determines whether the Microsoft Exchange Server transport provider uploads or downloads messages.
PR_PROFILE_TYPE Describes the type of information store.
PR_PROFILE_UI_STATE The property is used to remember the last state of the user interface.
PR_PROFILE_UNRESOLVED_NAME Contains the unresolved name of a user.
PR_PROFILE_UNRESOLVED_SERVER Contains the unresolved name of a server.
PR_PROFILE_USER Contains the mailbox of a logged-on user.
PR_PROFILE_VERSION Contains the current version of a MAPI profile that contains the service of Microsoft Exchange Server.
PR_PROGRESS_OP_RATE 0x66BD0003
PR_PROHIBIT_RECEIVE_QUOTA 0x666A0003
PR_PROHIBIT_SEND_QUOTA 0x666E0003
PR_PROMOTE_PROP_ID_LIST 0x666B0102
PR_PROOF_OF_DELIVERY Contains an ASN.1 proof of delivery value.
PR_PROOF_OF_DELIVERY_REQUESTED Contains true if a message sender requests proof of delivery for a particular recipient.
PR_PROOF_OF_SUBMISSION Contains an ASN.1 proof of submission value.
PR_PROOF_OF_SUBMISSION_REQUESTED Contains true if a message sender requests proof that the message transfer system has submitted a message for delivery to the originally intended recipient.
PR_PROPORTIONAL_FONT 0x01C90003
PR_PROTOCOL_LOGLEV 0x01780003
PR_PROVIDER_DISPLAY Contains the vendor-defined display name for a service provider.
PR_PROVIDER_DISPLAY_A Contains the vendor-defined display name

for a service provider.

PR_PROVIDER_DISPLAY_W Contains the vendor-defined display name for a service provider.

PR_PROVIDER_DLL_NAME Contains the base filename of the MAPI service provider DLL.

PR_PROVIDER_DLL_NAME_A Contains the base filename of the MAPI service provider DLL.

PR_PROVIDER_DLL_NAME_W Contains the base filename of the MAPI service provider DLL.

PR_PROVIDER_ITEMID 0x0EA30102

PR_PROVIDER_ORDINAL Contains the zero-based index of a service provider's position in the provider table.

PR_PROVIDER_PARENT_ITEMID 0x0EA40102

PR_PROVIDER_SUBMIT_TIME Contains the date and time a transport provider passed a message to its underlying messaging system.

PR_PROVIDER_UID Contains a Guid structure of the service provider that is handling a message.

PR_PROXY_IN 0x0111101E

PR_PROXY_OUT 0x0136001E

PR_PS_ROUTING_XLATE 0x017D0003

PR_PST_ENCRYPTION Contains the encryption level at which to create a file in the personal folder store.

PR_PST_PATH Contains the location of the object in the personal folder store to create or configure.

PR_PST_PATH_W 0x6700001F

PR_PST_PW_SZ_NEW Contains the new password to use for future access to the personal folder store.

PR_PST_PW_SZ_OLD 0x6703001E

PR_PST_REMEMBER_PW 0x6701000B

PR_PUBLIC_FOLDER_ENTRYID 0x663C0102

PR_PUBLISH_IN_ADDRESS_BOOK Determines whether a folder's display name appears in the address book.

PR_PUID 0x300E001E

PR_PUID_A 0x300E001E

PR_PUID_W 0x300E001F

PR_PURPORTED_SENDER_DOMAIN 0x4083001E

PR_QUEUE_WAIT_TIMEOUT 0x01980003

PR_QUOTA_RECEIVE_THRESHOLD 0x67230003

PR_QUOTA_SEND_THRESHOLD 0x67220003

PR_QUOTA_WARNING_THRESHOLD 0x67210003

PR_RADIO_TELEPHONE_NUMBER Contains the recipient's radio telephone number.

PR_RADIO_TELEPHONE_NUMBER_A Contains the recipient's radio telephone number.

PR_RADIO_TELEPHONE_NUMBER_W Contains the recipient's radio telephone number.

PR_RANK 0x67120003

PR_RAS_DATA 0x01370102

PR_RCVD_BY_FLAGS 0x401B0003

PR_RCVD_REPRESENTING_ADDRTYPE Contains the address type for the messaging user represented by the user actually receiving the message.

PR_RCVD_REPRESENTING_ADDRTYPE_A Contains the address type for the messaging user represented by the user actually receiving the message.

PR_RCVD_REPRESENTING_ADDRTYPE_W Contains the address type for the messaging user represented by the user actually receiving the message.

PR_RCVD_REPRESENTING_EMAIL_ADDRESS Contains the e-mail address for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_EMAIL_ADDRESS_A Contains the e-mail address for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_EMAIL_ADDRESS_W Contains the e-mail address for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_ENTRYID Contains the entry identifier for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_FLAGS 0x401C0003

PR_RCVD_REPRESENTING_NAME Contains the display name for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_NAME_A Contains the display name for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_NAME_W Contains the display name for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_SEARCH_KEY Contains the search key for the messaging user represented by the receiving user.

PR_RCVD_REPRESENTING_SID 0x0E570102

PR_RCVD_REPRESENTING_SID_AS_XML 0x0E78001E

PR_READ 0x0E69000B

PR_READ_RECEIPT_ENTRYID Contains an entry identifier for the messaging user to which the messaging system should direct a read report for this message.

PR_READ_RECEIPT_FLAGS 0x40200003

PR_READ_RECEIPT_REQUESTED Contains true if a message sender wants the messaging system to generate a read report when the recipient has read a message.

PR_READ_RECEIPT_SEARCH_KEY Contains a search key for the messaging user to which the messaging system should direct a read report for a message.

PR_READ_RECEIPT_SID 0x0E510102

PR_READ_RECEIPT_SID_AS_XML 0x0E72001E

PR_RECEIPT_TIME Contains the date and time a delivery report is generated.

PR_RECEIVE_FOLDER_SETTINGS Contains a table of a message store's receive folder settings.

PR_RECEIVED_BY_ADDRTYPE Contains the e-mail address type, such as SMTP, for the messaging user that actually receives the message.

PR_RECEIVED_BY_ADDRTYPE_A Contains the e-mail address type, such as SMTP, for the messaging user that actually receives the message.

PR_RECEIVED_BY_ADDRTYPE_W Contains the e-mail address type, such as SMTP, for the messaging user that actually receives the message.

PR_RECEIVED_BY_EMAIL_ADDRESS Contains the e-mail address for the messaging user that actually receives the message.

PR_RECEIVED_BY_EMAIL_ADDRESS_A Contains the e-mail address for the messaging user that actually receives the message.

PR_RECEIVED_BY_EMAIL_ADDRESS_W Contains the e-mail address for the messaging user that actually receives the message.

PR_RECEIVED_BY_ENTRYID Contains the entry identifier of the messaging user that actually receives the message.

PR_RECEIVED_BY_NAME Contains the display name of the messaging user that actually receives the message.

PR_RECEIVED_BY_NAME_A Contains the display name of the messaging user that actually receives the message.

PR_RECEIVED_BY_NAME_W Contains the display name of the messaging user that actually receives the message.

PR_RECEIVED_BY_SEARCH_KEY Contains the search key of the messaging user that actually receives the message.

PR_RECEIVED_BY_SID 0x0E560102

PR_RECEIVED_BY_SID_AS_XML 0x0E77001E

PR_RECIPIENT_CERTIFICATE Contains a message recipient's ASN.1 certificate for use in a report.

PR_RECIPIENT_DATA_EXTERNAL 0x3FB00102

PR_RECIPIENT_FLAGS 0x5FFD0003

PR_RECIPIENT_KEY A unique (to this server) 4-byte value which identifies the recipient list.

PR_RECIPIENT_NUMBER Contains an index into a table of recipients.

PR_RECIPIENT_NUMBER_FOR_ADVICE Contains a message recipient's voice telephone number to call to advise of the physical delivery of a message.

PR_RECIPIENT_NUMBER_FOR_ADVICE_A Contains a message recipient's voice telephone number to call to advise of the physical delivery of a message.

PR_RECIPIENT_NUMBER_FOR_ADVICE_W Contains a message recipient's voice telephone number to call to advise of the physical delivery of a message.

PR_RECIPIENT_ON_ASSOC_MSG_COUNT Contains the total number of recipients on all associated messages.

PR_RECIPIENT_ON_NORMAL_MSG_COUNT Contains the total number of recipients on all normal messages.

PR_RECIPIENT_REASSIGNMENT_PROHIBITED Contains true if recipient reassignment is prohibited.

PR_RECIPIENT_STATUS Contains a value used by the MAPI spooler in assigning delivery responsibility among transport providers.

PR_RECIPIENT_TYPE Contains the recipient type for a message recipient.

PR_RECIPSTAT 0x65FF0003

PR_RECORD_KEY Contains a unique binary-comparable identifier for a specific object.

PR_REDIRECTION_HISTORY Contains information about the route covered by a delivered message.

PR_REferred_BY_NAME Contains the name that the recipient prefers to be called.

PR_REferred_BY_NAME_A Contains the name that the recipient prefers to be called.

PR_REferred_BY_NAME_W Contains the name that the recipient prefers to be called.

PR_REGISTERED_MAIL_TYPE Contains the type of registration used for physical delivery of a message.

PR_REGISTRY_ON 0x01A40003

PR_RElated_IPMS Contains a list of identifiers for messages to which a message is related.

PR_RELAY_ALLOW_LIST 0x0212101E

PR_RELAY_DENY_LIST 0x0211101E

PR_RELAY_FLAGS 0x02100003

PR_RELAY_LOCAL_IP_LIST 0x0213101E

PR_REM_OFFLINE_ENTRYID 0x36D60102

PR_REM_ONLINE_ENTRYID 0x36D50102

PR_REMINDERS_OFFLINE_ENTRYID 0x36D60102

PR_REMINDERS_ONLINE_ENTRYID 0x36D50102

PR_REMOTE_P_SELECTOR 0x3DD90102

PR_REMOTE_PROGRESS Contains a number indicating the status of a remote transfer.

PR_REMOTE_PROGRESS_TEXT Contains an ASCII string indicating the status of a remote transfer.

PR_REMOTE_PROGRESS_TEXT_A Contains an ASCII string indicating the status of a remote transfer.

PR_REMOTE_PROGRESS_TEXT_W Contains an ASCII string indicating the status of a remote transfer.

PR_REMOTE_S_SELECTOR 0x3DDA0102

PR_REMOTE_SERVER 0x3DE90102

PR_REMOTE_T_SELECTOR 0x3DDB0102

PR_REMOTE_VALIDATE_OK Contains true if the remote viewer is allowed to call the IMAPISStatus.ValidateState method.

PR_RENDERING_POSITION Contains an offset, in characters, to use in rendering an attachment within the main message text.

PR_REPL_CHANGES 0x3FD20102

PR_REPL_HEADER 0x3FD00102

PR_REPL_RGM 0x3FD30102

PR_REPL_STATUS 0x3FD10102

PR_REPLICA_COUNT Contains the total number of replicas for this folder.

PR_REPLICA_LIST Contains a list of the distinguished names of the servers that are replicating the contents of a public folder.

PR_REPLICA_SERVER Contains the server name from which a message is replicated.

PR_REPLICA_VERSION Contains the version number of the installation of Microsoft Exchange Server. The format for PR_REPLICA_VERSION is:

The HighPart member contains the Microsoft Exchange major version in the high order word and the Microsoft Exchange minor version in the low order word.

The LowPart member contains the Microsoft Exchange build number (integral part) in the high order word, and the build number (decimal part) in the low-order word.

PR_REPLICATION_ALWAYS_INTERVAL 0x66940003

PR_REPLICATION_MESSAGE_PRIORITY 0x66920003

PR_REPLICATION_MSG_SIZE 0x66950003

PR_REPLICATION_SCHEDULE 0x66910102

PR_REPLICATION_STATUS Contains the replication status.

PR_REPLICATION_STYLE 0x66900003

PR_REPLY_RECIPIENT_ENTRIES Contains a sized array of entry identifiers for recipients that are to get a reply.

PR_REPLY_RECIPIENT_NAMES Contains a list of display names for recipients that are to get a reply.

PR_REPLY_RECIPIENT_NAMES_A Contains a list of display names for recipients that are to get a reply.

PR_REPLY_RECIPIENT_NAMES_W Contains a list of display names for recipients that are to get a reply.

PR_REPLY_RECIPIENT_SMTP_PROXIES 0x3FFC001E

PR_REPLY_REQUESTED Contains true if a message sender requests a reply from a recipient.

PR_REPLY_TEMPLATE_ID 0x65C20102

PR_REPLY_TIME Contains the date and time by which a reply is expected

for a message.

PR_REPORT_DESTINATION_ENTRYID Contains the entry identifier of the immediate destination of a delivery or nondelivery report.

PR_REPORT_DESTINATION_FLAGS 0x405C0003

PR_REPORT_DESTINATION_NAME Contains the display name of the immediate destination of a report.

PR_REPORT_DESTINATION_SEARCH_KEY 0x40640102

PR_REPORT_DESTINATION_SID 0x0E540102

PR_REPORT_DESTINATION_SID_AS_XML 0x0E75001E

PR_REPORT_ENTRYID Contains the entry identifier for the recipient that should get reports for this message.

PR_REPORT_FLAGS 0x401F0003

PR_REPORT_NAME Contains the display name for the recipient that should get reports for this message.

PR_REPORT_NAME_A Contains the display name for the recipient that should get reports for this message.

PR_REPORT_NAME_W Contains the display name for the recipient that should get reports for this message.

PR_REPORT_SEARCH_KEY Contains the search key for the recipient that should get reports for this message.

PR_REPORT_SID 0x0E520102

PR_REPORT_SID_AS_XML 0x0E73001E

PR_REPORT_TAG Contains a binary tag value that the messaging system should copy to any report generated for the message.

PR_REPORT_TEXT Contains optional text for a report generated by the messaging system.

PR_REPORT_TEXT_A Contains optional text for a report generated by the messaging system.

PR_REPORT_TEXT_W Contains optional text for a report generated by the messaging system.

PR_REPORT_TIME Contains the date and time when the messaging system generated a report.

PR_REPORTING_DL_NAME Contains the display name of a distribution list for which the messaging system is delivering a report.

PR_REPORTING_MTA_CERTIFICATE Contains an identifier for the message transfer agent that generated a report.

PR_REQUESTED_DELIVERY_METHOD Contains a binary array of

delivery methods (service providers), in order of a message sender's preference.

PR_REROUTE_VIA_STORE 0x02050003

PR_REROUTING_TABLE 0x01D1101E

PR_RESENT_HDRS_HAVE_PREC 0x017F0003

PR_RESERVE_RANGE_OF_IDS 0x0E7B0102

PR_RESOLVE_METHOD Specifies the method used to resolve conflicts on messages in a public folder.

PR_RESOLVE_P2 0x01720003

PR_RESOURCE_FLAGS Contains a bitmask of flags for message services and providers.

PR_RESOURCE_METHODS Contains a bitmask of flags indicating the methods in the IMAPISStatus interface that are supported by the status object.

PR_RESOURCE_PATH Contains a path to the service provider's server.

PR_RESOURCE_PATH_A Contains a path to the service provider's server.

PR_RESOURCE_PATH_W Contains a path to the service provider's server.

PR_RESOURCE_TYPE Contains a value indicating the service provider type.

PR_RESPONSE_REQUESTED Contains true if the message sender wants a response to a meeting request.

PR_RESPONSIBILITY Contains true if some transport provider has already accepted responsibility for delivering the message to this recipient, and false if the MAPI spooler considers that this transport provider should accept responsibility.

PR_RESTRICTION_COUNT Contains the total number of restrictions on the folder.

PR_RETENTION_AGE_LIMIT 0x66C40003

PR_RETRY_EXPIRY 0x01380003

PR_RETRY_FALLOFF_CONST 0x013A0003

PR_RETRY_FALLOFF_MULT 0x013C0003

PR_RETRY_INTERVAL 0x0139001E

PR_RETURNED_IPM Contains true if the original message is being returned with a nonread report.

PR_RFC1006_PORTNO 0x3DDE0002

PR_RIGHTS Contains a user's effective rights on a folder.

PR_RMI 0x3FD40102

PR_RMQ_STATUS 0x66EE0102

PR_RMQ_TIMEOUT Contains the time when this message will be deleted if not handled.

PR_RMQ_TYPE Contains the type of the entry.

PR_RMQ_XMIT_TIME Contains the time message took in transit.

PR_ROH_FLAGS 0x66230003

PR_ROH_PROXY_AUTH_SCHEME 0x66270003

PR_ROH_PROXY_PRINCIPAL_NAME 0x6625001F

PR_ROH_PROXY_SERVER 0x6622001F

PR_ROOTDIR 0x013E001E

PR_ROUTE_DIAGNOSTICS 0x01C00003

PR_ROUTE_RECALC_INTERVAL 0x01C20003

PR_ROW_TYPE Contains a value that indicates the type of a row in a table.

PR_ROWID Contains a unique identifier for a recipient in a recipient table or status table.

PR_RTF_COMPRESSED Contains the Rich Text Format version of the message text, usually in compressed form.

PR_RTF_IN_SYNC Contains true if PR_RTF_COMPRESSED has the same text content as PR_BODY for this message.

PR_RTF_SYNC_BODY_COUNT Contains a count of the significant characters of the message text.

PR_RTF_SYNC_BODY_CRC Contains the cyclical redundancy check (CRC) computed for the message text.

PR_RTF_SYNC_BODY_TAG Contains significant characters that appear at the beginning of the message text.

PR_RTF_SYNC_BODY_TAG_A Contains significant characters that appear at the beginning of the message text.

PR_RTF_SYNC_BODY_TAG_W Contains significant characters that appear at the beginning of the message text.

PR_RTF_SYNC_PREFIX_COUNT Contains a count of the ignorable characters that appear before the significant characters of the message.

PR_RTF_SYNC_TRAILING_COUNT Contains a count of the ignorable characters that appear after the significant characters of the message.

PR_RULE_ACTION_NUMBER 0x66500003

PR_RULE_ACTION_TYPE 0x66490003

PR_RULE_ACTIONS 0x668000FE

PR_RULE_CONDITION 0x667900FD
PR_RULE_ERROR 0x66480003
PR_RULE_FOLDER_ENTRYID 0x66510102
PR_RULE_ID 0x66740014
PR_RULE_IDS 0x66750102
PR_RULE_LEVEL Contains the exit level of a rule.
PR_RULE_MSG_ACTIONS 0x65EF0102
PR_RULE_MSG_CONDITION 0x65F00102
PR_RULE_MSG_CONDITION_LCID 0x65F10003
PR_RULE_MSG_LEVEL 0x65ED0003
PR_RULE_MSG_NAME 0x65EC001F
PR_RULE_MSG_PROVIDER 0x65EB001F
PR_RULE_MSG_PROVIDER_DATA 0x65EE0102
PR_RULE_MSG_SEQUENCE 0x65F30003
PR_RULE_MSG_STATE 0x65E90003
PR_RULE_MSG_USER_FLAGS 0x65EA0003
PR_RULE_MSG_VERSION 0x65F20002
PR_RULE_NAME Contains a name string that is used for provider self-documentation only.
PR_RULE_PROVIDER Contains the name of the application that set a rule.
PR_RULE_PROVIDER_DATA 0x66840102
PR_RULE_SEQUENCE 0x66760003
PR_RULE_SERVER_RULE_ID 0x65A00014
PR_RULE_STATE 0x66770003
PR_RULE_TRIGGER_HISTORY 0x3FF20102
PR_RULE_USER_FLAGS 0x66780003
PR_RULE_VERSION 0x668D0002
PR_RULES_DATA Contains the PR_RULES_TABLE object.
PR_RULES_SIZE 0x3FFF0003
PR_RULES_TABLE Contains a table with all rules applied to a folder.
PR_SAVE_BEFORE_SUBMIT 0x019E0003
PR_SCHEDULE_FOLDER_ENTRYID Contains the folder entry identifier for a schedule folder.
PR_SCRIPT 0x7102001E
PR_SCRIPT_A 0x7102001E
PR_SCRIPT_LAST_MOD_BY 0x71090102

PR_SCRIPT_LAST_MOD_TIME 0x71080040
PR_SCRIPT_W 0x7102001F
PR_SEARCH Contains a container object that is used for advanced searches.
PR_SEARCH_FLAGS 0x67830003
PR_SEARCH_KEY Contains a binary-comparable key that identifies correlated objects for a search.
PR_SECURE_CONNECTION_ATTRIBUTES 0x01F5101E
PR_SECURE_CONNECTIONS 0x01710102
PR_SECURE_IN_SITE 0x669E000B
PR_SECURE_ORIGINATION Determines whether messages have been modified to look like forwarded messages when they are dragged into the folder.
PR_SECURITY Contains a flag that indicates the security level of a message.
PR_SELECTABLE Contains true if the entry in the one-off table can be selected.
PR_SEND_INTERNET_ENCODING Contains a bitmask of encoding preferences.
PR_SEND_NATIVE_BODY 0x6637000B
PR_SEND_RICH_INFO Contains true if the recipient can receive all message content, including Rich Text Format and OLE objects.
PR_SEND_RICH_INFO_ONLY 0x6609000B
PR_SENDER_ADDRTYPE Contains the message sender's e-mail address type.
PR_SENDER_ADDRTYPE_A Contains the message sender's e-mail address type.
PR_SENDER_ADDRTYPE_W Contains the message sender's e-mail address type.
PR_SENDER_EMAIL_ADDRESS Contains the message sender's e-mail address.
PR_SENDER_EMAIL_ADDRESS_A Contains the message sender's e-mail address.
PR_SENDER_EMAIL_ADDRESS_W Contains the message sender's e-mail address.
PR_SENDER_ENTRYID Contains the message sender's entry identifier.
PR_SENDER_FLAGS 0x40190003

PR_SENDER_ID_STATUS 0x40790003

PR_SENDER_NAME Contains the message sender's display name.

PR_SENDER_NAME_A Contains the message sender's display name.

PR_SENDER_NAME_W Contains the message sender's display name.

PR_SENDER_SEARCH_KEY Contains the message sender's search key.

PR_SENDER_SID 0x0E4D0102

PR_SENDER_SID_AS_XML 0x0E6E001E

PR_SENDER_SIMPLE_DISP_NAME 0x4030001F

PR_SENSITIVITY Contains a value indicating the message sender's opinion of the sensitivity of a message.

PR_SENT_REPRESENTING_ADDRTYPE Contains the address type for the messaging user represented by the sender.

PR_SENT_REPRESENTING_ADDRTYPE_A Contains the address type for the messaging user represented by the sender.

PR_SENT_REPRESENTING_ADDRTYPE_W Contains the address type for the messaging user represented by the sender.

PR_SENT_REPRESENTING_EMAIL_ADDRESS Contains the e-mail address for the messaging user represented by the sender.

PR_SENT_REPRESENTING_EMAIL_ADDRESS_A Contains the e-mail address for the messaging user represented by the sender.

PR_SENT_REPRESENTING_EMAIL_ADDRESS_W Contains the e-mail address for the messaging user represented by the sender.

PR_SENT_REPRESENTING_ENTRYID Contains the entry identifier for the messaging user represented by the sender.

PR_SENT_REPRESENTING_FLAGS 0x401A0003

PR_SENT_REPRESENTING_NAME Contains the display name for the messaging user represented by the sender.

PR_SENT_REPRESENTING_NAME_A Contains the display name for the messaging user represented by the sender.

PR_SENT_REPRESENTING_NAME_W Contains the display name for the messaging user represented by the sender.

PR_SENT_REPRESENTING_SEARCH_KEY Contains the search key for the messaging user represented by the sender.

PR_SENT_REPRESENTING_SID 0x0E4E0102

PR_SENT_REPRESENTING_SID_AS_XML 0x0E6F001E

PR_SENT_REPRESENTING_SIMPLE_DISP_NAME 0x4031001F

PR_SENTMAIL_ENTRYID Contains the entry identifier of the folder

where the message should be moved after submission.

PR_SEQID 0x3F810014

PR_SERVER_DN 0x66E0001E

PR_SERVER_DN_A 0x66E0001E

PR_SERVER_DN_W 0x66E0001F

PR_SERVER_VERSION Contains the version (build) number of server.

PR_SERVICE_DELETE_FILES Contains a list of filenames that are to be deleted when the message service is uninstalled.

PR_SERVICE_DELETE_FILES_A Contains a list of filenames that are to be deleted when the message service is uninstalled.

PR_SERVICE_DELETE_FILES_W Contains a list of filenames that are to be deleted when the message service is uninstalled.

PR_SERVICE_DLL_NAME Contains the filename of the DLL containing the message service provider entry point function to call for configuration.

PR_SERVICE_DLL_NAME_A Contains the filename of the DLL containing the message service provider entry point function to call for configuration.

PR_SERVICE_DLL_NAME_W Contains the filename of the DLL containing the message service provider entry point function to call for configuration.

PR_SERVICE_ENTRY_NAME Contains the name of the entry point function for configuration of a message service.

PR_SERVICE_EXTRA_UIDS Contains a list of Guid structures that identify additional profile sections for the message service.

PR_SERVICE_NAME Contains the name of a message service as set by the user in the MAPISVC.INF file.

PR_SERVICE_NAME_A Contains the name of a message service as set by the user in the MAPISVC.INF file.

PR_SERVICE_NAME_W Contains the name of a message service as set by the user in the MAPISVC.INF file.

PR_SERVICE_SUPPORT_FILES Contains a list of the files that belong to the message service.

PR_SERVICE_SUPPORT_FILES_A Contains a list of the files that belong to the message service.

PR_SERVICE_SUPPORT_FILES_W Contains a list of the files that belong to the message service.

PR_SERVICE_UID Contains the Guid structure for a message service.

PR_SERVICES Contains a list of identifiers of message services in the current profile.

PR_SHARED_THREADS 0x013F0003

PR_SHORT_BACKFILL_ID 0x66F70102

PR_SHORT_CN_MAX 0x66F60102

PR_SHORT_CN_MIN 0x66F50102

PR_SHORT_CNSET 0x66F20102

PR_SHORT_CNSET_FAI 0x66F30102

PR_SHORT_MIDSET_DELETED 0x66F90102

PR_SHOW_PROPERTIES 0x3DF0000B

PR_SHUTDOWN_DISABLE 0x01D60003

PR_SITE_DN 0x01F8001E

PR_SITE_DOMAIN 0x0179001E

PR_SMTP_ADDRESS 0x39FE001E

PR_SMTP_ADDRESS_A 0x39FE001E

PR_SMTP_ADDRESS_W 0x39FE001F

PR_SMTP_LISTENER_MODE 0x01560003

PR_SMTP_RECV_TIMEOUT 0x01400003

PR_SMTP_SENDER_MODE 0x01580003

PR_SMTP_TEMP_TBL_DATA 0x10C00102

PR_SMTP_TEMP_TBL_DATA_2 0x10C10003

PR_SMTP_TEMP_TBL_DATA_3 0x10C20102

PR_SMTP_WAITFOR_ACK 0x01480003

PR_SMTP_WAITFOR_AUTH 0x01FD0003

PR_SMTP_WAITFOR_BANNER 0x014A0003

PR_SMTP_WAITFOR_DATABLOCK 0x01520003

PR_SMTP_WAITFOR_DATAINIT 0x01500003

PR_SMTP_WAITFOR_DATATERM 0x01540003

PR_SMTP_WAITFOR_ETRN 0x01FF0003

PR_SMTP_WAITFOR_MAILFROM 0x014C0003

PR_SMTP_WAITFOR_RCPT 0x014E0003

PR_SMTP_WAITFOR_STARTTLS 0x01FE0003

PR_SMTP_WAITFOR_TURN 0x02010003

PR_SOFT_DELETES 0x4021000B

PR_SORT_LOCALE_ID 0x67050003

PR_SOURCE_FID 0x0E5F0014

PR_SOURCE_KEY Contains a binary number that uniquely identifies the

message or folder.

PR_SPLUS_FREE_BUSY_ENTRYID Contains the entry identifier of the Schedule+ free/busy subtree top-level folder.

PR_SPOOL_DIR_IN 0x015A001E

PR_SPOOL_DIR_LOG 0x015E001E

PR_SPOOL_DIR_OUT 0x015C001E

PR_SPOOLER_STATUS Contains the status of the message based on information available to the MAPI spooler.

PR_SPOUSE_NAME Contains the name of the recipient's spouse.

PR_SPOUSE_NAME_A Contains the name of the recipient's spouse.

PR_SPOUSE_NAME_W Contains the name of the recipient's spouse.

PR_SRC_URL_NAME 0x670F001E

PR_SRC_URL_NAME_A 0x670F001E

PR_SRC_URL_NAME_W 0x670F001F

PR_START_DATE Contains the starting date and time of an appointment as managed by a scheduling application.

PR_START_EMBED 0x40010003

PR_START_FAI_MSG 0x40100003

PR_START_MESSAGE 0x400C0003

PR_START_RECIP 0x40030003

PR_START_SUB_FLD 0x400A0003

PR_START_TOP_FLD 0x40090003

PR_STATE_OR_PROVINCE Contains the name of the recipient's state or province.

PR_STATE_OR_PROVINCE_A Contains the name of the recipient's state or province.

PR_STATE_OR_PROVINCE_W Contains the name of the recipient's state or province.

PR_STATUS Contains a 32-bit bitmask of flags defining folder status.

PR_STATUS_CODE Contains a bitmask of flags indicating the current status of a session resource. All service providers set status codes as does MAPI to report on the status of the subsystem, the MAPI spooler, and the integrated address book.

PR_STATUS_SEND_TIME Next time the server sent a status message.

PR_STATUS_STRING Contains an ASCII message indicating the current status of a session resource.

PR_STATUS_STRING_A Contains an ASCII message indicating the

current status of a session resource.

PR_STATUS_STRING_W Contains an ASCII message indicating the current status of a session resource.

PR_STORAGE_LIMIT_INFORMATION Contains information about whether a mailbox is currently within the storage limit set by the Administrator program.

PR_STORAGE_QUOTA_LIMIT Contains the size of the storage quota that was exceeded by the user.

PR_STORE_ENTRYID Contains the unique entry identifier of the message store in which an object resides.

PR_STORE_OFFLINE 0x6632000B

PR_STORE_PROVIDERS Contains a list of identifiers of message store providers in the current profile.

PR_STORE_RECORD_KEY Contains the unique binary-comparable identifier (record key) of the message store in which an object resides.

PR_STORE_SLOWLINK 0x7C0A000B

PR_STORE_STATE Contains a flag that describes the state of the message store.

PR_STORE_SUPPORT_MASK Contains a bitmask of flags that client applications should query to determine the characteristics of a message store.

PR_STREAM_OP_RATE 0x66BC0003

PR_STREET_ADDRESS Contains the recipient's street address.

PR_STREET_ADDRESS_A Contains the recipient's street address.

PR_STREET_ADDRESS_W Contains the recipient's street address.

PR_SUBFOLDER 0x6708000B

PR_SUBFOLDER_CT 0x0E630003

PR_SUBFOLDERS Contains true if a folder contains subfolders.

PR_SUBJECT Contains the full subject of a message.

PR_SUBJECT_A Contains the full subject of a message.

PR_SUBJECT_IPM Contains a binary value that is copied from the message for which a report is being generated.

PR_SUBJECT_PREFIX Contains a subject prefix that typically indicates some action on a message.

PR_SUBJECT_PREFIX_A Contains a subject prefix that typically indicates some action on a message.

PR_SUBJECT_PREFIX_W Contains a subject prefix that typically

indicates some action on a message.

PR_SUBJECT_TRACE_INFO Contains trace information on a delivery or nondelivery message report.

PR_SUBJECT_W Contains the full subject of a message.

PR_SUBMIT_FLAGS Contains a bitmask of flags indicating details about a message submission.

PR_SUPERSEDES 0x103A001E

PR_SUPERSEDES_A 0x103A001E

PR_SUPERSEDES_W 0x103A001F

PR_SUPPLEMENTARY_INFO Contains additional information for use in a report.

PR_SUPPLEMENTARY_INFO_A Contains additional information for use in a report.

PR_SUPPLEMENTARY_INFO_W Contains additional information for use in a report.

PR_SUPPRESS_RETURN_RECEIPT 0x01600003

PR_SUPPRESS_TRACEINFO 0x01EA0003

PR_SURNAME Contains the recipient's family name.

PR_SURNAME_A Contains the recipient's family name.

PR_SURNAME_W Contains the recipient's family name.

PR_SVR_GENERATING_QUOTA_MSG Contains the identity of the server that generates a message when a user exceeds the storage quota limit.

PR_SYNCEVENT_FIRED 0x664F000B

PR_SYNCEVENT_SUPPRESS_GUID 0x38800102

PR_SYNCHRONIZE_FLAGS 0x65E40003

PR_SYS_CONFIG_FOLDER_ENTRYID 0x66360102

PR_TABLE_OP_RATE 0x66BA0003

PR_TARGET_ENTRYID 0x30100102

PR_TCP_DIRECTORY_PORT 0x662E0002

PR_TCP_EXCHANGE_PORT 0x662C0002

PR_TCP_REFERRAL_PORT 0x66300002

PR_TELEX_NUMBER Contains the recipient's telex number.

PR_TELEX_NUMBER_A Contains the recipient's telex number.

PR_TELEX_NUMBER_W Contains the recipient's telex number.

PR_TEMP_SEND_RICH_INFO 0x6609000B

PR_TEMPLATEID Contains an entry identifier that can find the code associated with a service provider.

PR_TEST_LINE_SPEED 0x662B0102
PR_THREADS_PER_PROCESSOR 0x01620003
PR_TID 0x6719001E
PR_TITLE Contains the recipient's job title.
PR_TITLE_A Contains the recipient's job title.
PR_TITLE_W Contains the recipient's job title.
PR_TLS_PACKAGE 0x01F6001E
PR_TNEF_CORRELATION_KEY Contains a value used to correlate a Transport Neutral Encapsulation Format (TNEF) attachment with a message.
PR_TNEF_WORK_STREAM 0x7CD90102
PR_TOTAL_OP_RATE 0x66BF0003
PR_TRACE_INFO Contains trace information indicating how each messaging domain handled a particular message.
PR_TRANSFER_ENABLED Contains whether gateway outbound message processing is enabled.
PR_TRANSFER_OP_RATE 0x66BB0003
PR_TRANSMITABLE_DISPLAY_NAME Contains a recipient's display name in a form with enhanced security so that it cannot be changed.
PR_TRANSMITABLE_DISPLAY_NAME_A Contains a recipient's display name in a form with enhanced security so that it cannot be changed.
PR_TRANSMITABLE_DISPLAY_NAME_W Contains a recipient's display name in a form with enhanced security so that it cannot be changed.
PR_TRANSMITTABLE_DISPLAY_NAME Contains a recipient's display name in a form with enhanced security so that it cannot be changed.
PR_TRANSPORT_KEY Contains a value used by the MAPI spooler to track the progress of an outbound message through the outgoing transport providers.
PR_TRANSPORT_MESSAGE_HEADERS Contains transport-specific message envelope information.
PR_TRANSPORT_MESSAGE_HEADERS_A Contains transport-specific message envelope information.
PR_TRANSPORT_MESSAGE_HEADERS_W Contains transport-specific message envelope information.
PR_TRANSPORT_MMP_INFO 0x406E0102
PR_TRANSPORT_PROVIDERS Contains a list of identifiers of transport providers in the current profile.

PR_TRANSPORT_STATUS Obsolete MAPI spooler property.
PR_TRUST_SENDER 0x0E790003
PR_TRY_COUNT Contains the number of tries of submission.
PR_TTY 0x6718001E
PR_TTYTDD_PHONE_NUMBER Contains the recipient's
Telecommunications Device For The Deaf (TTYTDD) telephone number.
PR_TTYTDD_PHONE_NUMBER_A Contains the recipient's
Telecommunications Device For The Deaf (TTYTDD) telephone number.
PR_TTYTDD_PHONE_NUMBER_W Contains the recipient's
Telecommunications Device For The Deaf (TTYTDD) telephone number.
PR_TURF_DIR 0x01F2001E
PR_TURF_TABLE 0x01F1101E
PR_TYPE_OF_MTS_USER Contains the type of a message recipient, for
use in a report.
PR_URGENT_MESSAGE_FREQ 0x01640003
PR_URGENT_MESSAGE_TIMEOUT 0x01660003
PR_URL_COMP_NAME 0x10F3001E
PR_URL_COMP_NAME_A 0x10F3001E
PR_URL_COMP_NAME_HASH 0x67100003
PR_URL_COMP_NAME_POSTFIX 0x0E610003
PR_URL_COMP_NAME_SET 0x0E62000B
PR_URL_COMP_NAME_W 0x10F3001F
PR_URL_DATA 0x66350102
PR_URL_DATA_EA 0x66350104
PR_URL_DATA_HANDLE 0x66350103
PR_URL_MIME 0x66340102
PR_URL_MIME_BODY 0x66330102
PR_URL_MIME_BODY_EA 0x66330104
PR_URL_MIME_BODY_HANDLE 0x66330103
PR_URL_MIME_EA 0x66340104
PR_URL_MIME_HANDLE 0x66340103
PR_URL_MIME_HEADER 0x66320102
PR_URL_MIME_HEADER_EA 0x66320104
PR_URL_MIME_HEADER_HANDLE 0x66320103
PR_URL_NAME 0x6707001E
PR_URL_NAME_A 0x6707001E
PR_URL_NAME_W 0x6707001F

PR_URL_VIEW 0x66360102
PR_URL_VIEW_EA 0x66360104
PR_URL_VIEW_HANDLE 0x66360103
PR_USE_CONN_MGR_API 0x01F90003
PR_USE_EXTENSION_DLL 0x01D20003
PR_USE_MFI_FOR_SMTP 0x3DF5000B
PR_USE_RTF_TEXT 0x01670003
PR_USE_TNS_RESOLVER 0x01C40003
PR_USENET_SITE_NAME 0x6802001F
PR_USER_CERTIFICATE Contains an ASN.1 authentication certificate for a messaging user.
PR_USER_DISPLAY_NAME Contains the display name of the logged on user.
PR_USER_DISPLAY_NAME_A Contains the display name of the logged on user.
PR_USER_DISPLAY_NAME_W Contains the display name of the logged on user.
PR_USER_DN Contains the DN of the logged on user.
PR_USER_DN_A Contains the DN of the logged on user.
PR_USER_DN_W Contains the DN of the logged on user.
PR_USER_ENTRYID Contains the entry identifier of a user.
PR_USER_GUID 0x67070102
PR_USER_NAME Contains the name of a user of a message store.
PR_USER_NOTIFICATION 0x01680003
PR_USER_SID 0x67830102
PR_USER_X509_CERTIFICATE Contains X.509 version 3 security certificates for a messaging user.
PR_VALID_FOLDER_MASK Contains a bitmask of flags that indicate the validity of the entry identifiers of the folders in a message store.
PR_VD_BINARY 0x70010102
PR_VD_FLAGS 0x70030003
PR_VD_LINK_TO 0x70040102
PR_VD_NAME 0x7006001E
PR_VD_STRINGS 0x7002001E
PR_VD_VERSION 0x70070003
PR_VD_VIEW_FOLDER 0x70050102
PR_VERSION_OP_CODE 0x3F850003

PR_VERSION_OP_DATA 0x3F860102
PR_VERSION_SEQUENCE_NUMBER 0x3F870003
PR_VERSIONING_FLAGS 0x3F900002
PR_VIEWS_ENTRYID Contains the entry identifier of the user-defined Views folder.
PR_WAIT_FOR_ETRN 0x02000003
PR_WARNED_ABOUT_TCPIP_CONFIG 0x01B10003
PR_WEDDING_ANNIVERSARY Contains the date of the recipient's wedding anniversary.
PR_WIN32_SECURITY_DESCRIPTOR 0x3D220102
PR_WIZARD_NO_PAB_PAGE Contains true if the Profile Wizard is to suppress the PAB page.
PR_WIZARD_NO_PST_PAGE Contains true if the Profile Wizard is to suppress the PST page.
PR_X121 0x6717001E
PR_X400_CONTENT_TYPE Contains the content type for a submitted message.
PR_X400_DEFERRED_DELIVERY_CANCEL Was originally meant to contain true if the message transfer system (MTS) allows X.400 deferred delivery cancellation.
PR_X400_ENVELOPE_TYPE 0x66530003
PR_X500_DN 0x802D001E
PR_XMT_SECURITY_ROLE_1 0x3D250102
PR_XMT_SECURITY_ROLE_1_AS_XML 0x3D25001E
PR_XMT_SECURITY_ROLE_2 0x3D260102
PR_XMT_SECURITY_ROLE_2_AS_XML 0x3D26001E
PR_XMT_SECURITY_ROLE_3 0x3D270102
PR_XMT_SECURITY_ROLE_3_AS_XML 0x3D27001E
PR_XMT_SECURITY_ROLE_4 0x3D280102
PR_XMT_SECURITY_ROLE_4_AS_XML 0x3D28001E
PR_XMT_SECURITY_ROLE_5 0x3D290102
PR_XMT_SECURITY_ROLE_5_AS_XML 0x3D29001E
PR_XMT_SECURITY_ROLE_6 0x3D2A0102
PR_XMT_SECURITY_ROLE_6_AS_XML 0x3D2A001E
PR_XMT_SECURITY_ROLE_7 0x3D2B0102
PR_XMT_SECURITY_ROLE_7_AS_XML 0x3D2B001E
PR_XMT_SECURITY_ROLE_8 0x3D2C0102

PR_XMT_SECURITY_ROLE_8_AS_XML 0x3D2C001E
PR_XORG_TRANSPORT_MMP_INFO 0x40780102
PR_XPOS Contains the x coordinate of the starting position (the upper-left corner) of a dialog box control, in standard Windows dialog units.
PR_YPOS Contains the y coordinate of the starting position (the upper-left corner) of a dialog box control, in standard Windows dialog units.
ptagAbstract 0x3FDA001E
ptagAccess Contains a bitmask of flags indicating the operations a client application can perform on the open object.
ptagAccessLevel Contains a bitmask of flags indicating the level at which a client application can access the open object.
ptagACLData Contains the binary form of the PR_ACL_TABLE object, which is the access control list (ACL) table for a folder.
ptagACLDataChecksum 0x3FD70003
ptagACLID 0x677D0102
ptagACLListData 0x67CA0102
ptagACLListRefCt 0x67C90003
ptagACLMemberCreate 0x67F00102
ptagACLMemberData 0x67CD0102
ptagACLMemberMentioned 0x67F10102
ptagACLMemberRefCt 0x67CB0003
ptagACLMemberVisible 0x67EE0102
ptagACLTable Contains a table consisting of all the access control lists (ACLs) applied to a folder.
ptagActiveSearchCount 0x67770003
ptagActiveUserEntryId 0x66520102
ptagAddrbookMID 0x674F0014
ptagAddrCc 0x0E98001E
ptagAddressBookDisplayName 0x3FE8001E
ptagAddressBookEntryId Contains of the name-service entry identifier of a directory object referring to a public folder.
ptagAddrTo 0x0E97001E
ptagAddrType Contains the messaging user's e-mail address type, such as Simple Mail Transfer Protocol (SMTP).
ptagAdminDescription 0x671C001E
ptagAdminDescriptionA 0x671C001E
ptagAdminDescriptionW 0x671C001F

ptagAdminFolderFlags 0x672D0003
ptagAdminGivenName 0x6776001E
ptagAdminNickName 0x6778001E
ptagAdminNickNameA 0x6778001E
ptagAdminNickNameW 0x6778001F
ptagAdminNTSD Contains the Administrator permissions on a folder. By default, they are not set on individual folders, but are inherited from the root folder. However, if you set specific Administrator permissions on a folder, this property is added and replicated with that folder.
ptagAdminNTSDAsXML 0x0E6B001E
ptagAdminSurName 0x6775001E
ptagAgeLimit 0x0E670003
ptagAlternateRecipientAllowed Contains true if the sender permits autoforwarding of this message.
ptagAltRecipientDN 0x676F001E
ptagAMID 0x67CC0102
ptagAnonymousRights 0x67C40002
ptagAntiVirusScanInfo 0x0E88001E
ptagAntiVirusScanStatus 0x0E870003
ptagAntiVirusVendor 0x0E85001E
ptagAntiVirusVersion 0x0E860003
ptagAQContext 0x680A0102
ptagAQEntryNum 0x68080003
ptagAQSubsId 0x68070002
ptagAQURLName 0x6809001F
ptagArrivalTime Contains the date and time a specific message arrived at a gateway.
ptagArticleIndexFolder 0x668A0102
ptagArticleNumMic 0x675D0003
ptagArticleNumMost 0x675E0003
ptagArticleNumNext 0x67510003
ptagAssociated 0x67AA000B
ptagAssociatedCount Contains the count of items in the associated contents table of the folder.
ptagAssocMsgSize 0x66B40003
ptagAssocMsgSizeExtended 0x66B40014
ptagAssocMsgWithAttachCt 0x66AE0003

ptagAttachCreationTime 0x67C10040

ptagAttachDataBin Contains binary attachment data typically accessed through the COM IStream interface.

ptagAttachDataObj Contains an attachment object typically accessed through the OLE IStorage interface.

ptagAttachFilename Contains an attachment's base filename and extension, excluding path.

ptagAttachID 0x3F880014

ptagAttachLastModificationTime 0x67C20040

ptagAttachLongPathname Contains an attachment's fully qualified long path and filename.

ptagAttachMethod Contains a MAPI-defined constant representing the way the contents of an attachment can be accessed.

ptagAttachNum Contains a number that uniquely identifies the attachment within its parent message.

ptagAttachOnAssocMsgCt Contains the total count of attachments on all associated messages in a folder.

ptagAttachOnNormalMsgCt Contains the total count of attachments on all normal messages in a folder.

ptagAttachPathname Contains an attachment's fully qualified path and filename.

ptagAttachProptagArray 0x67C00102

ptagAttachRefCt 0x67BF0003

ptagAttachRendering Contains a Microsoft Windows metafile with rendering information for an attachment.

ptagAttachSize Contains the sum, in bytes, of the sizes of all properties on an attachment.

ptagAttachVirusScanInfo 0x0E960102

ptagAttrHidden 0x10F4000B

ptagAttrReadOnly 0x10F6000B

ptagAttrSystem 0x10F5000B

ptagAutoForwarded Contains true if an automatic agent has forwarded a message.

ptagAutoReply 0x6772000B

ptagAutoReset 0x670C1048

ptagAutoResponseSuppress 0x3FDF0003

ptagBackfill 0x67D80102

ptagBackfillRanking 0x66E10003
ptagBatchId 0x68180003
ptagBID 0x38000014
ptagBilateralInfo 0x3FDC0102
ptagBody Contains the message text.
ptagBodyHtml Contains the Hypertext Markup Language (HTML) version
of the message text.
ptagBranchConfigID 0x3F8B0014
ptagCALDue 0x10C90040
ptagCALEndTime 0x10C40040
ptagCALRecurringId 0x10C50040
ptagCALReminderNextTime 0x10CA0040
ptagCALStartTime 0x10C30040
ptagCatalog 0x0E5B0102
ptagCategColumns 0x678B0102
ptagCategFIDs 0x678A0102
ptagCategID 0x674B0014
ptagCategVisibleIDs 0x678C0102
ptagCDODeferredDelete 0x36240102
ptagCDODeferredModify 0x36250102
ptagCDODisableExpansion 0x361E0003
ptagCDOExpansionData 0x3D2D0003
ptagCDOExpansionIndex 0x10C70003
ptagCDOExpansionMID 0x0EFE0014
ptagCDOExpansionStatus 0x36200102
ptagCDOExpansionVersion 0x36410003
ptagCDOExpTable 0x36220102
ptagCDOFBCMonth1 0x36280102
ptagCDOFBCMonth10 0x36310102
ptagCDOFBCMonth11 0x36320102
ptagCDOFBCMonth12 0x36330102
ptagCDOFBCMonth13 0x36340102
ptagCDOFBCMonth14 0x36350102
ptagCDOFBCMonth15 0x36360102
ptagCDOFBCMonth16 0x36370102
ptagCDOFBCMonth17 0x36380102
ptagCDOFBCMonth18 0x36390102

ptagCDOFBCMonth19 0x363A0102
ptagCDOFBCMonth2 0x36290102
ptagCDOFBCMonth20 0x363B0102
ptagCDOFBCMonth21 0x363C0102
ptagCDOFBCMonth22 0x363D0102
ptagCDOFBCMonth23 0x363E0102
ptagCDOFBCMonth24 0x363F0102
ptagCDOFBCMonth3 0x362A0102
ptagCDOFBCMonth4 0x362B0102
ptagCDOFBCMonth5 0x362C0102
ptagCDOFBCMonth6 0x362D0102
ptagCDOFBCMonth7 0x362E0102
ptagCDOFBCMonth8 0x362F0102
ptagCDOFBCMonth9 0x36300102
ptagCDOFBCMonthes 0x36260102
ptagCDOFBCReserved 0x36270102
ptagCDOJasperResource 0x361D0003
ptagCDOOORTable 0x36230102
ptagCDORrecurMasterID 0x0EFF0003
ptagCDORMTable 0x36210102
ptagChangeAdvisor 0x6634000D
ptagCheckInComment 0x3F84001E
ptagCheckInComment_A 0x3F84001E
ptagCheckInComment_W 0x3F84001F
ptagCheckInTime 0x3F830040
ptagCiNotificationEnabled 0x0E5D000B
ptagCiSearchEnabled 0x0E5C000B
ptagClearReceipts 0x67AC0002
ptagClientActions Contains the rule actions.
ptagClientIsOwner 0x65B3000B
ptagCn 0x67A40014
ptagCnExport 0x67590102
ptagCnLastSent 0x67D90102
ptagCnLMaxExpired 0x67970102
ptagCnMax 0x67E90014
ptagCnMin 0x67E80014
ptagCnMv 0x67A61014

ptagCnMvExport 0x675B0102
ptagCnSegmentIndex 0x67A20002
ptagCnSegmentSize 0x67A30002
ptagCnSegmentStart 0x67A10014
ptagCnsetBackfill 0x67960102
ptagCnsetBackfillFAI 0x67DA0102
ptagCnsetIn 0x67940102
ptagCnsetRead 0x67D20102
ptagCnsetSeen 0x67960102
ptagCnsetSeenFAI 0x67DA0102
ptagCodePageId 0x66C30003
ptagCollector The property is used with the MAPI OpenProperty function to retrieve either the IExchangeImportHierarchyChanges interface or the IExchangeImportContentsChanges interface.
ptagComment Contains a comment about the purpose or content of an object.
ptagConflictEntryId Contains the entry identifier of an original conflict message that contains conflicting versions of the message as attachments.
ptagConflictMsgKey 0x3FCA0102
ptagConnectionModulus 0x67430003
ptagContactCount Contains the number of contacts in a public folder.
ptagContainerContents Contains an embedded contents table object that provides information about a container.
ptagContainerHierarchy Contains an embedded hierarchy table object that provides information about the child containers.
ptagContentCorrelator Contains a value the message sender can use to match a report with the original message.
ptagContentCount Contains the number of messages in a folder, as computed by the message store.
ptagContentIdentifier Contains a key value that enables the message recipient to identify its content.
ptagContentReturnRequested Contains true if a message should be returned with a nondelivery report.
ptagContentSearchKey Contains the entry identifier of the message inside the message transfer envelope (MTE).
ptagContentUnread Contains the number of unread messages in a folder, as computed by the message store.

ptagConversationIndex Contains a binary value that indicates the relative position of this message within a conversation thread.

ptagConversationKey The obsolete precursor of the PR_CONVERSATION_INDEX and PR_CONVERSATION_TOPIC properties.

ptagConversationTopic Contains the topic of the first message in a conversation thread.

ptagConversionWithLossProhibited Contains true if a message transfer agent (MTA) is prohibited from making message text conversions that lose information.

ptagConvState 0x67780003

ptagConvTopicOffSync 0x6772000B

ptagCopyRefCt 0x67F50003

ptagCreationTime Contains the creation date and time for a message.

ptagCreatorAddrType 0x402284E4

ptagCreatorCAI 0x67BD0102

ptagCreatorEmailAddr 0x402384E4

ptagCreatorEntryId Contains the address book entry identifier of the user who created the message.

ptagCreatorFlags 0x40590003

ptagCreatorGuid 0x0E4B0102

ptagCreatorName Contains the display name of the user who created the message.

ptagCreatorOrgAddrType 0x404F84E4

ptagCreatorOrgEmailAddr 0x405084E4

ptagCreatorSid 0x0E580102

ptagCreatorSidAsXML 0x0E6C001E

ptagCreatorSimpleDispName 0x403884E4

ptagCreatorSMTPAddress 0x0E94001E

ptagCreatorToken 0x67830102

ptagDamBackPatched 0x6647000B

ptagDamOrgMsgEntryId 0x66460102

ptagDamOrgMsgGidSvrEID 0x36420102

ptagDamOrgMsgSvrEID 0x674100FB

ptagDamOrigMsgSvrEID 0x65C10102

ptagDamStoreEntryId 0x65C00102

ptagDateDiscoveredAbsentInDS 0x680C0040

ptagDavNTSD 0x0E840102

ptagDAVSubmitData 0x10C6001E

ptagDefaultViewEntryId Contains the entry identifier of a folder's default view.

ptagDeferredDeliveryTime Contains the date and time at which a message sender wants a message delivered.

ptagDeferredSendTime Contains a future time at which a message is to be sent.

ptagDeleteAfterSubmit Contains true if a client application wants MAPI to delete the associated message after submission.

ptagDeletedAssocMessageSizeExtended 0x669D0014

ptagDeletedAssocMsgCt 0x66430003

ptagDeletedCountTotal 0x670B0003

ptagDeletedFolderCt 0x66410003

ptagDeletedMessageSizeExtended 0x669B0014

ptagDeletedMsgCt 0x66400003

ptagDeletedNormalMessageSizeExtended 0x669C0014

ptagDeletedOn 0x668F0040

ptagDeletedSubfolderCt 0x0E640003

ptagDeleteState 0x67F70003

ptagDeleteTime 0x0E660040

ptagDelivContLength 0x67710003

ptagDeliverTime Contains the date and time at which the original message was delivered.

ptagDeliverToDN 0x6744001E

ptagDeliveryReportRequested Contains true if a message sender requests a delivery report for a particular recipient from the messaging system before the message is placed in the message store.

ptagDepth Represents the relative level of indentation, or depth, of an object in a hierarchy table.

ptagDesignInProgress Contains a flag that indicates a folder is being modified and can only be accessed by the owner.

ptagDID 0x3F800014

ptagDisableFullFidelity 0x10F2000B

ptagDisableNTAcls 0x67730003

ptagDisablePerUserRead 0x66C5000B

ptagDisableWinsock 0x66180003

ptagDiscardReason Contains a reason why a message transfer agent (MTA) has discarded a message.

ptagDisclosureOfRecipients Contains true if disclosure of recipients is allowed.

ptagDiscreteValues Contains true if a nondelivery report applies only to discrete members of a distribution list rather than the entire list.

ptagDisplayBcc Contains an ASCII list of the display names of any blind carbon copy (BCC) message recipients, separated by semicolons (;).

ptagDisplayCc Contains an ASCII list of the display names of any carbon copy (CC) message recipients, separated by semicolons (;).

ptagDisplayName Contains the display name of the message store.

ptagDisplayNameW Contains the display name of the message store.

ptagDisplayTo Contains an ASCII list of the display names of the primary (To) message recipients, separated by semicolons (;).

ptagDisplayType Contains a value used to associate an icon with a particular row of a table.

ptagDLExpansionProhibited Contains true if a message transfer agent (MTA) is prohibited from expanding distribution lists.

ptagDLReportFlags 0x3FDB0003

ptagDN 0x67CF001E

ptagDNmdb 0x67E00102

ptagDNmdbTrans Contains a subject prefix that typically indicates some action on a message.

ptagDNPrefix 0x400884E4

ptagDNPrefixList 0x67C7101E

ptagDNPrefixVersion 0x67C80003

ptagDocumentId 0x68150003

ptagDocumentState 0x68170002

ptagDomain 0x67680102

ptagDRAFTID 0x3F820014

ptagEcWarning 0x400F0003

ptagEformsRegistryFolder Contains the entry identifier of the forms library folder under the non-IPM subtree.

ptagELCPolicyComment 0x6733001F

ptagELCPolicyIds 0x6732001E

ptagEmailAddr Contains the messaging user's e-mail address.

ptagEndAttach 0x400E0003

ptagEndBccRecip 0x40060003
ptagEndCcRecip 0x40050003
ptagEndEmbed 0x40020003
ptagEndFolder 0x400B0003
ptagEndMessage 0x400D0003
ptagEndP1Recip 0x40070003
ptagEndRecip 0x40040003
ptagEndToRecip 0x40040003
ptagEntryId Contains a MAPI entry identifier used to open and edit properties of a particular MAPI object.
ptagERFlag 0x40650003
ptagEventCounter 0x68070102
ptagEventCreatedTime 0x680F0040
ptagEventData 0x67C80102
ptagEventFid 0x68090014
ptagEventFidOld 0x680C0014
ptagEventFidOldParent 0x680E0014
ptagEventFidParent 0x680B0014
ptagEventFidRoot 0x68120102
ptagEventFlags 0x68150003
ptagEventItemCount 0x68110003
ptagEventMailboxGuid 0x676A0102
ptagEventMask 0x68080003
ptagEventMid 0x680A0014
ptagEventMidOld 0x680D0014
ptagEventMsgClass 0x6810001E
ptagEventsRootFolder 0x667A0102
ptagEventTime 0x67C70040
ptagEventTransacId 0x68140003
ptagEventUnreadCount 0x68130003
ptagEventWMConsumerGuid 0x68160102
ptagEventWMCreatedTime 0x68170040
ptagEventWMEventCounter 0x68070102
ptagEventWMMailboxDSGuid 0x676A0102
ptagExcessStorageUsed 0x3FF60003
ptagExpiryTime Contains the date and time at which the messaging system can invalidate the content of a message.

ptagExplicitConversion Contains a value that indicates that a message sender has requested a message content conversion for a particular recipient.

ptagExtendedACLData 0x3FFE0102

ptagFAIContentCount Contains the count of items in the associated contents table of the folder.

ptagFAIMsgFolderPropTagArray 0x67FF0102

ptagFastTransfer 0x662F000D

ptagFavoritesDefaultName 0x6635001E

ptagFID 0x67480014

ptagFIDC 0x67660102

ptagFIDMIDBlob 0x67850102

ptagFidVidGlobal 0x664C0102

ptagFileSize 0x67470003

ptagFlatURLName 0x670E001F

ptagFolderAssocContents Contains an embedded contents table object that provides information about the associated contents table.

ptagFolderCDN 0x678D0102

ptagFolderChildCt 0x66380003

ptagFolderDN 0x678D001E

ptagFolderInternetId 0x0E230003

ptagFolderMessages 0x67E60102

ptagFolderPathname 0x66B5001E

ptagFolderPathnameA 0x66B5001E

ptagFolderPathnameW 0x66B5001F

ptagFolderProps 0x67E40102

ptagFolderPropTagArray 0x677E0102

ptagFolderQuota 0x67310003

ptagFolderSize 0x67300014

ptagFolderTreeRootFID 0x67A70014

ptagFolderType Contains a constant that indicates the folder type.

ptagForceClientRefresh 0x65A1000B

ptagFreeBusyNTSD 0x0F000102

ptagFromIHave 0x3FFF000B

ptagFtBackfillExpiry 0x67D60040

ptagFtCn Contains the date and time the object or subobject was last modified.

ptagFtExpiry 0x67D60040
ptagFtFolderWideExpiry 0x67D70040
ptagFtLastBackfill 0x67E10040
ptagFtLastLogoffTime 0x66A30040
ptagFtLastLogonTime 0x66A20040
ptagFtLastUsed 0x67890040
ptagFtSend 0x67D50040
ptagFtSendStatus 0x67D30040
ptagFtSyncDs 0x679E0040
ptagFtTimeout 0x67D40040
ptagFtUnused 0x67E10040
ptagFXDelProp 0x40160003
ptagFXErrorInfo 0x40180003
ptagGBID 0x3F8C0102
ptagGDefVID 0x3F960102
ptagGDID 0x3F8A0102
ptagGetPropsExcludePropIdList 0x667E0102
ptagGLID 0x380B0102
ptagGlobalCounter 0x67610102
ptagGlobalFlags 0x67670003
ptagGlobalGUID 0x67620102

ptagGlobalPerUserGUID 0x67630102
ptagGlobalVersion 0x67600003
ptagGUID 0x676A0102
ptagGUIDmdb 0x67E00102
ptagGVID 0x3F890102
ptagGWFolder 0x679A000B
ptagHasAttach Contains at least one attachment.
ptagHasAttachFromImail 0x665A000B
ptagHasDAMs 0x3FEA000B
ptagHasModeratorRules 0x663F000B
ptagHasNamedProperties 0x664A000B
ptagHasRules 0x663A000B
ptagHierarchyServer 0x6633001E
ptagHierChangeNum 0x663E0003
ptagHierRev 0x40820040

ptagHierSynchronizer 0x662C000D
ptagHighestFolderInternetId 0x0E230003
ptagHtml Contains the Hypertext Markup Language (HTML) version of the message text.
ptagIcon Contains a bitmap of a full size icon for a form.
ptagIconIndex 0x10800003
ptagICSChangeKey 0x66550102
ptagICSGid 0x3D2E0102
ptagICSNotif 0x67500003
ptagICSNotifGUID 0x66370048
ptagICSType 0x68070003
ptagIdBackfill 0x67A40014
ptagIdentityDisplay Contains the display name for a service provider's identity as defined within a messaging system.
ptagIdentityEntryId Contains the entry identifier for a service provider's identity as defined within a messaging system.
ptagIdentitySearchKey Contains the search key for a service provider's identity as defined within a messaging system.
ptagIdsetDeleted 0x67E50102
ptagIdsetGiven 0x40170003
ptagIdsetRead 0x402D0102
ptagIdsetUnread 0x402E0102
ptagIFSInternalData 0x10C80102
ptagImapCachedBodystructure 0x676D0102
ptagImapCachedEnvelope 0x676C0102
ptagImapCachedMsgsize 0x10F00102
ptagImapInternalDate 0x65F50040
ptagImapLastArticleId 0x67520003
ptagImapSubscribeList 0x65F6101F
ptagImapUID 0x0E230003
ptagImplicitConversionProhibited Contains true if a message transfer agent (MTA) is prohibited from making implicit message text conversions.
ptagImpliedRestrictions 0x667F1102
ptagImportance Contains a value indicating the message sender's opinion of the importance of a message.
ptagInboundNewsfeedDn 0x668D001E
ptagInConflict 0x666C000B

ptagIncrSyncChg 0x40120003
ptagIncrSyncChgPartial 0x407D0003
ptagIncrSyncDel 0x40130003
ptagIncrSyncEnd 0x40140003
ptagIncrSyncGroupId 0x407C0003
ptagIncrSyncGroupInfo 0x407B0102
ptagIncrSyncImailStream 0x403C0003
ptagIncrSyncImailStream2Continue 0x40710003
ptagIncrSyncImailStreamCancel 0x40670003
ptagIncrSyncImailStreamContinue 0x40660003
ptagIncrSyncMsg 0x40150003
ptagIncrSyncMsgPartial 0x407A0003
ptagIncrSyncProgressMode 0x4074000B
ptagIncrSyncProgressPerMsg 0x4075000B
ptagIncrSyncRead 0x402F0003
ptagIncrSyncStateBegin 0x403A0003
ptagIncrSyncStateEnd 0x403B0003
ptagIndexAge 0x67ED0014
ptagIndexDeleteTime 0x0E660040
ptagIndexName 0x67EC001E
ptagInetArticleNum 0x0E230003
ptagInetControl 0x1031001E
ptagInetDistribution 0x1032001E
ptagInetMailOverrideFormat 0x59020003
ptagInetMessageID 0x1035001E
ptagInetNewsgroupName 0x66A7001E
ptagInetNewsgroups 0x1036001E
ptagInetNewsgroupsBinary 0x10360102
ptagInetNewsPath 0x1038001E
ptagInetReferences 0x1039001E
ptagInidNew 0x68000014
ptagInstanceGuid 0x681D0048
ptagInstanceID 0x67B00102
ptagInstanceKey Contains a value that uniquely identifies a row in a table.
ptagInstanceNum 0x674E0003
ptagInstID 0x674D0014
ptagInternalFID 0x67650014

ptagInternalPostReply 0x3FD50102
ptagInternetApproved 0x1030001E
ptagInternetContent 0x66590102
ptagInternetContentEA 0x66590104
ptagInternetContentHandle 0x66590103
ptagInternetCpid 0x3FDE0003
ptagInternetFollowupTo 0x1033001E
ptagInternetFreeDocInfo 0x67200102
ptagInternetMdns 0x66A5000B
ptagInternetMessageInfo 0x66C70102
ptagInternetNoSender 0x4070000B
ptagInternetParseState 0x66C60102
ptagInternetSentRepresentingName 0x40690102
ptagInternetSubject 0x40680102
ptagInTransitState 0x6618000B
ptagInTransitStatus 0x66180003
ptagIntTraceInfo 0x666A0102
ptagIPMCommonViewsFolder Contains the entry identifier of the predefined common view folder.
ptagIPMDafFolder 0x661F0102
ptagIPMFinderFolder Contains the entry identifier for the folder in which search results are typically created.
ptagIPMFolder 0x679B000B
ptagIPMOutboxFolder Contains the entry identifier of the standard interpersonal message (IPM) Outbox folder.
ptagIPMSentmailFolder Contains the entry identifier of the standard IPM Sent Items folder.
ptagIPMShortcutsFolder 0x66300102
ptagIPMSubtreeFolder Contains the entry identifier of the root of the IPM folder subtree in the message store's folder tree.
ptagIPMViewsFolder Contains the entry identifier of the user-defined Views folder.
ptagIPMWastebasketFolder Contains the entry identifier of the standard IPM Deleted Items folder.
ptagIsDeleted 0x6819000B
ptagIsExtendedRule 0x679A000B
ptagIsNewsgroup 0x6697000B

ptagIsNewsgroupAnchor 0x6696000B
ptagItemLevelACL 0x3D24000B
ptagLastAccessTime 0x66A90040
ptagLastConflict 0x3FC90102
ptagLastFullBackup 0x66850040
ptagLastMaintenanceWork 0x676B0003
ptagLastModificationTime Contains the date and time the object or subobject was last modified.
ptagLastModifierAddrType 0x402484E4
ptagLastModifierCAI 0x67BE0102
ptagLastModifierEmailAddr 0x402584E4
ptagLastModifierEntryId 0x3FFB0102
ptagLastModifierFlags 0x405A0003
ptagLastModifierGuid 0x0E4C0102
ptagLastModifierName 0x3FFA001E
ptagLastModifierOrgAddrType 0x405184E4
ptagLastModifierOrgEmailAddr 0x405284E4
ptagLastModifierSid 0x0E590102
ptagLastModifierSidAsXML 0x0E6D001E
ptagLastModifierSimpleDispName 0x403984E4
ptagLastModifierSMTPAddress 0x0E95001E
ptagLastTransmissionTime 0x66E20003
ptagLastVerbExecuted 0x10810003
ptagLastVerbExecutionTime 0x10820040
ptagLatestDeliveryTime Contains the latest date and time when a message transfer agent (MTA) should deliver a message.
ptagLCID 0x676E0003
ptagLCIDRestriction 0x67880003
ptagLID 0x3F880014
ptagLISErrorCode 0x65AA0003
ptagLISErrorItemType 0x65AB0003
ptagLISErrorItemUrl 0x65AD001F
ptagLISErrorLogUrl 0x6570001F
ptagLISErrorOperation 0x65AC0003
ptagLISErrorSourceUrl 0x65AE001F
ptagLISExtendedErrorinfo 0x65B00003
ptagLISModifiedPropertyList 0x65AF001F

ptagLISNewMail 0x65C5000B
ptagLISRulesData 0x36400102
ptagLISSD 0x65F90102
ptagLISSubfolders 0x6500000B
ptagLISUnreadCount 0x65010003
ptagLocalCommitTime 0x67090040
ptagLocalCommitTimeMax 0x670A0040
ptagLocalDeliveryDone 0x6772000B
ptagLocaleEformsRegistryFolder 0x66240102
ptagLocaleId Contains the locale identifier of a logged-on mailbox user.
ptagLocalized 0x676D000B
ptagLocallyDelivered 0x67450102
ptagLocalRepCounter 0x67FC0102
ptagLocalRepGUID 0x67FB0003
ptagLocalSiteAddrBookFolder 0x66260102
ptagLocalSiteFreeBusyFolder 0x66250102
ptagLocalXPostList 0x65FE0102
ptagLocalXPostListURL 0x65FE101F
ptagLocalXref 0x67860102
ptagLockComment Contains a comment about the purpose or content of an object.
ptagLockDaclId 0x66000003
ptagLockDepth 0x38080003
ptagLockEnlistmentContext 0x38040102
ptagLockExpiryTime 0x380A0040
ptagLockGroupId 0x66030003
ptagLockInfoStruct 0x380B0003
ptagLockNullResourceURL 0x380C001F
ptagLockOwnerId 0x66020003
ptagLockResourceDID 0x38020014
ptagLockResourceFID 0x38010014
ptagLockResourceVID 0x38030014
ptagLockSaclId 0x66010003
ptagLockScope 0x38060002
ptagLockTime Contains the creation date and time for a message.
ptagLockTimeout 0x38090003
ptagLockTransientID 0x38070102

ptagLockType 0x38050002
ptagLongtermEntryId 0x66700102
ptagLtid 0x67580102
ptagMailboxDSGuid 0x67070102
ptagMailboxId 0x68160048
ptagMailboxInCreation 0x680B000B
ptagMailboxLastUpdated 0x67740014
ptagMailboxMiscFlags 0x68060003
ptagMailboxOwnerDisplayName 0x6773001F
ptagMailboxOwnerDN 0x676B001E
ptagMailboxOwnerEntryId 0x661B0102
ptagMailboxOwnerName 0x661C001E
ptagMailboxState 0x681A0003
ptagMailFlags 0x67A90002
ptagMapiEntryIdGUID 0x676C0102
ptagMappingSignature Contains the mapping signature for named properties of a particular MAPI object.
ptagMasterInid 0x67760102
ptagMaxCachedViews 0x0E680003
ptagMaxIndices 0x0E5E0003
ptagMaxSubmitMsgSize 0x666D0003
ptagMdbDsGuid 0x676A0102
ptagMdbDsGuidHistroyList 0x67750102
ptagMdbProvider Contains a provider-defined Guid structure that indicates the type of the message store.
ptagMemberEntryId Contains a MAPI entry identifier used to open and edit properties of a particular MAPI object.
ptagMemberId 0x66710014
ptagMemberName 0x6672001E
ptagMemberRights 0x66730003
ptagMergeMidsetDeleted 0x0E7A0102
ptagMessageAttachments Contains a table of restrictions that can be applied to a contents table to find all messages that contain attachment subobjects meeting the restrictions.
ptagMessageCcMe Contains true if this messaging user is specifically named as a carbon copy (CC) recipient of this message and is not part of a distribution list.

ptagMessageClass Contains a text string that identifies the sender-defined message class, such as IPM.Note.

ptagMessageFlags Contains a bitmask of flags indicating the origin and current state of a message.

ptagMessageProcessed 0x65E8000B

ptagMessageRecipients Contains a table of restrictions that can be applied to a contents table to find all messages that contain recipient subobjects meeting the restrictions.

ptagMessageRecipMe Contains true if this messaging user is specifically named as a primary (To), carbon copy (CC), or blind carbon copy (BCC) recipient of this message and is not part of a distribution list.

ptagMessageSiteName 0x65E7001E

ptagMessageSize Contains the sum, in bytes, of the sizes of all properties on a message object.

ptagMessageSizeExtended Contains the sum (in bytes) of the sizes of all properties on a message object.

ptagMessageSubmissionId Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

ptagMessageSubmissionIdFromClient Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

ptagMessageToMe Contains true if this messaging user is specifically named as a primary (To) recipient of this message and is not part of a distribution list.

ptagMID 0x674A0014

ptagMidMic 0x67F30014

ptagMidMost 0x67F40014

ptagMidSegmentIndex 0x679F0002

ptagMidSegmentSize 0x67A00002

ptagMidSegmentStart 0x67910014

ptagMidsetDeleted 0x67920102

ptagMidsetDeletedExport 0x675C0102

ptagMidsetDeletedRules 0x67680102

ptagMidsetExpired 0x67930102

ptagMidsetExpiredExtended 0x68040102

ptagMidsetTombstones 0x67980102

ptagMimeHandlerClassId 0x0E5E1048

ptagMimeHandlerGuids 0x0E5E1048

ptagMimeSize 0x67460003
ptagMiniIcon Contains a bitmap of a half-size icon for a form.
ptagModeratorRuleCount 0x663F0003
ptagModifiedCount 0x67F60003
ptagMoveToFolderEid 0x3FF40102
ptagMoveToStoreEid 0x3FF30102
ptagMsgAttachlist 0x67B30102
ptagMsgBodyId 0x3FDD0003
ptagMsgDaclId 0x66000003
ptagMsgDeliveryTime Contains the date and time a message was delivered.
ptagMsgEditorFormat 0x59090003
ptagMsgFolderDummy 0x670C000B
ptagMsgFolderPropTagArray 0x677F0102
ptagMsgFolderTemplateRes10 0x6719001E
ptagMsgFolderTemplateRes11 0x671A001E
ptagMsgFolderTemplateRes12 0x671B001E
ptagMsgFolderTemplateRes13 0x6770000B
ptagMsgFolderTemplateRes2 0x67110003
ptagMsgFolderTemplateRes4 0x6713000B
ptagMsgFolderTemplateRes5 0x6714000B
ptagMsgFolderTemplateRes6 0x6715000B
ptagMsgFolderTemplateRes7 0x67160102
ptagMsgFolderTemplateRes8 0x67170102
ptagMsgFolderTemplateRes9 0x67180102
ptagMsgFoldTime 0x66540040
ptagMsgGroupId 0x66030003
ptagMsgIDHash 0x676E0003
ptagMsgLCID 0x3FF10003
ptagMsgOwnerId 0x66020003
ptagMsgPropList 0x678F0102
ptagMsgPropListFAI 0x67900102
ptagMsgPropTagArray 0x67B20102
ptagMsgRecipientData 0x67B40102
ptagMsgRefCt 0x67B10003
ptagMsgSaclId 0x66010003
ptagMsgSDControl 0x66040003
ptagMsgStatus Contains a bitmask of property tags that define the status of

a message.

ptagMsgSynchronizer The property is used with the MAPI OpenProperty function to retrieve the IExchangeExportChanges interface. This interface is for exporting only a folder's contents changes, not its hierarchy changes.

ptagMTSID Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

ptagMTSInFolder 0x66280102

ptagMTSOutFolder 0x66290102

ptagMTSReportId Contains a message transfer system (MTS) identifier for the message transfer agent (MTA).

ptagMTSSubjectId 0x66630102

ptagMvncsetInConflict 0x67950102

ptagMVIProperty 0x67990003

ptagMVLong 0x700E1003

ptagMvPKMOperationReq 0x3F8E101E

ptagMvPKMOperationReq_A 0x3F8E101E

ptagMvPKMOperationReq_W 0x3F8E101F

ptagMvPKMVersionLabels 0x3F92101E

ptagMvPKMVersionLabels_A 0x3F92101E

ptagMvPKMVersionLabels_W 0x3F92101F

ptagMvPKMVersionStatus 0x3F93101E

ptagMvPKMVersionStatus_A 0x3F93101E

ptagMvPKMVersionStatus_W 0x3F93101F

ptagMVString8 0x7016101E

ptagNamedPropExpSrc 0x67F30102

ptagNamedPropIdFree 0x67F2000B

ptagNativeCpid 0x3FFD0003

ptagNDRReasonCode Contains an encoded reason for nondelivery that forms part of a nondelivery report.

ptagNDRStatusCode 0x0C200003

ptagNewAttach 0x40000003

ptagNewFXFolder 0x40110102

ptagNewsfeedAcl 0x66A60102

ptagNewsfeedDN 0x6803001E

ptagNewsfeedID 0x68010003

ptagNewsfeedsSeen 0x677D0102

ptagNewsgroupComp 0x66A5001E

ptagNewsgroupRootFolder 0x668C0102
ptagNntpArticleNum 0x67110003
ptagNntpControlFolder 0x668B0102
ptagNNTPFlags 0x40730003
ptagNNTPPostingHostName 0x4072001E
ptagNNTPXref 0x1040001E
ptagNoLocalDelivery 0x6770000B
ptagNonDeliveryDiagCode Contains a diagnostic code that forms part of a nondelivery report.
ptagNonDeliveryReportRequested Contains true if a message sender requests a nondelivery report for a particular recipient.
ptagNonIPMSubtreeFolder 0x66200102
ptagNonReceiptNotificationReq Contains true if a message sender wants notification of non-receipt for a specified recipient.
ptagNonReceiptNotificationRequested Contains true if a message sender wants notification of non-receipt for a specified recipient.
ptagNonReceiptReason Contains reasons why a message was not received that forms part of a nondelivery report.
ptagNonWin32ACL 0x3D23000B
ptagNonXmtSecurityRole1 0x0E7C0102
ptagNonXmtSecurityRole1AsXML 0x0E7C001E
ptagNonXmtSecurityRole2 0x0E7D0102
ptagNonXmtSecurityRole2AsXML 0x0E7D001E
ptagNonXmtSecurityRole3 0x0E7E0102
ptagNonXmtSecurityRole3AsXML 0x0E7E001E
ptagNonXmtSecurityRole4 0x0E7F0102
ptagNonXmtSecurityRole4AsXML 0x0E7F001E
ptagNonXmtSecurityRole5 0x0E800102
ptagNonXmtSecurityRole5AsXML 0x0E80001E
ptagNonXmtSecurityRole6 0x0E810102
ptagNonXmtSecurityRole6AsXML 0x0E81001E
ptagNonXmtSecurityRole7 0x0E820102
ptagNonXmtSecurityRole7AsXML 0x0E82001E
ptagNonXmtSecurityRole8 0x0E830102
ptagNonXmtSecurityRole8AsXML 0x0E83001E
ptagNormalizedSubject Contains the message subject with any prefix removed.

ptagNormalMsgSize 0x66B30003
ptagNormalMsgSizeExtended 0x66B30014
ptagNormalMsgWithAttachCt 0x66AD0003
ptagNot822Renderable 0x6753000B
ptagNTSD Contains the NT Security Descriptors of the users or groups that can access the folder.
ptagNTSDAsXML 0x0E6A001E
ptagNTSDModificationTime 0x3FD60040
ptagNTUsername 0x66A0001E
ptagNTUserSid 0x66A00102
ptagNull Represents a null value or setting of a property or reserves array space.
ptagObjectType Provides file type information for a non-Windows attachment.
ptagOfflineAddrBookFolder 0x66230102
ptagOfflineFlags Contains the folder availability flag.
ptagOFLData 0x680D0102
ptagOFLHdrDiscACL 0x67F10003
ptagOFLHdrGroup 0x67EF0003
ptagOFLHdrOwner 0x67ED0003
ptagOFLHdrSysACL 0x67F30003
ptagOFLID 0x680A0003
ptagOFLIndex 0x680C0102
ptagOFLListDiscACL 0x67F00102
ptagOFLListGroup 0x67EE0102
ptagOFLListOwner 0x67EC0102
ptagOFLListSysACL 0x67F20102
ptagOFLMasterID 0x68090102
ptagOFLMasterTbt 0x68070003
ptagOFLPtag 0x68080003
ptagOFLRefCt 0x680B0003
ptagOkToDelete 0x676D000B
ptagOldestDeletedOn 0x66420040
ptagOOFState 0x661D000B
ptagOOFStateEx 0x68100003
ptagOrgAddrType 0x403D84E4
ptagOrgEmailAddr 0x403E84E4

ptagOrgName 0x67F90102

ptagOriginalAuthorAddrType Contains the address type of the author of the first version of a message. That is ? the message before being forwarded or replied to.

ptagOriginalAuthorCAI 0x67FA0102

ptagOriginalAuthorEmailAddr Contains the e-mail address of the author of the first version of a message. That is ? the message before being forwarded or replied to.

ptagOriginalAuthorEntryId Contains the entry identifier of the author of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalAuthorFlags 0x405D0003

ptagOriginalAuthorGuid 0x0E480102

ptagOriginalAuthorName Contains the display name of the author of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalAuthorOrgAddrType 0x405784E4

ptagOriginalAuthorOrgEmailAddr 0x405884E4

ptagOriginalAuthorSearchKey Contains the search key of the author of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalAuthorSid 0x0E550102

ptagOriginalAuthorSidAsXML 0x0E76001E

ptagOriginalAuthorSimpleDispName 0x406084E4

ptagOriginalAuthorSMTPAddress 0x0E91001E

ptagOriginalDeliveryTime Contains a copy of the original message's delivery date and time in a thread.

ptagOriginalDisplayBcc Contains the display names of any blind carbon copy (BCC) recipients of the original message.

ptagOriginalDisplayCc Contains the display names of any carbon copy (CC) recipients of the original message.

ptagOriginalDisplayName Contains the original display name for an entry copied from an address book to a personal address book or other writable address book.

ptagOriginalDisplayTo Contains the display names of the primary (To) recipients of the original message.

ptagOriginalEntryId Contains the original entry identifier for an entry

copied from an address book to a personal address book or other writeable address book.

ptagOriginalInetMessageID 0x1046001E

ptagOriginallyIntendedRecip Contains the entry identifier of the originally intended recipient of an autoforwarded message.

ptagOriginallyIntendedRecipName Contains the encoded name of the originally intended recipient of an autoforwarded message.

ptagOriginalSearchKey Contains the original search key for an entry copied from an address book to a personal address book or other writeable address book.

ptagOriginalSenderAddrType Contains the address type of the sender of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalSenderCAI 0x67B70102

ptagOriginalSenderEmailAddr Contains the e-mail address of the sender of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalSenderEntryId Contains the entry identifier of the sender of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalSenderFlags 0x401D0003

ptagOriginalSenderGuid 0x0E420102

ptagOriginalSenderName Contains the display name of the sender of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalSenderOrgAddrType 0x404384E4

ptagOriginalSenderOrgEmailAddr 0x404484E4

ptagOriginalSenderSearchKey Contains the search key for the sender of the first version of a message, that is, the message before being forwarded or replied to.

ptagOriginalSenderSid 0x0E4F0102

ptagOriginalSenderSidAsXML 0x0E70001E

ptagOriginalSenderSimpleDispName 0x403284E4

ptagOriginalSenderSMTPAddress 0x0E8B001E

ptagOriginalSensitivity Contains the sensitivity value assigned by the sender of the first version of a message ? that is, the message before being forwarded or replied to.

ptagOriginalSentRepresentingAddrType Contains the address type of the messaging user on whose behalf the original message was sent.
ptagOriginalSentRepresentingCAI 0x67B80102
ptagOriginalSentRepresentingEmailAddr Contains the e-mail address of the messaging user on whose behalf the original message was sent.
ptagOriginalSentRepresentingEntryId Contains the entry identifier of the messaging user on whose behalf the original message was sent.
ptagOriginalSentRepresentingFlags 0x401E0003
ptagOriginalSentRepresentingGuid 0x0E430102
ptagOriginalSentRepresentingName Contains the display name of the messaging user on whose behalf the original message was sent.
ptagOriginalSentRepresentingOrgAddrType 0x404584E4
ptagOriginalSentRepresentingOrgEmailAddr 0x404684E4
ptagOriginalSentRepresentingSearchKey Contains the search key of the messaging user on whose behalf the original message was sent.
ptagOriginalSentRepresentingSid 0x0E500102
ptagOriginalSentRepresentingSidAsXML 0x0E71001E
ptagOriginalSentRepresentingSimpleDispName 0x403384E4
ptagOriginalSentRepresentingSMTPAddress 0x0E8C001E
ptagOriginalSubject Contains the subject of an original message for use in a report about the message.
ptagOriginalSubmitTime Contains the original submission date and time of the message in the report.
ptagOriginatorAddr 0x665C001E
ptagOriginatorAddrType 0x665D001E
ptagOriginatorCAI 0x67F80102
ptagOriginatorEmailAddr 0x665C001E
ptagOriginatorEntryId 0x665E0102
ptagOriginatorFlags 0x405B0003
ptagOriginatorGuid 0x0E460102
ptagOriginatorName 0x665B001E
ptagOriginatorOrgAddrType 0x405384E4
ptagOriginatorOrgEmailAddr 0x405484E4
ptagOriginatorRequestedAlternateRecipient Contains an entry identifier for an alternate recipient designated by the sender.
ptagOriginatorSearchKey 0x40610102
ptagOriginatorSid 0x0E530102

ptagOriginatorSidAsXML 0x0E74001E
ptagOriginatorSimpleDispName 0x405E84E4
ptagOriginatorSMTPAddress 0x0E8F001E
ptagOriginId 0x664D0102
ptagOrigMsgClass Contains the class of the original message for use in a report.
ptagOutboundNewsfeedDn 0x668E001E
ptagOverallAgeLimit 0x66990003
ptagOverallMsgAgeLimit 0x66930003
ptagOverQuotaLimit 0x677A0003
ptagOWAUrl 0x10F1001E
ptagOwnerCount Contains the number of owners of a public folder.
ptagOwnStoreEntryId Contains the entry identifier of a transport's tightly coupled message store.
ptagP1Content 0x11000102
ptagP1ContentType 0x11010102
ptagPackedNamedProps 0x361C0102
ptagParentCategID 0x674C0014
ptagParentEntryId Contains the entry identifier of the folder containing a folder or message.
ptagParentFID 0x67490014
ptagParentKey Was originally meant to contain a value used in correlating conversation threads.
ptagParentURLName 0x670D001F
ptagParentXfid Contains the ptagXfid property of the parent folder of a folder.
ptagPcl 0x67A50102
ptagPclExport 0x675A0102
ptagPerInstanceExpiryInfo 0x678D0102
ptagPerUserLastMod 0x67D10040
ptagPFContactsGuid 0x0E600102
ptagPFContactsNtdn 0x0E60101E
ptagPFDisallowMdbWideExpiry 0x6723000B
ptagPFMsgAgeLimit 0x67010003
ptagPFMsgSizeLimit 0x67220003
ptagPFOverHardQuotaLimit 0x67210003
ptagPFPlatinumHomeMdb 0x671E000B

ptagPFProxy 0x671D0102
ptagPFProxyRequired 0x671F000B
ptagPhysicalDeliveryBureauFaxDelivery Contains true if the messaging system should use a fax bureau for physical delivery of this message.
ptagPhysicalDeliveryMode Contains a bitmask of flags defining the physical delivery mode (for example, special delivery) for a message designated for a specific recipient.
ptagPhysicalDeliveryReportRequest Contains the mode of a report to be delivered to a particular message recipient upon completion of physical message delivery or delivery by the message handling system.
ptagPhysicalForwardingAddressRequested Contains true if a message sender requests the message transfer agent to attach a physical forwarding address for a message recipient.
ptagPhysicalForwardingProhibited Contains true if a message sender prohibits physical message forwarding for a specific recipient.
ptagPKMDocInternalState 0x3F8F001E
ptagPKMDocInternalState_A 0x3F8F001E
ptagPKMDocInternalState_W 0x3F8F001F
ptagPKMDocStatus 0x3F8D001E
ptagPKMDocStatus_A 0x3F8D001E
ptagPKMDocStatus_W 0x3F8D001F
ptagPKMInternalData 0x3F940102
ptagPKMLastUnapprovedVID 0x3F910102
ptagPop3Last 0x67540102
ptagPostReplyFolderEntries 0x103D0102
ptagPostReplyFolderNames 0x103E001E
ptagPreventMsgCreate 0x65F4000B
ptagPreview 0x3FD9001E
ptagPreviewUnread 0x3FD8001E
ptagPrimarySMTPAddress 0x39FE001E
ptagPriority Contains the relative priority of a message.
ptagProfileAddrInfo 0x66870102
ptagProfileAddrTimestamp 0x66860014
ptagProfileBindingOrder 0x6609001E
ptagProfileConfigFlags 0x66010003
ptagProfileConnectFlags 0x66040003
ptagProfileDisplayNameSet 0x66880003

ptagProfileHomeServer 0x6602001E
ptagProfileHomeServerAddrs 0x6613101E
ptagProfileHomeServerDN 0x6612001E
ptagProfileMailbox 0x660B001E
ptagProfileOpenFlags 0x66090003
ptagProfileOptionsData 0x66890102
ptagProfileReconnectInterval 0x661A0003
ptagProfileServer 0x660C001E
ptagProfileServerDN 0x6614001E
ptagProfileTransportFlags 0x66050003
ptagProfileType 0x660A0003
ptagProfileUser 0x6603001E
ptagProhibitReceiveQuota 0x666A0003
ptagProhibitSendQuota 0x666E0003
ptagPromotePropIdList 0x666B0102
ptagProofOfDeliveryRequested Contains true if a message sender requests proof of delivery for a particular recipient.
ptagProofOfSubmissionRequested Contains true if a message sender requests proof that the message transfer system has submitted a message for delivery to the originally intended recipient.
ptagPropGroupCn0 0x67360014
ptagPropGroupCn1 0x67370014
ptagPropGroupCn2 0x67380014
ptagPropGroupCn3 0x67390014
ptagPropGroupCn4 0x673A0014
ptagPropGroupCn5 0x673B0014
ptagPropGroupCn6 0x673C0014
ptagPropGroupCn7 0x673D0014
ptagPropGroupCnOther 0x67350014
ptagPropGroupMapId 0x67340014
ptagPropGroupMappings 0x67340102
ptagPropID 0x67F10002
ptagPropName 0x67F4001F
ptagPropNameGuid 0x67F00102
ptagPropNameHash 0x67F50003
ptagPropNameId 0x67EF0003
ptagPropNameSz 0x67EE001F

ptagProviderDisplay Contains the vendor-defined display name for a service provider.

ptagProviderSubmitTime Contains the date and time a transport provider passed a message to its underlying messaging system.

ptagProvisionedFid 0x672F0014

ptagProvisionedFolderGuid 0x672E0102

ptagPseudo220 0x67670003

ptagPseudo224 0x67670003

ptagPublicFolderPath 0x679C001E

ptagPublishInAddressBook 0x3FE6000B

ptagQuotaStyle 0x67790003

ptagRank 0x67120003

ptagRcvdByCAI 0x67B90102

ptagRcvdByEntryId Contains the entry identifier of the messaging user that actually receives the message.

ptagRcvdByFlags 0x401B0003

ptagRcvdByGuid 0x0E490102

ptagRcvdByName Contains the display name of the messaging user that actually receives the message.

ptagRcvdByOrgAddrType 0x404784E4

ptagRcvdByOrgEmailAddr 0x404884E4

ptagRcvdBySearchKey Contains the search key of the messaging user that actually receives the message.

ptagRcvdBySet 0x67AE000B

ptagRcvdBySid 0x0E560102

ptagRcvdBySidAsXML 0x0E77001E

ptagRcvdBySimpleDispName 0x403484E4

ptagRcvdBySMTPAddress 0x0E92001E

ptagRcvdRepresentingAddrType Contains the address type for the messaging user represented by the user actually receiving the message.

ptagRcvdRepresentingCAI 0x67BA0102

ptagRcvdRepresentingEmailAddr Contains the e-mail address for the messaging user represented by the receiving user.

ptagRcvdRepresentingEntryId Contains the entry identifier for the messaging user represented by the receiving user.

ptagRcvdRepresentingFlags 0x401C0003

ptagRcvdRepresentingGuid 0x0E4A0102

ptagRcvdRepresentingName Contains the display name for the messaging user represented by the receiving user.

ptagRcvdRepresentingOrgAddrType 0x404984E4

ptagRcvdRepresentingOrgEmailAddr 0x404A84E4

ptagRcvdRepresentingSearchKey Contains the search key for the messaging user represented by the receiving user.

ptagRcvdRepresentingSet 0x67AF000B

ptagRcvdRepresentingSid 0x0E570102

ptagRcvdRepresentingSidAsXML 0x0E78001E

ptagRcvdRepresentingSimpleDispName 0x403584E4

ptagRcvdRepresentingSMTPAddress 0x0E93001E

ptagRead 0x0E69000B

ptagReadCnNew 0x67FE0102

ptagReadReceiptAddrType 0x402984E4

ptagReadReceiptCAI 0x67BB0102

ptagReadReceiptDisplayName 0x402B84E4

ptagReadReceiptEmailAddr 0x402A84E4

ptagReadReceiptEntryId Contains an entry identifier for the messaging user to which the messaging system should direct a read report for this message.

ptagReadReceiptFlags 0x40200003

ptagReadReceiptGuid 0x0E440102

ptagReadReceiptOrgAddrType 0x404B84E4

ptagReadReceiptOrgEmailAddr 0x404C84E4

ptagReadReceiptRequested Contains true if a message sender wants the messaging system to generate a read report when the recipient has read a message.

ptagReadReceiptSearchKey Contains a search key for the messaging user to which the messaging system should direct a read report for a message.

ptagReadReceiptSid 0x0E510102

ptagReadReceiptSidAsXML 0x0E72001E

ptagReadReceiptSimpleDispName 0x403684E4

ptagReadReceiptSMTPAddress 0x0E8D001E

ptagReceiptTime Contains the date and time a delivery report is generated.

ptagReceivedByAddrType Contains the e-mail address type, such as SMTP, for the messaging user that actually receives the message.

ptagReceivedByEmailAddr Contains the e-mail address for the messaging user that actually receives the message.

ptagRecipientCAI 0x0E5A0102
ptagRecipientDataExternal 0x3FB00102
ptagRecipientKey 0x67E30040
ptagRecipientNumber 0x66620003
ptagRecipientReassignmentProhibited Contains true if recipient reassignment is prohibited.
ptagRecipientType Contains the recipient type for a message recipient.
ptagRecipOnAssocMsgCt 0x66B00003
ptagRecipOnNormalMsgCt 0x66AF0003
ptagRecordKey Contains a unique binary-comparable identifier for a specific object.
ptagRecursiveSearchFIDs 0x67860102
ptagRefCnt 0x676E0003
ptagRegisteredMailType Contains the type of registration used for physical delivery of a message.
ptagRenderingPosition Contains an offset, in characters, to use in rendering an attachment within the main message text.
ptagRenPropTagArray 0x67810102
ptagReplChanges 0x3FD20102
ptagReplHeader 0x3FD00102
ptagReplHeaderTwo 0x3FC00102
ptagReplicaChangeNumber 0x3FC80102
ptagReplicaGuid 0x67D00102
ptagReplicaList 0x66980102
ptagReplicaListR 0x67610102
ptagReplicaListRC 0x67620102
ptagReplicaListRCGUB 0x67600102
ptagReplicaListRGUB 0x67630102
ptagReplicaServer 0x6644001E
ptagReplicationAlwaysInterval 0x66940003
ptagReplicationMsgPriority 0x66920003
ptagReplicationMsgSize 0x66950003
ptagReplicationStyle 0x66900003
ptagReplicationTib 0x66910102
ptagReplicaVersion 0x664B0014
ptagReplid 0x67690003
ptagReplMsgPriority 0x67DF0003

ptagReplMsgType 0x67EA0003
ptagReplMsgVersion 0x67DE0003
ptagReplPrivate 0x3FC90102
ptagReplReserved1 0x3FF00102
ptagReplRgm 0x3FD30102
ptagReplSchedule 0x67DC0003
ptagReplSearchFolderProps 0x3FC70102
ptagReplServerInfo Contains a binary value that indicates the relative position of this message within a conversation thread.
ptagReplStateFlags 0x67DD0003
ptagReplStatus 0x3FD10102
ptagReplyFwdStatus 0x7C0B001E
ptagReplyRecipientEntries Contains a sized array of entry identifiers for recipients that are to get a reply.
ptagReplyRecipientNames Contains a list of display names for recipients that are to get a reply.
ptagReplyRecipientSMTPProxies 0x3FFC001E
ptagReplyRequested Contains true if a message sender requests a reply from a recipient.
ptagReplyTemplateId 0x65C20102
ptagReportAddrType 0x402684E4
ptagReportCAI 0x67BC0102
ptagReportDestEntryId 0x66650102
ptagReportDestinationAddrType 0x406284E4
ptagReportDestinationCAI 0x67F90102
ptagReportDestinationEmailAddr 0x406384E4
ptagReportDestinationEntryId 0x66650102
ptagReportDestinationFlags 0x405C0003
ptagReportDestinationGuid 0x0E470102
ptagReportDestinationName 0x6664001E
ptagReportDestinationOrgAddrType 0x405584E4
ptagReportDestinationOrgEmailAddr 0x405684E4
ptagReportDestinationSearchKey 0x40640102
ptagReportDestinationSid 0x0E540102
ptagReportDestinationSidAsXML 0x0E75001E
ptagReportDestinationSimpleDispName 0x405F84E4
ptagReportDestinationSMTPAddress 0x0E90001E

ptagReportDestName 0x6664001E
ptagReportDisplayName 0x402884E4
ptagReportEmailAddr 0x402784E4
ptagReportEntryId Contains the entry identifier for the recipient that should get reports for this message.
ptagReportFlags 0x401F0003
ptagReportGuid 0x0E450102
ptagReportingDLName Contains the display name of a distribution list for which the messaging system is delivering a report.
ptagReportOrgAddrType 0x404D84E4
ptagReportOrgEmailAddr 0x404E84E4
ptagReportSearchKey Contains the search key for the recipient that should get reports for this message.
ptagReportSid 0x0E520102
ptagReportSidAsXML 0x0E73001E
ptagReportSimpleDispName 0x403784E4
ptagReportSMTPAddress 0x0E8E001E
ptagReportTag Contains a binary tag value that the messaging system should copy to any report generated for the message.
ptagReportText Contains optional text for a report generated by the messaging system.
ptagReportTime Contains the date and time when the messaging system generated a report.
ptagRequestedDeliveryMethod Contains a binary array of delivery methods (service providers), in order of a message sender's preference.
ptagRequiresRefResolve 0x6751000B
ptagReserveRangeOfIds 0x0E7B0102
ptagResolveMethod 0x3FE70003
ptagResourceFlags Contains a bitmask of flags for message services and providers.
ptagResourceMethods Contains a bitmask of flags indicating the methods in the IMAPISStatus interface that are supported by the status object.
ptagResponsibility Contains true if some transport provider has already accepted responsibility for delivering the message to this recipient, and false if the MAPI spooler considers that this transport provider should accept responsibility.
ptagRestrictFlags 0x67DC0003

ptagRestrictUserFlags 0x67DD0003
ptagRetentionAgeLimit 0x66C40003
ptagRetryTime 0x681E0040
ptagReturnRequested Contains true if this message should be returned with a report.
ptagRfc822Bcc 0x6758001E
ptagRfc822Cc 0x6757001E
ptagRfc822From 0x6756001E
ptagRfc822To 0x6755001E
ptagRgszDNResponsters 0x67EB0102
ptagRights 0x66390003
ptagRmi 0x3FD40102
ptagRootFID 0x67640014
ptagRowId Contains a unique identifier for a recipient in a recipient table or status table.
ptagRowType Contains a value that indicates the type of a row in a table.
ptagRsd 0x67600102
ptagRte 0x67610102
ptagRTFCompressed Contains the Rich Text Format version of the message text, usually in compressed form.
ptagRTFInSync Contains true if PR_RTF_COMPRESSED has the same text content as PR_BODY for this message.
ptagRTFSyncBodyCount Contains a count of the significant characters of the message text.
ptagRTFSyncBodyCRC Contains the cyclical redundancy check (CRC) computed for the message text.
ptagRTFSyncBodyTag Contains significant characters that appear at the beginning of the message text.
ptagRuleActionNumber 0x66500003
ptagRuleActions 0x668000FE
ptagRuleActionType 0x66490003
ptagRuleCondition 0x667900FD
ptagRuleError 0x66480003
ptagRuleFolderEntryId 0x66510102
ptagRuleFolderFID 0x67420014
ptagRuleFolderGidSvrEID 0x36430102
ptagRuleId 0x66740014

ptagRuleIds 0x66750102
ptagRuleLevel 0x66830003
ptagRuleMsgActions 0x65EF0102
ptagRuleMsgActionsOld 0x66800102
ptagRuleMsgCondition 0x65F00102
ptagRuleMsgConditionLCID 0x65F10003
ptagRuleMsgConditionOld 0x66790102
ptagRuleMsgLevel 0x65ED0003
ptagRuleMsgName 0x65EC001E
ptagRuleMsgProvider 0x65EB001E
ptagRuleMsgProviderData 0x65EE0102
ptagRuleMsgSequence 0x65F30003
ptagRuleMsgState 0x65E90003
ptagRuleMsgUserFlags 0x65EA0003
ptagRuleMsgVersion 0x65F20002
ptagRuleName 0x6682001E
ptagRuleProvider 0x6681001E
ptagRuleProviderData 0x66840102
ptagRulesData 0x3FE10102
ptagRuleSequence 0x66760003
ptagRulesSync 0x67600003
ptagRulesTable 0x3FE1000D
ptagRuleState 0x66770003
ptagRuleTriggerHistory 0x3FF20102
ptagRuleUserFlags 0x66780003
ptagRuleVersion 0x668D0002
ptagScheduleFolder 0x661E0102
ptagScopeFIDs 0x67120102
ptagSearchAttachments 0x666D001F
ptagSearchBacklinks 0x67870102
ptagSearchedFID 0x0E650014
ptagSearchedFIDs 0x67C50102
ptagSearchFID 0x67490014
ptagSearchFIDs 0x67850102
ptagSearchFlags 0x67830003
ptagSearchGUID 0x67CE0102
ptagSearchKey Contains a binary-comparable key that identifies correlated

objects for a search.

ptagSearchRestriction 0x67840102

ptagSearchState 0x67830003

ptagSecondUpgradeList 0x67D30102

ptagSecureInSite 0x669E000B

ptagSecureOrigination 0x3FE5000B

ptagSenderAddrType Contains the message sender's e-mail address type.

ptagSenderCAI 0x67B50102

ptagSenderEmailAddr Contains the message sender's e-mail address.

ptagSenderEntryId Contains the message sender's entry identifier.

ptagSenderFlags 0x40190003

ptagSenderGuid 0x0E400102

ptagSenderMdbGuid 0x67610102

ptagSenderName Contains the message sender's display name.

ptagSenderOrgAddrType 0x403F84E4

ptagSenderOrgEmailAddr 0x404084E4

ptagSenderReplid 0x67E70102

ptagSenderSearchKey Contains the message sender's search key.

ptagSenderServerVersion 0x67600003

ptagSenderSid 0x0E4D0102

ptagSenderSidAsXML 0x0E6E001E

ptagSenderSimpleDispName 0x403084E4

ptagSenderSMTPAddress 0x0E89001E

ptagSendInternetEncoding Contains a bitmask of encoding preferences.

ptagSendRichInfo Contains true if the recipient can receive all message content, including Rich Text Format and OLE objects.

ptagSensitivity Contains a value indicating the message sender's opinion of the sensitivity of a message.

ptagSentMailEntryId Contains the entry identifier of the folder where the message should be moved after submission.

ptagSentMailSvrEID 0x674000FB

ptagSentMailSvrEIDBin 0x65F70102

ptagSentRepresentingAddrType Contains the address type for the messaging user represented by the sender.

ptagSentRepresentingCAI 0x67B60102

ptagSentRepresentingEmailAddr Contains the e-mail address for the messaging user represented by the sender.

ptagSentRepresentingEntryId Contains the entry identifier for the messaging user represented by the sender.

ptagSentRepresentingFlags 0x401A0003

ptagSentRepresentingGuid 0x0E410102

ptagSentRepresentingName Contains the display name for the messaging user represented by the sender.

ptagSentRepresentingOrgAddrType 0x404184E4

ptagSentRepresentingOrgEmailAddr 0x404284E4

ptagSentRepresentingSearchKey Contains the search key for the messaging user represented by the sender.

ptagSentRepresentingSid 0x0E4E0102

ptagSentRepresentingSidAsXML 0x0E6F001E

ptagSentRepresentingSimpleDispName 0x403184E4

ptagSentRepresentingSMTPAddress 0x0E8A001E

ptagSEQID 0x3F810014

ptagServerDN_A 0x66E0001E

ptagServerDN_W 0x66E0001F

ptagServerName 0x67FF0102

ptagServerRuleId 0x65A00014

ptagSetReceiveCount 0x67800003

ptagSEV 0x67C40003

ptagSharedReceiptHandling 0x67AD000B

ptagShowJournaledBCC 0x0EA0000B

ptagShutoffQuota 0x68050003

ptagSimpleDisplayCc 0x67FD001E

ptagSimpleDisplayName Contains a 7-bit ASCII version of a messaging user's name.

ptagSimpleDisplayTo 0x678E001E

ptagSiteID 0x67F80003

ptagSiteName 0x67FA0102

ptagSiteStatus 0x675F0003

ptagSmtplargeP1Limit 0x664E0003

ptagSMTPTempTblData 0x10C00102

ptagSMTPTempTblData2 0x10C10003

ptagSMTPTempTblData3 0x10C20102

ptagSoftDeleted 0x6770000B

ptagSoftDeletes 0x40210102

ptagSoftRefCt 0x67790003
ptagSortLocaleId 0x67050003
ptagSortOrder 0x67610102
ptagSourceEntryId 0x67A80102
ptagSourceFID 0x0E5F0014
ptagSplusFreeBusyFolder 0x66220102
ptagSpoolerStatus Contains the status of the message based on information available to the MAPI spooler.
ptagSql 0x65D0001F
ptagSqlFrom 0x65D2001F
ptagSqlGroup 0x65D5001F
ptagSqlOrder 0x65D4001F
ptagSqlSelect 0x65D1001F
ptagSqlWhere 0x65D3001F
ptagSRCHID 0x67C30102
ptagSrcURLName 0x670F001F
ptagSRD 0x3FC80102
ptagStartEmbed 0x40010003
ptagStartFAIMsg 0x40100003
ptagStartMessage 0x400C0003
ptagStartRecip 0x40030003
ptagStartSubFld 0x400A0003
ptagStartTime 0x681B0040
ptagStartTopFld 0x40090003
ptagStatusCode Contains a bitmask of flags indicating the current status of a session resource. All service providers set status codes as does MAPI to report on the status of the subsystem, the MAPI spooler, and the integrated address book.
ptagStorageQuota 0x677B0003
ptagStorageQuotaLimit 0x3FF50003
ptagStoreEntryId Contains the unique entry identifier of the message store in which an object resides.
ptagStoreRecordKey Contains the unique binary-comparable identifier (record key) of the message store in which an object resides.
ptagStoreSlowLink 0x7C0A000B
ptagStoreSupportMask Contains a bitmask of flags that client applications should query to determine the characteristics of a message store.

ptagSubfolder 0x6708000B
ptagSubfolderCt 0x0E630003
ptagSubfolderEntriesAdded 0x67F4000B
ptagSubFolders Contains true if a folder contains subfolders.
ptagSubject Contains the full subject of a message.
ptagSubjectPrefix Contains a subject prefix that typically indicates some action on a message.
ptagSubjectTraceInfo 0x66610102
ptagSubmitContLength 0x677C0003
ptagSubmitFlags Contains a bitmask of flags indicating details about a message submission.
ptagSubmitResponsibility 0x67AB0003
ptagSubmittedCount 0x67820003
ptagSubmitTime Contains the date and time the message sender submitted a message.
ptagSupersedes 0x103A001E
ptagSupersedes 0x103A001E
ptagSupplementaryInfo Contains additional information for use in a report.
ptagSvrGeneratingQuotaMsg 0x3FF7001E
ptagSyncDs 0x679D0003
ptagSyncEventFired 0x664F000B
ptagSyncEventSuppressGuid 0x38800102
ptagSysConfigFolder 0x66360102
ptagTargetEntryId 0x30100102
ptagTemporary 0x676D000B
ptagTestLineSpeed 0x662B0102
ptagTIB 0x67DB0002
ptagTibArray 0x67DB0102
ptagTraceInfo 0x66600102
ptagTransferEnabled 0x662A000B
ptagTransitionSizeDelta 0x66560003
ptagTransmissionTime 0x67E20040
ptagTransmittableDisplayName Contains a recipient's display name in a form with enhanced security so that it cannot be changed.
ptagTrustSender 0x0E790003
ptagTypeOfMTSUser Contains the type of a message recipient, for use in a report.

ptagUnique 0x67C60003
ptagUnlockMid 0x68070014
ptagUnlockMsg 0x68070102
ptagUnModified 0x6713000B
ptagUpgradeList 0x67DB0102
ptagURLCompName 0x10F3001F
ptagURLCompNameHash 0x67100003
ptagURLCompNameMungable 0x0E66000B
ptagURLCompNamePostfix 0x0E610003
ptagURLCompNameSet 0x0E62000B
ptagURLName 0x6707001F
ptagURLNameHash 0x68080003
ptagUsenetSiteName 0x6802001E
ptagUserCertificate Contains an ASN.1 authentication certificate for a messaging user.
ptagUserConfigurationDataType 0x7C060003
ptagUserConfigurationDictionary 0x7C070102
ptagUserConfigurationStream 0x7C090102
ptagUserConfigurationXmlStream 0x7C080102
ptagUserEntryId 0x66190102
ptagUserGUID 0x676A0102
ptagUserName 0x661A001E
ptagUserSid 0x67830102
ptagValidFolderMask Contains a bitmask of flags that indicate the validity of the entry identifiers of the folders in a message store.
ptagVersioningFlags 0x3F900002
ptagVersionOpCode 0x3F850003
ptagVersionOpData 0x3F860102
ptagVersionSequenceNumber 0x3F870003
ptagVID 0x3F880014
ptagViewDeleteTime 0x0E660040
ptagViewSearchFolder 0x67AA000B
ptagVirusScannerStamp 0x0E960102
ptagWatermark 0x681C0014
ptagWin32NTSD 0x3D220102
ptagX400EnvelopeType 0x66530003
ptagXcn 0x65E20102

ptagXfid 0x65E00102
ptagXID 0x674B0014
ptagXmid 0x65E00102
ptagXmtSecurityRole1 0x3D250102
ptagXmtSecurityRole1AsXML 0x3D25001E
ptagXmtSecurityRole2 0x3D260102
ptagXmtSecurityRole2AsXML 0x3D26001E
ptagXmtSecurityRole3 0x3D270102
ptagXmtSecurityRole3AsXML 0x3D27001E
ptagXmtSecurityRole4 0x3D280102
ptagXmtSecurityRole4AsXML 0x3D28001E
ptagXmtSecurityRole5 0x3D290102
ptagXmtSecurityRole5AsXML 0x3D29001E
ptagXmtSecurityRole6 0x3D2A0102
ptagXmtSecurityRole6AsXML 0x3D2A001E
ptagXmtSecurityRole7 0x3D2B0102
ptagXmtSecurityRole7AsXML 0x3D2B001E
ptagXmtSecurityRole8 0x3D2C0102
ptagXmtSecurityRole8AsXML 0x3D2C001E
ptagXpcl 0x65E30102
ptagXPostList 0x65F80102
ptagXPostListURL 0x65F8101F
ptagXref 0x67850102
ptagXrefComplete 0x6770000B
ptagXrefString 0x67860102
ptagXVID 0x3F950102

Value property

Applies to

[TMSGProperty](#) component

Declaration

```
property Value: Variant;
```

Description

Returns the actual value of the property/attribute with original type.

To get the value converted as string, use the [AsString](#) property

ValueLength property

Applies to

[TMSGProperty](#) component

Declaration

```
property ValueLength: Integer;
```

Description

Returns the actual length of value for the property/attribute.

Please note that content of attached file or another binary property/attribute, can contain the "system" characters (including #0)

AttachmentIsEmbeddedMessage method

[Example](#)

Applies to

[TMSGProperty](#) component

Declaration

```
function AttachmentIsEmbeddedMessage: Boolean;
```

Description

If property/attribute contains the sub-properties (so usually this is attached file or forwarded message), you may check if this is an embedded/forwarded message

GetAttachmentFileName method

[See also](#)

Applies to

[TMSGProperty](#) component

Declaration

```
function GetAttachmentFileName(Index: Integer): string;
```

Description

This method returns the original file name for attached file. Use this value to save the file on disk.

GetAttachmentFileSize method

Applies to

[TMSGProperty](#) component

Declaration

```
function GetAttachmentFileSize(Index: Integer): Integer;
```

Description

This method returns the original file size for attached file.

GetAttachmentName method

[See also](#)

Applies to

[TMSGProperty](#) component

Declaration

```
function GetAttachmentName(Index: Integer): string;
```

Description

This method returns the human caption for for attached file or embedded message.

GetName method

Applies to

[TMSGProperty](#) component

Declaration

```
function GetName(IncludeCaption, MAPIAlways: Boolean): string;
```

Description

Returns the "human" description of property by [TagID](#) property

For example, for PR_ADDRTYPE tag:

GetName(True, True) returns the 'ADDRTYPE (Address Type)'

GetName(False, True) returns the 'ADDRTYPE'

PropertyType method

Applies to

[TMSGProperty](#) component

Declaration

```
function PropertyType: Integer;
```

Description

Returns the part of [TagID](#) property which presents the value type

The next property types supported:

const

{ Property Types }

MV_FLAG = \$1000; // Multi-value flag

PT_UNSPECIFIED = ULONG(0); // (Reserved for interface use) type doesn't matter to caller

PT_NULL = ULONG(1); // NULL property value

PT_I2 = ULONG(2); // Signed 16-bit value

PT_LONG = ULONG(3); // Signed 32-bit value

PT_R4 = ULONG(4); // 4-byte floating point

PT_DOUBLE = ULONG(5); // Floating point double

PT_CURRENCY = ULONG(6); // Signed 64-bit int (decimal w/ 4 digits right of decimal pt)

PT_APPTIME = ULONG(7); // Application time

PT_ERROR = ULONG(10); // 32-bit error value

PT_BOOLEAN = ULONG(11); // 16-bit boolean (non-zero true)

PT_OBJECT = ULONG(13); // Embedded object in a property

PT_I8 = ULONG(20); // 8-byte signed integer

PT_STRING8 = ULONG(30); // Null terminated 8-bit character string

PT_UNICODE = ULONG(31); // Null terminated Unicode string

PT_SYSTIME = ULONG(64); // FILETIME 64-bit int w/ number of 100ns periods since Jan 1,1601

PT_CLSID = ULONG(72); // OLE GUID

PT_BINARY = ULONG(258); // Uninterpreted (counted byte array)

{ Alternate property type names for ease of use }

PT_TSTRING = PT_STRING8;

PT_MV_TSTRING = MV_FLAG or PT_STRING8;

PT_SHORT = PT_I2;

PT_I4 = PT_LONG;

PT_FLOAT = PT_R4;

PT_R8 = PT_DOUBLE;

PT_LONGLONG = PT_I8;

PT_MV_I2 = (MV_FLAG or PT_I2);

PT_MV_LONG = (MV_FLAG or PT_LONG);

PT_MV_R4 = (MV_FLAG or PT_R4);

PT_MV_DOUBLE = (MV_FLAG or PT_DOUBLE);

PT_MV_CURRENCY = (MV_FLAG or PT_CURRENCY);

PT_MV_APPTIME = (MV_FLAG or PT_APPTIME);

PT_MV_SYSTIME = (MV_FLAG or PT_SYSTIME);

PT_MV_STRING8 = (MV_FLAG or PT_STRING8);

PT_MV_BINARY = (MV_FLAG or PT_BINARY);

PT_MV_UNICODE = (MV_FLAG or PT_UNICODE);

PT_MV_CLSID = (MV_FLAG or PT_CLSID);

PT_MV_I8 = (MV_FLAG or PT_I8);

{ Alternate property type names for ease of use }

PT_MV_SHORT = PT_MV_I2;

PT_MV_I4 = PT_MV_LONG;

PT_MV_FLOAT = PT_MV_R4;

PT_MV_R8 = PT_MV_DOUBLE;

PT_MV_LONGLONG = PT_MV_I8;

ApplyGeneralProperty method

Applies to

[TMSGProperty](#) component

Declaration

```
procedure ApplyGeneralProperty(Stream: TStream; AID, ATypeID: dWord);
```

Description

This method allow to parse the general attribute ('__properties_version1.0' container in msg-stream)

ApplyValue method

Applies to

[TMSGProperty](#) component

Declaration

```
procedure ApplyValue(Stream: TStream; brLen: Integer);
```

Description

This method allow to load the property/attribute from stream

ApplyValueTag method

Applies to

[TMSGProperty](#) component

Declaration

```
procedure ApplyValueTag(ATagID: Integer; Stream: TStream; brLen: Integer);
```

Description

This method allow to load the tag from stream

TMSGProperties component

[See also](#) [Properties](#) [Methods](#)

Unit

[smmsg](#)

Description

TMSGProperties is a container for [TMSGProperty](#) objects.

Items property

Applies to

[TMSGProperties](#) component

Declaration

```
property Items[i: Integer]: TMSGProperty;
```

Description

An index of the columns in the collection.

The value of the Index parameter corresponds to the Index property of TMsgProperty.

Create method

Applies to

[TMSGProperties](#) component

Declaration

constructor Create(AOwner: TComponent);

Description

Creates and initializes a TMSGProperties object.

Add method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

function Add: [TMSGProperty](#);

Description

Creates a new TMSGProperty instance and adds it to the Items array.

Add method returns the new property/attribute for message.

GetAttachment method

[See also](#) [Example](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetAttachment(Index: Integer): TMSGProperty;
```

Description

Returns the attachment item from collection by Index parameter

GetAttachmentCount method

[See also](#) [Example](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetAttachmentCount: Integer;
```

Description

Returns the count of attachments in message

GetBCC method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetBCC: WideString;
```

Description

Returns the recipient addresses (BCC:)

GetBody method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetBody: WideString;
```

Description

Returns the body (plain text) for message

GetCC method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetCC: WideString;
```

Description

Returns the recipient addresses (CC:)

GetCodePage method

Applies to

[TMSGProperties](#) component

Declaration

```
function GetCodePage: Integer;
```

Description

Returns the codepage for message (PR_MESSAGE_CODEPAGE tag)

GetHTMLBody method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetHTMLBody: WideString;
```

Description

Returns the body (HTML-formatted) for message

GetMessageDate method

Applies to

[TMSGProperties](#) component

Declaration

```
function GetMessageDate: TDateTime;
```

Description

Returns the date when message was submitted (PR_CLIENT_SUBMIT_TIME tag) or delivered (PR_MESSAGE_DELIVERY_TIME tag)

GetMessageID method

Applies to

[TMSGProperties](#) component

Declaration

```
function GetMessageID: WideString;
```

Description

Returns the unique message identifier (PR_INTERNET_MESSAGE_ID tag)

GetPropertyAsString method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetPropertyAsString(ATagID: Integer; WithoutType,  
IncludeDetails: Boolean): WideString;
```

Description

Search the property/attribute by [TagID](#) value and return the string value

GetPropertyByTag method

[See also](#) [Example](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetPropertyByTag(ATagID: Integer; WithoutType,  
IncludeDetails: Boolean): TMSGProperty;
```

Description

Search the property/attribute by [TagID](#) value

GetRecipientName method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetRecipientName: WideString;
```

Description

Returns the human presentation of recipient (like '[Peter Smith](#) <[peter@domain.com](#)>')

GetRTFBody method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetRTFBody: WideString;
```

Description

Returns the body (RichEdit-text formatted) for message

GetSenderName method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetSenderName: WideString;
```

Description

Returns the human presentation of sender (like '[Peter Smith](#) <[peter@domain.com](#)>')

GetSubject method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
function GetSubject: WideString;
```

Description

Returns the subject (plain text) for message

GetTransportHeader method

Applies to

[TMSGProperties](#) component

Declaration

```
function GetTransportHeader: WideString;
```

Description

Returns the full header for message which include the route, original IP etc

IsMainProperties method

Applies to

[TMSGProperties](#) component

Declaration

```
function IsMainProperties: Boolean;
```

Description

True for usual normal message

False for embedded/forwarded message

SaveAttachmentToFile method

[See also](#) [Example](#)

Applies to

[TMSGProperties](#) component

Declaration

```
procedure SaveAttachmentToFile(Index: Integer; const AFileName:  
string);
```

Description

Allow to save the attached file to file

SaveAttachmentToStream method

[See also](#)

Applies to

[TMSGProperties](#) component

Declaration

```
procedure SaveAttachmentToStream(Index: Integer; Stream: TStream);
```

Description

Allow to save the attached file to any stream (memory stream, BLOB-field, ole-container etc)

SaveToMsgFile method

[Example](#)

Applies to

[TMSGProperties](#) component

Declaration

```
procedure SaveToMsgFile(const AFileName: string; SaveAllProperties:  
Boolean);
```

Description

Allow to create the new msg-file with message content

TSMMMessage component

[See also](#) [Properties](#) [Methods](#)

Unit

[smmsg](#)

Description

TSMMMessage class is a basic type for message parsers.

About property

Applies to

[TSMMessage](#) component

Declaration

property About: [TSMMAbout](#);

Description

This is design-time property only.

If you press an ellipses button in Object Inspector, you'll see a dialog with short information about SMMsg suite and authors.

BCC property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property BCC: WideString;
```

Description

Returns the recipient addresses (BCC:)

Body property

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
property Body: WideString;
```

Description

Returns the body (plain text) for message

CC property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property CC: WideString;
```

Description

Returns the recipient addresses (CC:)

HTMLBody property

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
property HTMLBody: WideString;
```

Description

Returns the body (html-formatted) for message

MessageDate property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

property MessageDate: TDateTime;

Description

Returns the date when message was submitted (PR_CLIENT_SUBMIT_TIME tag) or delivered (PR_MESSAGE_DELIVERY_TIME tag)

MessageID property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

property MessageID: WideString;

Description

Returns the unique message identifier (PR_INTERNET_MESSAGE_ID tag)

Properties property

Applies to

[TSMMMessage](#) component

Declaration

property Properties: [TMSGProperties](#);

Description

Use Properties to read or set the message properties/attributes and display attributes of the message in your form.

Properties can be set at design time through the standard editor, or programmatically at runtime.

RecipientName property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property RecipientName: WideString;
```

Description

Returns the human presentation of recipient (like 'Peter Smith <peter@domain.com>')

RTFBody property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property RTFBody: WideString;
```

Description

Returns the body (rtf-formatted) for message

SenderName property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property SenderName: WideString;
```

Description

Returns the human presentation of sender (like 'Peter Smith <peter@domain.com>')

Subject property

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
property Subject: WideString;
```

Description

Returns the subject (plain text) for message

TransportHeader property

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
property TransportHeader: WideString;
```

Description

Returns the full header for message which include the route, original IP etc

GetHTMLCharset method

Applies to

[TSMMessage](#) component

Declaration

```
function GetHTMLCharset: string;
```

Description

This method converts the [CodePage](#) of message into html-charset.

For example,

1252 iso-8859-1

20866 koi8-r

932 shift_jis

950 big5

936 gb2312

50221 csISO2022JP

6500 UNICODE-1-1-UTF-7

...

LoadFromFile method

[See also](#) [Example](#)

Applies to

[TSMMessage](#) component

Declaration

```
procedure LoadFromFile(const AFileName: string);
```

Description

Loads the message from file

LoadFromStream method

[See also](#) [Example](#)

Applies to

[TSMMMessage](#) component

Declaration

```
procedure LoadFromStream(Stream: TStream); virtual;
```

Description

Loads the message from stream (memory, BLOB-field, archive stream etc)

SaveToEMLFile method

[See also](#)

Applies to

[TSMMMessage](#) component

Declaration

```
procedure SaveToEMLFile(const AFileName: string; SaveAllProperties:  
Boolean); virtual;
```

Description

Allow to create the new EML-file with message content (compatible with any mailer)

If SaveAllProperties parameter is False then only general properties (like Sender, Recipient, Subject, message date etc) saved

SaveToHTMLFile method

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
procedure SaveToHTMLFile(const AFileName: string;  
SaveAllProperties: Boolean); virtual;
```

Description

Allow to create the new HTML-file with message content

If SaveAllProperties parameter is False then only general properties (like Sender, Recipient, Subject, message date etc) saved

SaveToMsgFile method

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
procedure SaveToMsgFile(const AFileName: string; SaveAllProperties:  
Boolean);
```

Description

Allow to create the new MSG-file with message content

If SaveAllProperties parameter is False then only general properties (like Sender, Recipient, Subject, message date etc) saved

SaveToFile method

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
procedure SaveToFile(const AFileName: string;  
SaveAllProperties: Boolean); virtual;
```

Description

Allow to create the new text file with message content.

If SaveAllProperties parameter is False then only general properties (like Sender, Recipient, Subject, message date etc) saved

SaveToXMLFile method

[See also](#)

Applies to

[TSMMessage](#) component

Declaration

```
procedure SaveToXMLFile(const AFileName: string; SaveAllProperties:  
Boolean); virtual;
```

Description

Allow to create the new XML-file with message content.

If SaveAllProperties parameter is False then only general properties (like Sender, Recipient, Subject, message date etc) saved

TSMMSGFile component

[Hierarchy](#), [See also](#) [Methods](#)

Unit

[smmsg](#)

Description

TSMMSGFile class is a parser for MSG-files.

MSG-file used by MS Outlook to create the messages.

TSMTNEFFile component

[Hierarchy](#), [See also](#) [Methods](#)

Unit

[smmsg](#)

Description

TSMTNEFFile class is a parser for winmail.dat file which created by MS Outlook.

This file contains the full message including text formatting, attachments etc

TSMEMLFile component

[Hierarchy](#), [See also](#) [Properties](#) [Methods](#) [Events](#)

Unit

[smmsg](#)

Description

TSMEMLFile class is a parser for EML-files

See the RFC for information about EML-files with messages:

RFC822 <http://www.faqs.org/rfcs/rfc822.html>

RFC1049 <http://www.faqs.org/rfcs/rfc1049.html>

RFC2045 <http://www.faqs.org/rfcs/rfc2045.html>

RFC2046 <http://www.faqs.org/rfcs/rfc2046.html>

RFC2047 <http://www.faqs.org/rfcs/rfc2047.html>

OnConvertCodepage event

Applies to

[TSMEMLFile](#) component

Declaration

property OnConvertCodepage: [TSMMSGConvertCodepage](#);

Description

This event called for every property/attribute.

In own handler you may convert the string value using any (own or third-party) library which supports the codepage conversions

OriginalEML property

Applies to

[TSMEMLFile](#) component

Declaration

```
property OriginalEML: TStrings;
```

Description

Returns the list of original contents for loaded EML-message

Properties

▸ Run-time only ▣ Key properties

▸ ▣ [AsString](#)

▣ [Category.](#)

▣ [SubProperties](#)

▣ [TagID](#)

▣ [Value](#)

▸ ▣ [ValueLength](#)

Methods

- Key methods

~~Create~~{linkDelphi=Create_Method}

~~Destroy~~{linkDelphi=Destroy_Method}

- [AttachmentIsEmbeddedMessage](#)

- [GetAttachmentFileName](#)

- [GetAttachmentFileSize](#)

- [GetAttachmentName](#)

- [GetName](#)

- [PropertyType](#)

- [ApplyGeneralProperty](#)

- [ApplyValue](#)

- [ApplyValueTag](#)

~~Assign~~{linkDelphi=Assign_Method}

smmsg unit

In this unit all basic classes and types are declared for message parsers.

Components

[TMSGProperty](#)

[TMSGProperties](#)

[TSMMMessage](#)

[TSMMMSGFile](#)

[TSMTNEFFile](#)

[TSMEMLFile](#)

Types

[TMSGPropertyCategory](#)

[TSMMAbout](#)

[TSMMMSGConvertCodepage](#)

Constants

SMMSGVersion

TMSGPropertyCategory type

[See also](#)

Unit

[smmsg](#)

Declaration

```
type TMSGPropertyCategory = (mpcGeneral, mpcEnvelope, mpcRecipient,  
mpcNonTransmittable, mpcMessage, mpcTransportEnvelope,  
mpcTransportRecipient, mpcUserNonTransmittable,  
mpcProviderNonTransmittable, mpcMessageClassContent,  
mpcMessageClassNonTransmittable, mpcUserProperty, mpcMessageStore,  
mpcFolderABContainer, mpcAttachment, mpcAddressBook, mpcUser,  
mpcDistributionList, mpcProfile, mpcStatus);
```

Description

Enumerates the available categories for properties/attributes in message

AttachmentsIsEmbeddedMessage method example

{attachments}

```
for i := 0 to AProperties.GetAttachmentCount-1 do  
begin  
  prop := AProperties.GetAttachment(i);  
  if Assigned(prop) then  
    begin  
      if prop.AttachmentsIsEmbeddedMessage then  
        <this is forwarded message>  
      else  
        <this is attached file>;  
      end;  
    end  
  end;  
end;
```

See also

- [GetAttachmentName](#)

See also

- [GetAttachmentFileName](#)

See also

[Properties](#)

[SubProperties](#)

Properties

▶ Run-time only ■ Key properties

▶ ■ [Items](#)

Methods

- Key methods
- [Create](#)
- [Add](#)
- [GetAttachment](#)
- [GetAttachmentCount](#)
- [GetBCC](#)
- [GetBody](#)
- [GetCC](#)
- [GetCodePage](#)
- [GetHTMLBody](#)
- [GetMessageDate](#)
- [GetMessageID](#)
- [GetPropertyAsString](#)
- [GetPropertyByTag](#)
- [GetRecipientName](#)
- [GetRTFBody](#)
- [GetSenderName](#)
- [GetSubject](#)
- [GetTransportHeader](#)
- [IsMainProperties](#)
- [SaveAttachmentToFile](#)
- [SaveAttachmentToStream](#)
- [SaveToMsgFile](#)

See also

▶  [Items](#)

See also

- [GetAttachmentCount](#)

GetAttachment method example

{attachments}

```
for i := 0 to AProperties.GetAttachmentCount-1 do  
begin  
  prop := AProperties.GetAttachment(i);  
  if Assigned(prop) then  
    begin  
      with ListViewAttachments.Items.Add do  
        begin  
          Caption := prop.GetAttachmentName(i);  
          SubItems.Add(prop.GetAttachmentFileName(i));  
  
          if prop.AttachmentsIsEmbeddedMessage then  
            ImageIndex := 1  
          else  
            ImageIndex := 0;  
          end;  
        end  
      end;  
    end;  
  end;  
end;
```

See also

- [GetAttachment](#)

GetAttachmentCount method example

{attachments}

```
for i := 0 to AProperties.GetAttachmentCount-1 do  
begin  
  prop := AProperties.GetAttachment(i);  
  if Assigned(prop) then  
    begin  
      with ListViewAttachments.Items.Add do  
        begin  
          Caption := prop.GetAttachmentName(i);  
          SubItems.Add(prop.GetAttachmentFileName(i));  
  
          if prop.AttachmentsIsEmbeddedMessage then  
            ImageIndex := 1  
          else  
            ImageIndex := 0;  
          end;  
        end  
      end;  
    end;  
  end;  
end;
```

See also

- [GetCC](#)

See also

- [GetHTMLBody](#).
- [GetRTFBody](#).
- [GetSubject](#)

See also

- [GetBCC](#)

See also

- [GetBody](#).
- [GetRTFBody](#).
- [GetSubject](#)

See also

- [GetPropertyByTag](#)

See also

- [GetPropertyAsString](#)

GetPropertyByTag method example

```
function GetAttachmentFileSize(attach: TMSGProperty; Index: Integer): Integer;  
var  
p: TMSGProperty;  
begin  
  p := attach.SubProperties.GetPropertyByTag(PR_ATTACH_SIZE, False, False);  
  if Assigned(p) then  
    Result := VarAsType(p.Value, varInteger)  
  else  
    begin  
      p := attach.SubProperties.GetPropertyByTag(PR_ATTACH_DATA_OBJ, False, False);  
      if Assigned(p) then  
        Result := p.ValueLength  
      else  
        Result := 0;  
      end  
    end;  
end;
```

See also

- [GetSenderName](#)

See also

- [GetBody](#).
- [GetHTMLBody](#).
- [GetSubject](#)

See also

- [GetRecipientName](#)

See also

- [GetBody](#).
- [GetMessageDate](#)
- [GetRecipientName](#)
- [GetRTFBody](#).
- [GetSenderName](#)

See also

- [GetAttachment](#)
- [GetAttachmentCount](#)
- [SaveAttachmentToStream](#)

SaveAttachmentToFile method example

```
msg.Properties.SaveAttachmentToFile(AttachmentIndex, yourFileName)
```

See also

- [GetAttachment](#)
- [GetAttachmentCount](#)
- [SaveAttachmentToFile](#)

SaveToMsgFile method example

```
msg.SubProperties.SaveToMsgFile(yourFileName, True)
```

See also

[TSMMSGFile](#)

[TSMTNEFFile](#)

[TSMEMLFile](#)

Properties

▸ Run-time only ▣ Key properties

▣ [About](#)

▸ ▣ [BCC](#)

▸ ▣ [Body](#)

▸ ▣ [CC](#)

▸ ▣ [HTMLBody](#)

▸ ▣ [MessageDate](#)

▸ ▣ [MessageID](#)

▣ [Properties](#)

▸ ▣ [RecipientName](#)

▸ ▣ [RTFBody](#)

▸ ▣ [SenderName](#)

▸ ▣ [Subject](#)

▸ ▣ [TransportHeader](#)

Methods

- Key methods

~~Create~~{linkDelphi=Create_Method}

~~Destroy~~{linkDelphi=Destroy_Method}

- [GetHTMLCharset](#)

- [LoadFromFile](#)

- [LoadFromStream](#)

- [SaveToEMLFile](#)

- [SaveToHTMLFile](#)

- [SaveToMsgFile](#)

- [SaveToTextFile](#)

- [SaveToXMLFile](#)

TSMMAbout type

Unit

[smmsg](#)

Declaration

```
type TSMMAbout = string;
```

Description

This type is design-time only and is declared for [About](#) property that allow to receive a short information about SMMsg suite in Delphi/C++Builder IDE from Object Inspector window.

See also

[TSMMsgProperties.GetBCC](#)

- [CC](#)

See also

[TSMMsgProperties.GetBody](#).

- [HTMLBody](#).

- [RTFBody](#).

See also

[TSMMsgProperties.GetCC](#)

- [BCC](#)

See also

[TSMMsgProperties.GetHTMLBody.](#)

- [Body.](#)
- [RTFBody.](#)

See also

[TSMMSGProperties.GetMessageDate](#)

See also

[TSMMSGProperties.GetMessageID](#)

See also

[TMSGProperties.GetRecipientName](#)

- [SenderName](#)

See also

[TSMMsgProperty.GetRTFBody.](#)

- [Body.](#)
- [HTMLBody.](#)

See also

[TMSGProperties.GetSenderName](#)

- [RecipientName](#)

See also

[TMSGProperties.GetSubject](#)

- [BCC](#)
- [Body](#)
- [CC](#)
- [HTMLBody](#)
- [MessageDate](#)
- [RecipientName](#)
- [RTFBody](#)
- [SenderName](#)
- [TransportHeader](#)

See also

[TMSGProperties.GetTransportHeader](#)

See also

- [LoadFromStream](#)

LoadFromFile method example

```
yourTSMMSGFile.LoadFromFile('c:\data\request.msg')
```

See also

- [LoadFromFile](#)

LoadFromStream method example

var

Stream: TBlobStream;

i: integer;

begin

try

Stream := TBlobStream.Create(yourDataset.FieldName('yourBLOB', bmRead);

try

yourMSGFile.LoadFromStream(Stream);

finally

Stream.Free;

end;

except

on EOpenError **do** {*nothing*};

end;

end;

See also

- [SaveToHTMLFile](#)
- [SaveToMsgFile](#)
- [SaveToTextFile](#)
- [SaveToXMLFile](#)

See also

- [SaveToEMLFile](#)
- [SaveToMsgFile](#)
- [SaveToTextFile](#)
- [SaveToXMLFile](#)

See also

- [SaveToEMLFile](#)
- [SaveToHTMLFile](#)
- [SaveToTextFile](#)
- [SaveToXMLFile](#)

See also

- [SaveToEMLFile](#)
- [SaveToHTMLFile](#)
- [SaveToMsgFile](#)
- [SaveToXMLFile](#)

See also

- [SaveToEMLFile](#)
- [SaveToHTMLFile](#)
- [SaveToMsgFile](#)
- [SaveToTextFile](#)

Hierarchy

TComponent

|

[TSMMMessage](#)

See also

[TSMTNEFFile](#)

[TSMEMLFile](#)

Methods

- Key methods

~~LoadFromFile~~{linkDelphi=LoadFromFile_Method}

~~LoadFromStream~~{linkDelphi=LoadFromStream_Method}

See also

[TSMMSGFile](#)

[TSMEMLFile](#)

Methods

- Key methods

~~LoadFromFile~~{linkDelphi=LoadFromFile_Method}

~~LoadFromStream~~{linkDelphi=LoadFromStream_Method}

See also

[TSMMSGFile](#)

[TSMTNEFFile](#)

Properties

▸ Run-time only ▣ Key properties

▸ ▣ [OriginalEML](#)

Methods

■ Key methods

~~Create~~{linkDelphi=Create_Method}

~~Destroy~~{linkDelphi=Destroy_Method}

~~LoadFromFile~~{linkDelphi=LoadFromFile_Method}

~~LoadFromStream~~{linkDelphi=LoadFromStream_Method}

Events

- Key events
- [OnConvertCodepage](#)

TSMMSGConvertCodepage type

[See also](#)

Unit

[smmsg](#)

Declaration

```
type TSMMSGConvertCodepage = procedure(Sender: TObject; const
ACodePage: string; var Value: string); of object;
```

Description

This type declared for codepage conversions (for property/attribute values)

See also

[TMSGPropertyCategory](#).

See also

[TSMEMLFile.OnConvertCodepage](#)